



Features

- 6.3 ~ 18 ϕ , 125°C, 1,000 ~ 2,000 hours assured
- Chip type high temperature range, for +125°C use
- For automobile modules and other high temperature applications
- RoHS Compliance



Marking color: Black

SPECIFICATIONS

Items	Performance																				
Category Temperature Range	-40°C ~ +125°C																				
Capacitance Tolerance	±20% (at 120Hz, 20°C)																				
Leakage Current (at 20°C)	I = 0.03CV or 4 (μA) whichever is greater (after 1 minutes) Where, C = rated capacitance in μF V = rated DC working voltage in V																				
Dissipation Factor (Tan δ at 120Hz, 20°C)	<table border="1"> <tr> <th>Rated Voltage</th> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> </tr> <tr> <th>Tan δ (max)</th> <td>0.32</td> <td>0.24</td> <td>0.21</td> <td>0.18</td> <td>0.15</td> </tr> </table> <p>When the capacitance exceeds 1,000μF, 0.02 shall be added every 1,000μF increase.</p>	Rated Voltage	10	16	25	35	50	Tan δ (max)	0.32	0.24	0.21	0.18	0.15								
Rated Voltage	10	16	25	35	50																
Tan δ (max)	0.32	0.24	0.21	0.18	0.15																
Low Temperature Characteristics (at 120Hz)	<p>Impedance ratio shall not exceed the values given in the table below.</p> <table border="1"> <tr> <th colspan="2">Rated Voltage</th> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> </tr> <tr> <th rowspan="2">Impedance Ratio</th> <th>Z(-25°C)/Z(+20°C)</th> <td>6</td> <td>5</td> <td>4</td> <td>3</td> <td>3</td> </tr> <tr> <th>Z(-40°C)/Z(+20°C)</th> <td>12</td> <td>8</td> <td>6</td> <td>4</td> <td>4</td> </tr> </table>	Rated Voltage		10	16	25	35	50	Impedance Ratio	Z(-25°C)/Z(+20°C)	6	5	4	3	3	Z(-40°C)/Z(+20°C)	12	8	6	4	4
Rated Voltage		10	16	25	35	50															
Impedance Ratio	Z(-25°C)/Z(+20°C)	6	5	4	3	3															
	Z(-40°C)/Z(+20°C)	12	8	6	4	4															
Endurance	<table border="1"> <tr> <th>Test Time</th> <td>1,000 Hrs for $\phi D \leq 8 \times 6.5\text{mm}$ 2,000 Hrs for $\phi D \geq 8 \times 10\text{mm}$</td> </tr> <tr> <th>Capacitance Change</th> <td>Within ±30% of initial value</td> </tr> <tr> <th>Dissipation Factor</th> <td>Less than 300% of specified value</td> </tr> <tr> <th>Leakage Current</th> <td>Within specified value</td> </tr> </table> <p>* The above specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage applied for 1,000 / 2,000 hours at 125°C.</p>	Test Time	1,000 Hrs for $\phi D \leq 8 \times 6.5\text{mm}$ 2,000 Hrs for $\phi D \geq 8 \times 10\text{mm}$	Capacitance Change	Within ±30% of initial value	Dissipation Factor	Less than 300% of specified value	Leakage Current	Within specified value												
Test Time	1,000 Hrs for $\phi D \leq 8 \times 6.5\text{mm}$ 2,000 Hrs for $\phi D \geq 8 \times 10\text{mm}$																				
Capacitance Change	Within ±30% of initial value																				
Dissipation Factor	Less than 300% of specified value																				
Leakage Current	Within specified value																				
Shelf Life Test	<table border="1"> <tr> <th>Test Time</th> <td>1,000 Hrs</td> </tr> <tr> <th>Capacitance Change</th> <td>Within ±30% of initial value</td> </tr> <tr> <th>Dissipation Factor</th> <td>Less than 300% of specified value</td> </tr> <tr> <th>Leakage Current</th> <td>Within specified value</td> </tr> </table> <p>* The above specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours at 125°C without voltage applied.</p>	Test Time	1,000 Hrs	Capacitance Change	Within ±30% of initial value	Dissipation Factor	Less than 300% of specified value	Leakage Current	Within specified value												
Test Time	1,000 Hrs																				
Capacitance Change	Within ±30% of initial value																				
Dissipation Factor	Less than 300% of specified value																				
Leakage Current	Within specified value																				
Ripple Current & Frequency Multipliers	<table border="1"> <tr> <th rowspan="3">Cap.(μF)</th> <th colspan="4">Freq.(Hz)</th> </tr> <tr> <th>50</th> <th>120</th> <th>1k</th> <th>10k up</th> </tr> <tr> <td>Under 330</td> <td>0.80</td> <td>1.0</td> <td>1.25</td> <td>1.40</td> </tr> <tr> <td>300 < C ≤ 4,700</td> <td>0.85</td> <td>1.0</td> <td>1.20</td> <td>1.30</td> </tr> </table>	Cap.(μF)	Freq.(Hz)				50	120	1k	10k up	Under 330	0.80	1.0	1.25	1.40	300 < C ≤ 4,700	0.85	1.0	1.20	1.30	
Cap.(μF)	Freq.(Hz)																				
	50		120	1k	10k up																
	Under 330	0.80	1.0	1.25	1.40																
300 < C ≤ 4,700	0.85	1.0	1.20	1.30																	

DIAGRAM OF DIMENSIONS

Fig. 1





Fig. 2




LEAD SPACING AND DIAMETER

Unit: mm


ϕD	L	A	B	C	W	P ± 0.2	Fig. No.
6.3	5.7±0.3	6.6	6.6	7.4	0.5 ~ 0.8	2.0	1
6.3	7.7±0.3	6.6	6.6	7.4	0.5 ~ 0.8	2.0	1
8	6.5±0.3	8.4	8.4	9.2	0.5 ~ 0.8	2.3	1
8	10±0.5	8.4	8.4	9.2	0.7 ~ 1.1	3.1	1
10	10±0.5	10.4	10.4	11.2	0.7 ~ 1.1	4.7	1
12.5	13.5±0.5	13.0	13.0	15.0	1.1 ~ 1.4	4.4	2
12.5	16±0.5	13.0	13.0	15.0	1.1 ~ 1.4	4.4	2
16	16.5±0.5	17.0	17.0	19.0	1.1 ~ 1.4	6.4	2
18	16.5±0.5	19.0	19.0	21.0	1.1 ~ 1.4	6.4	2

MARKING


$\phi D = 6.3 \text{ mm}$



$\phi D = 8 \sim 10 \text{ mm}$



$\phi D \geq 12.5 \text{ mm}$



DIMENSION & PERMISSIBLE RIPPLE CURRENT

Dimension: $\phi D \times L(\text{mm})$

Ripple Current: mA/rms at 120 Hz, 125°C

μF	V. DC Contents	10V (1A)		16V (1C)		25V (1E)		35V (1V)		50V (1H)	
		$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA
22	220							6.3×5.7	50	8×6.5	75
33	330			6.3×5.7	50	6.3×5.7	50	6.3×7.7	70	8×10	130
47	470			6.3×7.7	70	6.3×7.7	70	8×6.5	75	8×10	130
68	680	6.3×5.7	50	8×6.5	75	8×6.5	75	8×10	130	10×10	180
100	101	8×6.5	75	8×6.5	75	8×10	130	10×10	180	12.5×13.5	357
220	221	8×10	130	10×10	180	10×10	180	12.5×13.5	357	12.5×16	400
330	331	8×10	130	12.5×13.5	480	12.5×13.5	480	16×16.5	650	16×16.5	650
470	471	12.5×13.5	480	12.5×13.5	480	12.5×13.5	480	16×16.5	650	16×16.5	650
680	681	12.5×13.5	480	12.5×13.5	480	12.5×16	585	16×16.5	650	18×16.5	855
1,000	102	12.5×16	585	12.5×16	585	16×16.5	650	18×16.5	855		
1,500	152	12.5×16	585	16×16.5	650	18×16.5	855				
2,200	222	16×16.5	650	18×16.5	855						
3,300	332	18×16.5	855								
4,700	472	18×16.5	855								