

Plug Fuses

125 VAC • Time-Delay • 1/4 – 30 Amperes



Edison-base Plug fuses

T00 Fuses are dual-element time-delay Edison-base fuses designed for motor and motor branch circuit protection; also suitable for all general purpose circuits. Use for replacement purposes only.

Ampere Ratings

3/10	1 1/8	2 1/4	4	7	15
4/10	1 1/4	2 1/2	4 1/2	8	20
1/2	1 5/10	2 5/10	5	9	25
5/10	1 5/10	3	5 5/10	10	30
5/10	1 5/10	3 1/10	6	12	
1	2	3 1/2	6 1/4	14	

TLO Fuses are medium time-delay Edison-base fuses designed for general purpose branch circuit protection. See T00 and S00 fuses for motor protection. Use for replacement purposes only.

Ampere Ratings

15	20	25	30
----	----	----	----

Littelfuse Plug fuses provide overcurrent protection to general purpose circuits and small motor loads. Edison-base Plug fuses (T00 and TLO series) feature metal threads similar to incandescent lamp bases. Type S Plug fuses (S00 and SLO series) utilize a nonmetallic threaded base and must be used with Type S adapters (SAO series). The National Electrical Code permits Edison-base Plug fuses to be used for replacement purposes only. Type S fuses and adapters prevent shunting open fuses and over-fusing.

SAO Adapter Rating	Accepts Fuse Ratings:	Other S00 Fuse Ratings Which Fit
SAO 1	3/10 – 1	—
SAO 1 1/4	1 1/8, 1 1/4	3/10 – 1
SAO 1 5/10	1 5/10, 1 5/10	3/10 – 1 1/4
SAO 2	1 5/10, 2	—
SAO 2 1/2	2 1/4, 2 1/2	1 5/10, 2
SAO 3 1/10	2 5/10, 3 1/10	1 5/10 – 2 1/2
SAO 4	3 1/2, 4	—
SAO 5	4 1/2, 5	3 1/2, 4
SAO 6 1/4	3 1/2, 6 1/4	3 1/2 – 5
SAO 8	7, 8	—
SAO 15	7, 8, 9, 10, 12, 14, 15	7, 8, 9, 10
SAO 20	20 only	—
SAO 30	20, 25, 30	—

Specifications

Voltage Rating: 125 VAC
Interrupting Rating: 10,000 amperes rms symmetrical
Approvals: UL Listed Plug Fuses, Standard UL 248-11

Note: See NEC Article 240-V for additional information on Plug fuse applications.

Type S Plug fuses

S00 Fuses are dual-element time-delay Type S fuses designed for motor and motor branch circuit protection; also suitable for all general purpose circuits.

Ampere Ratings

1/4	1	2	3 1/2	6 1/4	14
3/10	1 1/8	2 1/4	4	7	15
4/10	1 1/4	2 1/2	4 1/2	8	20
1/2	1 5/10	2 5/10	5	9	25
5/10	1 5/10	3	5 5/10	10	30
5/10	1 5/10	3 1/10	6	12	

SLO Fuses are medium time-delay Type S fuses for general purpose branch circuit protection.

Ampere Ratings

15	20	25	30
----	----	----	----