

HM10480-15, HM10480F-15

16,384-words × 1-bit Fully Decoded Random Access Memory

The HM10480 is ECL 10K compatible, 16,384-words × 1-bit, read/write random access memory developed for high speed systems such as scratch pads and control/buffer storages.

The fabrication process uses the Hitachi's low capacitance, oxide isolation method with double metalization.

The HM10480 is encapsulated in cerdip-20 pin and flat 20-pin package, compatible with Fairchild's F10480.

FEATURES


- 16,384-words × 1-bit organization
- Fully compatible with 10K ECL level
- Address access time: 15ns (max)
- Write pulse width: 15ns (min)
- Low power dissipation: 0.06mW/bit
- Output obtainable by wired-OR (open emitter)

TRUTH TABLE

$\overline{CS}$	Input		Output	Mode
	$\overline{WE}$	Din		
H	X	X	L	Not Selected
L	L	L	L	Write "0"
L	L	H	L	Write "1"
L	H	X	Dout*	Read

Notes) X : Irrelevant
* : Read Out Noninvert

BLOCK DIAGRAM




ABSOLUTE MAXIMUM RATINGS (Ta = 25°C)

Item	Symbol	Rating	Unit
Supply Voltage	V_{EE} to V_{CC}	+0.5 to -7.0	V
Input Voltage	V_{in}	+0.5 to V_{EE}	V
Output Current	I_{out}	-30	mA
Storage Temperature	T_{stg}	-65 to +150	°C
Storage Temperature	$T_{stg}(\text{Bias})^*$	-55 to +125	°C


* Under Bias

HM10480-15




(DG-20N)

HM10480F-15



(FG-20D)

PIN ARRANGEMENT



Hitachi America Ltd. • 2210 O'Toole Ave. • San Jose, CA 95131 • (408) 435-8300

■ ELECTRICAL CHARACTERISTICS

● DC CHARACTERISTICS ($V_{EE} = -5.2V$, $R_L = 50\Omega$ to $-2.0V$, $T_a = 0$ to $+75^\circ C$, air flow exceeding 2m/sec)

Item	Symbol	Test Condition		min (B)	typ	max (A)	Unit	
Output Voltage	V_{OH}	$V_{IN} = V_{IH}$ or V_{IL}		0°C	-1000	—	-840	mV
				+25°C	-960	—	-810	
				+75°C	-900	—	-720	
	V_{OL}			0°C	-1870	—	-1665	
				+25°C	-1850	—	-1650	
				+75°C	-1830	—	-1625	
Output Threshold Voltage	V_{OHc}	$V_{IN} = V_{IH}$ or V_{IL}		0°C	-1020	—	—	mV
				+25°C	-980	—	—	
				+75°C	-920	—	—	
	V_{OLc}			0°C	—	—	-1645	
				+25°C	—	—	-1630	
				+75°C	—	—	-1605	
Input Voltage	V_{IH}	Guaranteed Input Voltage High for All Inputs		0°C	-1145	—	-840	mV
				+25°C	-1105	—	-810	
				+75°C	-1045	—	-720	
	V_{IL}	Guaranteed Input Voltage Low for All Inputs		0°C	-1870	—	-1490	
				+25°C	-1850	—	-1475	
				+75°C	-1830	—	-1450	
Input Current	I_{IH}	$V_{IN} = V_{IH}$	$V_{IN} = V_{IL}$	0 to +75°C	—	—	220	μA
	I_{IL}	CS		0 to +75°C	0.5	—	170	
		Others			-50	—	—	
Supply Current	I_{EX}	All Input and Output Open, Test Pin 10		$T_a = 0^\circ\text{C}$	-240	-220	—	mA
				$T_a = 75^\circ\text{C}$	—	-200	—	

● AC CHARACTERISTICS ($V_{EE} = -5.2V \pm 5\%$, $T_a = 0$ to $+75^\circ C$, air flow exceeding 2m/sec)

1. READ MODE

Item	Symbol	Test Condition	min	typ	max	Unit
Chip Select Access Time	t_{ACS}		2	—	8	ns
Chip Select Recovery Time	t_{RCS}		2	—	8	ns
Address Access Time	t_{AA}		3	12	15	ns

2. WRITE MODE

Item	Symbol	Test Condition	min	typ	max	Unit
Write Pulse Width	t_W	$t_{WSA} = 3ns$	15	—	—	ns
Data Setup Time	t_{WSD}		2	—	—	ns
Data Hold Time	t_{WHD}		3	—	—	ns
Address Setup Time	t_{WSA}	$t_W = 15ns$	3	—	—	ns
Address Hold Time	t_{WHA}		2	—	—	ns
Chip Select Setup Time	t_{WSCS}		3	—	—	ns
Chip Select Hold Time	t_{WHCS}		3	—	—	ns
Write Disable Time	t_{WD}		—	—	12	ns
Write Recovery Time	t_{WR}		—	—	17	ns



