

DESCRIPTION

The HY5116400B is the new generation and fast dynamic RAM organized 4,194,304 x 4-bit. The HY5116400B utilizes Hyundai's CMOS silicon gate process technology as well as advanced circuit techniques to provide wide operating margins to the users. Multiplexed address inputs permit the HY5116400B to be packaged in standard 24/26 pin plastic SOJ, TSOP-II and Reverse TSOP-II.

The package size provides high system bit densities and is compatible with widely available automated testing and insertion equipments. System oriented feature includes single power supply of 5V $\pm$ 10% tolerance and direct interfacing capability with high performance logic families such as Schottky TTL.

FEATURES

• Low power dissipation

Max. battery back-up 3.3mW (SL-part)

Max. CMOS standby 2.2mW (SL-part)
5.5mW

Max. TTL standby 11.0mW

Max. operating

Speed	Power
50	605mW
60	495mW
70	440mW

• Single power supply of 5V $\pm$ 10%

• TTL compatible inputs and outputs

• Fast access and cycle time

Speed	t _{RAC}	t _{CAC}	t _{PC}
50	50ns	13ns	35ns
60	60ns	15ns	40ns
70	70ns	18ns	45ns

• Fast page mode operation

• Multi-bit test capability

• Read-Modify-Write capability

• CAS-before-RAS, RAS-only, Hidden refresh and Self Refresh capability



• 4096 refresh cycles / 256ms (SL-part)

4096 refresh cycles / 64ms


PIN DESCRIPTION

RAS	Row Address Strobe
CAS	Column Address Strobe
WE	Write Enable
OE	Output Enable
A0-A11	Address input
DQ0-DQ3	Data Input/Output
Vcc	Power (+5V)
Vss	Ground

PIN CONNECTION



BLOCK DIAGRAM



4675088 0004520 6T3

This document is a general product description and is subject to change without notice. Hyundai Electronics does not assume any responsibility for use of circuits described. No patent licences are implied.

1AD42-00-MAY95

ABSOLUTE MAXIMUM RATING

SYMBOL	PARAMETER	RATING	UNIT
TA	Ambient Temperature	0 to 70	°C
TSTG	Storage Temperature	-55 to 150	°C
VIN, VOUT	Voltage on Any Pin Relative to Vss	-1.0 to 7.0	V
VCC	Voltage on VCC Relative to Vss	-1.0 to 7.0	V
IOS	Short Circuit Output Current	50	mA
PD	Power Dissipation	1.0	W
TSOLDER	Soldering Temperature • Time	260 • 10	°C • sec

NOTE: Operation at or above Absolute Maximum Ratings can adversely affect device reliability.

RECOMMENDED DC OPERATING CONDITIONS

(TA = 0°C to 70°C)

SYMBOL	PARAMETER	MIN.	TYP.	MAX.	UNIT
VCC	Power Supply Voltage	4.5	5.0	5.5	V
VIH	Input High Voltage	2.4	-	Vcc+1.0	V
VIL	Input Low Voltage	-1.0	-	0.8	V

NOTE: All Voltages are referenced to Vss.

DC CHARACTERISTICS

(TA=0°C to 70°C, VCC=5V±10%, VSS=0V, unless otherwise noted.)

SYMBOL	PARAMETER	TEST CONDITIONS	SPEED/ POWER	MIN.	MAX.	UNIT	NOTE
ILI	Input Leakage Current (Any Input Pins)	VSS ≤ VIN ≤ VCC+1.0, All other pins not under test = VSS		-10	10	mA	
ILO	Output Leakage Current (High impedance State)	VSS ≤ VOUT ≤ VCC RAS & CAS at VIH		-10	10	μA	
ICC1	VCC Supply Current, Operating	trc = trc (min.)	50 60 70	- - -	110 90 80	mA	1,2,3
ICC2	VCC Supply Current, TTL Standby	RAS & CAS at VIH(min.), other inputs ≥ VSS		-	2	mA	
ICC3	VCC Supply Current, RAS-only refresh	trc = trc (min.)	50 60 70	- - -	110 90 80	mA	1,3
ICC4	VCC Supply Current, Fast Page mode	tpc = tpc (min.)	50 60 70	- - -	80 70 60	mA	1,2,3
ICC5	VCC Supply Current, CMOS Standby	RAS & CAS ≥ VCC-0.2V	SL-part	-	1 0.4	mA	5
ICC6	VCC Supply Current, CAS-before- RAS refresh	trc = trc (min.)	50 60 70	- - -	110 90 80	mA	1,3
ICC7	VCC Supply Current, Battery Back up (SL-part only)	trc = 62.5μs, CAS = CBR cycling or 0.2V, WE = VCC-0.2V, A0-A11 = VCC-0.2V or 0.2V, DQ0-D Q3 = 0.2V, VCC-0.2V or open	trc ≤ 300ns trc ≤ 1 μs	- -	350 600	μA	1,4,5
ICC8	VCC Supply Current Self Refresh(SL-part only)	RAS & CAS ≤ 0.2V OE & WE & A0-A11= VCC-0.2V or 0.2V, DQ0-DQ3=VCC-0.2V,0.2V or open		-	300	μA	5
VOL	Output Low Voltage	IOL = 4.2mA		-	0.4	V	
VOH	Output High Voltage	IOH = -5.0mA		2.4	-	V	

NOTE :

1. ICC1, ICC3, ICC4, ICC6 and ICC7 depend on cycle rates.
2. ICC1, ICC3, ICC4 and ICC6 depend on output loading. Specified values are obtained with the output open.
3. ICC is specified as average current. ICC1, ICC3, ICC6, Address can be changed maximum two times while RAS=VIL. ICC4, Address can be changed maximum once while CAS=VIH.
4. trc(max.)=1μs is only applied to refresh of battery backup but trc(max.)=10μs is applied to normal functional operation .
5. ICC5(max.) =0.4mA, ICC7 and ICC8 are applied to SL-parts only.

AC CHARACTERISTICS

(TA=0°C to 70°C, Vcc=5V±10%, Vss=0V, unless otherwise noted.)

#	SYMBOL	PARAMETER	HY5116400BJ/T/R/SLJ/SLT/SLR						UNIT	NOTE
			- 50		- 60		- 70			
			MIN.	MAX.	MIN.	MAX.	MIN.	MAX.		
1	tRC	Random Read or Write Cycle Time	90	-	110	-	130	-	ns	
2	tRWC	Read-Modify-Write Cycle Time	140	-	160	-	180	-	ns	
3	tPC	Fast Page Mode cycle Time	35	-	40	-	45	-	ns	
4	tPRWC	Fast Page Mode Read-Modify-write cycle Time	80	-	85	-	90	-	ns	
5	tRAC	Access Time form RAS	-	50	-	60	-	70	ns	4,9,10
6	tCAC	Access Time from CAS	-	13	-	15	-	18	ns	4,9
7	tAA	Access Time from Column Address	-	25	-	30	-	35	ns	4,10
8	tCPA	Access Time from CAS Precharge	-	30	-	35	-	40	ns	4
9	tCLZ	CAS to Output Low Impedance	0	-	0	-	0	-	ns	
10	tOFF	Output Buffer Turn-off Delay	0	10	0	13	0	15	ns	
11	tT	Transition Time (Rise and Fall)	3	50	3	50	3	50	ns	3
12	tRP	RAS Precharge Time	30	-	40	-	50	-	ns	
13	tRAS	RAS Pulse Width	50	10K	60	10K	70	10K	ns	
14	tRASP	RAS Pulse Width (Fast Page Mode)	50	200K	60	200K	70	200K	ns	
15	tRSH	RAS Hold Time	13	-	15	-	18	-	ns	
16	tCSH	CAS Hold Time	50	-	60	-	70	-	ns	
17	tCAS	CAS Pulse width	13	10K	15	10K	18	10K	ns	
18	tRCD	RAS to CAS Delay	18	37	20	45	20	52	ns	9
19	tRAD	RAS to Column Address Delay Time	15	30	15	35	15	40	ns	10
20	tCRP	CAS to RAS Precharge Time	5	-	5	-	5	-	ns	
21	tCP	CAS Precharge Time	8	-	10	-	10	-	ns	
22	tASR	Row Address Set-up Time	0	-	0	-	0	-	ns	
23	tRAH	Row Address Hold time	8	-	10	-	10	-	ns	
24	tASC	Column Address Set-up Time	0	-	0	-	0	-	ns	
25	tCAH	Column Address Hold Time	10	-	10	-	10	-	ns	
26	tAR	Column Address Hold Time from RAS	50	-	50	-	50	-	ns	
27	tRAL	Column Address to RAS Lead Time	25	-	30	-	35	-	ns	
28	tRCS	Read Command Set-up Time	0	-	0	-	0	-	ns	
29	tRCH	Read Command Hold Time Referenced to CAS	0	-	0	-	0	-	ns	6
30	tRRH	Read Command Hold Time Referenced to RAS	0	-	0	-	0	-	ns	6
31	tWCH	Write Command Hold Time	8	-	10	-	10	-	ns	
32	tWCR	Write Command Hold Time from RAS	45	-	50	-	55	-	ns	
33	tWP	Write Command Pulse Width	8	-	10	-	10	-	ns	
34	tRWL	Write Command to RAS Lead Time	13	-	18	-	18	-	ns	
35	tCWL	Write Command to CAS Lead Time	13	-	15	-	18	-	ns	
36	tDS	Data-In Set-up Time	0	-	0	-	0	-	ns	7
37	tDH	Data-In Hold Time	10	-	10	-	10	-	ns	7
38	tDHR	Data-In Hold Time Referenced to RAS	50	-	50	-	55	-	ns	
39	tREF	Refresh Period (4096)	-	64	-	64	-	64	ms	12
		SL-part	-	256	-	256	-	256		11
40	tWCS	Write Command Set-up Time	0	-	0	-	0	-	ns	8

AC CHARACTERISTICS

(continued)

#	SYMBOL	PARAMETER	HY5116400BJ/T/R/SLJ/SLT/SLR						UNIT	NOTE
			- 50		- 60		- 70			
			MIN.	MAX.	MIN.	MAX.	MIN.	MAX.		
41	tCWD	CAS to WE Delay Time	33	-	35	-	43	-	ns	8
42	tRWD	RAS to WE Delay Time	70	-	83	-	95	-	ns	8
43	tAWD	Column Address to WE Delay Time	45	-	53	-	60	-	ns	8
44	tCSR	CAS Set-up Time (CBR Cycle)	5	-	5	-	5	-	ns	
45	tCHR	CAS Hold Time (CBR Cycle)	10	-	10	-	10	-	ns	
46	tRPC	RAS to CAS Precharge Time	0	-	0	-	0	-	ns	
47	tCPT	CAS Precharge Time (CBR Counter Test)	15	-	20	-	25	-	ns	
48	tROH	RAS Hold Time Referenced to OE	0	-	0	-	0	-	ns	
49	tOEA	OE Access Time	-	15	-	18	-	20	ns	
50	tOED	OE to Data Delay	13	-	15	-	15	-	ns	
51	tOEZ	Output Buffer Turn Off Delay Time from OE	0	10	0	13	0	15	ns	
52	tOEH	OE Command Hold Time	10	-	10	-	10	-	ns	
53	tCPWD	WE Delay Time from CAS Precharge	30	-	35	-	40	-	ns	8
54	tRHCP	RAS Hold Time from CAS Precharge	30	-	35	-	40	-	ns	
55	tWRP	WE to RAS Precharge Time(CBR Cycle)	10	-	10	-	10	-	ns	
56	tWRH	WE to RAS Hold Time(CBR Cycle)	10	-	10	-	10	-	ns	
57	tWTS	Write Command Set-up Time (Test Mode In)	10	-	10	-	10	-	ns	
58	tWTH	Write Command Hold Time (Test Mode In)	10	-	10	-	10	-	ns	
59	tRASS	RAS Pulse Width (Self Refresh)	100	-	100	-	100	-	μs	
60	tRPS	RAS Precharge Time (Self Refresh)	90	-	110	-	130	-	ns	
61	tCHS	CAS Hold Time from RAS (Self Refresh)	- 50	-	- 50	-	- 50	-	ns	

4675088 0004524 249

AC CHARACTERISTICS IN TEST MODE

NOTE 13

#	SYMBOL	PARAMETER	HY5116400BJ/T/R/SLJ/SLT/SLR						UNIT	NOTE
			- 50		- 60		- 70			
			MIN.	MAX.	MIN.	MAX.	MIN.	MAX.		
1	tRC	Random Read or Write Cycle Time	95	-	115	-	135	-	ns	
2	tRWC	Read-Modify-Write Cycle Time	140	-	160	-	185	-	ns	
3	tPC	Fast Page Mode Cycle Time	40	-	45	-	50	-	ns	
4	tPRWC	Fast Page Mode Read-Modify-Write Cycle Time	60	-	65	-	75	-	ns	
5	tRAC	Access Time from RAS	-	55	-	65	-	75	ns	4,9,10
6	tCAC	Access Time from CAS	-	18	-	20	-	23	ns	4,9
7	tAA	Access Time from Column Address	-	30	-	35	-	40	ns	4,10
8	tCPA	Access Time from CAS Precharge		35	-	40	-	45	ns	4
13	tRAS	RAS Pulse Width	55	10K	65	10K	75	10K	ns	
14	trasp	RAS Pulse Width (Fast Page Mode)	55	200K	65	200K	75	200K	ns	
15	tRSH	RAS Hold Time	18	-	20	-	23	-	ns	
16	tCSH	CAS Hold Time	55	-	65	-	75	-	ns	
17	tCAS	CAS Pulse Width	18	10K	20	10K	23	10K	ns	
27	tRAL	Column Address to RAS Lead Time	30	-	35	-	40	-	ns	
41	tCWD	CAS to WE Delay Time	18	-	20	-	23	-	ns	8
42	tRWD	RAS to WE Delay Time	55	-	65	-	75	-	ns	8
43	tAWD	Column Address to WE Delay Time	30	-	35	-	40	-	ns	8
49	tOEA	OE Access Time	-	20	-	20	-	25	ns	
50	tOED	OE to Data Delay	20	-	20	-	25	-	ns	
52	tOEH	OE Command Hold Time	20	-	20	-	25	-	ns	

NOTE:

1. An initial pause of 200 μ s is required after power-up followed by 8 refresh ($\overline{\text{RAS}}$ only refresh or $\overline{\text{CAS}}$ before RAS refresh) cycle before proper device operation is achieved.
2. If $\text{RAS}=\text{Vss}$ during power-up, the device could begin an active cycle. These condition results in higher current than necessary which is demanded from the power supply during power-up. It is recommended that RAS and CAS track with Vcc during power-up or be held at a valid VIH in order to minimize the power-up current.
3. VIH(min.) and VIL(max.) are reference levels for measuring timing of input signals. Also, transition times are measured between VIH(min.) and VIL(max.), and are assumed to be 5ns for all inputs.
4. Measured at VOH=2.4V and VOL=0.4V with a load equivalent to 2 TTL loads and 100pF.
5. toFF(max.) and tOEZ define the time at which the output achieves the open circuit condition and is not referenced to output voltage levels.
6. Either trCH or trRH must be satisfied for a read cycle.
7. These parameters are referenced to $\overline{\text{CAS}}$ leading edge in early write cycles and to $\overline{\text{WE}}$ leading edge in Read-Modify-Write cycles.
8. twCS, trWD, tcWD, tAWD and tCPWD are not restrictive operating parameters. They are included in the data sheet as electrical characteristics only. If twCS $\geq$ twCS(min.), the cycle is an early write cycle and data out pin will remain open circuit (high impedance) through the entire cycle. If trWD $\geq$ trWD(min.), tcWD $\geq$ tcWD(min.), tAWD $\geq$ tAWD(min.), and tCPWD $\geq$ tCPWD(min.), the cycle is a Read-Modify-Write cycle and data out will contain data read from the selected cell. If neither of the above sets of conditions is satisfied, the condition of the data out (at access time) is indeterminated.
9. Operation within the trCD(max.) limit insures that trAC(max.) can be met. trCD(max.) is specified as a reference point only. If trCD is greater than the specified trCD(max.) limit, then access time is controlled by tCAC.
10. Operation within the trAD(max.) limit insures that trAC(max.) can be met. trAD(max.) is specified as a reference point only. If trAD is greater than the specified trAD(max.) limit, then access time is controlled by tAA.
11. tREF(max.)=256ms is applied to SL-Parts.
12. A burst of 4096 $\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ refresh cycles must be executed within 64ms(256ms for SL-part) after exiting self refresh.
13. These specifications are applied to the test Mode.


CAPACITANCE

(TA=25°C, VCC=5V $\pm$ 10%, VSS=0V, f=1MHZ, unless otherwise noted.)

SYMBOL	PARAMETER	TYP.	MAX.	UNIT
CIN1	Input Capacitance (A0-A11)	-	5	pF
CIN2	Input Capacitance (RAS, CAS, WE, OE)	-	7	pF
CDQ	Data Input/Output Capacitance (DQ0-DQ3)	-	7	pF

4675088 0004526 011

READ CYCLE




The timing diagram illustrates the relationship between several control and data signals for the 64K1602 device. The signals shown are RAS, CAS, AO-11, WE, OE, and DQ0-3. The diagram includes various timing parameters such as $t_{RC}(1)$, $t_{RP}(12)$, $t_{RCD}(18)$, $t_{RSH}(19)$, $t_{RCP}(20)$, $t_{RAD}(18)$, $t_{RAH}(23)$, $t_{ASQ}(24)$, $t_{CAH}(25)$, $t_{RAL}(27)$, $t_{OWL}(35)$, $t_{RWL}(34)$, $t_{WP}(33)$, $t_{OE}(32)$, $t_{OED}(50)$, $t_{DS}(36)$, and $t_{DH}(37)$. The signals are shown as waveforms with high (VH) and low (VL) levels, and some signals like AO-11, WE, OE, and DQ0-3 are shown as shaded regions indicating specific states or data validity.

[illegible][illegible]


NOTE : OE and WE = "H" or "L"

CAS-BEFORE-RAS REFRESH CYCLE




NOTE : A0-11 and OE = "H" or "L"


HIDDEN REFRESH CYCLE (READ)



HIDDEN REFRESH CYCLE (WRITE)



CAS-BEFORE-RAS SELF REFRESH CYCLE




NOTE : A0-11, OE and WE = "H" or "L"

TEST MODE


The HY5116400B is a DRAM organized 4,194,304 x 4-bit. It is internally organized 1,048,576 x 16-bit. In Test Mode, data are written into 16 sectors (Each is composed of 1M bits) in parallel and retrieved the same way. Column address A0 and A1 are not used. If upon reading, 4-bit data from 4 sectors connected to one DQ pin are equal (all "1"s or "0"s), the DQ pin indicates a "1". If they are not equal, the DQ pin indicates a "0". Belowing shows the timing diagram of the HY5116400B to enter Test Mode. In Test Mode, the 4M x 4 DRAM can be tested as if it were a 1M x 4 DRAM. WE, CAS-before-RAS cycle (Test Mode In Cycle) puts the HY5116400B into Test Mode and CAS-before-RAS or RAS-only refresh cycle puts it back into Normal Model. In Test Mode, WE, CAS-before-RAS cycle shall be used for the refresh operation. The Test Mode function reduces test time (1/4 in case of N test pattern).

TEST MODE IN CYCLE





PACKAGE INFORMATION


300 mil 24/26 pin Small Outline J-form Package (J)





UNIT : INCH(mm)



300 mil 24/26 pin Thin Small Outline Package (T) (R)



UNIT : INCH(mm)



ORDERING INFORMATION

PART NUMBER	SPEED	POWER	PACKAGE
HY5116400BJ	50/60/70		SOJ
HY5116400BSLJ	50/60/70	SL-part	SOJ
HY5116400BT	50/60/70		TSOP-II
HY5116400BSLT	50/60/70	SL-part	TSOP-II
HY5116400BR	50/60/70		TSOP-II(R)
HY5116400BSLR	50/60/70	SL-part	TSOP-II(R)