

TOSHIBA TRANSISTOR SILICON NPN TRIPLE DIFFUSED TYPE (PCT PROCESS)

2SC2230, 2SC2230A


HIGH VOLTAGE GENERAL AMPLIFIER APPLICATIONS.
 COLOR TV CLASS B SOUND OUTPUT APPLICATIONS.

Unit in mm

- High Voltage : $V_{CEO} = 180V$ (2SC2230A)
- High DC Current Gain.

MAXIMUM RATINGS ($T_a = 25^\circ C$)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	V_{CBO}	200	V
Collector-Emitter Voltage	V_{CEO}	160	V
		180	
Emitter-Base Voltage	V_{EBO}	5	V
Collector Current	I_C	100	mA
Base Current	I_B	50	mA
Collector Power Dissipation	P_C	800	mW
Junction Temperature	T_j	150	$^\circ C$
Storage Temperature Range	T_{stg}	-55~150	$^\circ C$



JEDEC TO-92MOD

EIAJ —

TOSHIBA 2-5J1A

Weight : 0.36g

ELECTRICAL CHARACTERISTICS ($T_a = 25^\circ C$)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I_{CBO}	$V_{CB} = 200V, I_E = 0$	—	—	0.1	μA
Emitter Cut-off Current	I_{EBO}	$V_{EB} = 5V, I_C = 0$	—	—	0.1	μA
DC Current Gain	$h_{FE} (1)$ (Note)	$V_{CE} = 10V, I_C = 10mA$	120	—	400	
	$h_{FE} (2)$	$V_{CE} = 10V, I_C = 50mA$	80	—	—	
Collector-Emitter Saturation Voltage	$V_{CE} (sat)$	$I_C = 50mA, I_B = 5mA$	—	—	0.5	V
Base-Emitter Voltage	V_{BE}	$V_{CE} = 10V, I_C = 1mA$	0.50	0.60	0.70	V
Transition Frequency	f_T	$V_{CE} = 10V, I_C = 10mA$	50	—	—	MHz
Collector Output Capacitance	C_{ob}	$V_{CB} = 10V, I_E = 0, f = 1MHz$	—	—	7.0	pF

Note : $h_{FE} (1)$ Classification Y : 120~240, GR : 200~400

961001EAA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

