

1. SCOPE

1.1 Scope. This drawing describes device requirements for class B microcircuits in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices".

1.2 Part number. The complete part number shall be as shown in the following example:

5962-86860	01	E	X
┆	┆	┆	┆
┆	┆	┆	┆
┆	┆	┆	┆
┆	┆	┆	┆
Drawing number	Device type (1.2.1)	Case outline (1.2.2)	Lead finish per MIL-M-38510

1.2.1 Device type. The device type shall identify the circuit function as follows:

Device type	Generic number	Circuit function
01	HA-4902	Precision quad comparator

1.2.2 Case outlines. The case outlines shall be as designated in appendix C of MIL-M-38510, and as follows:

Outline letter	Case outline
E	D-2 (16-lead, .840" X .310" X .200"), dual-in-line package
2	C-2 (20-terminal, .358" X .358" X .100"), square chip carrier package

1.3 Absolute maximum ratings.

Voltage between +V and -V terminals - - - - -	33 V dc
Differential input voltage - - - - -	±15 V dc
Output short-circuit duration - - - - -	Indefinite 1/
Peak output current - - - - -	±50 mA
Storage temperature range - - - - -	-65°C to +150°C
Maximum power dissipation (P _D):	
Case E - - - - -	1.33 W 2/
Case 2 - - - - -	1.32 W 3/
Lead temperature (soldering, 10 seconds) - - - - -	+275°C
Thermal resistance, junction-to-case (θ _{JC}) - - - - -	See MIL-M-38510, appendix C
Thermal resistance, junction-to-ambient (θ _{JA}):	
Case E - - - - -	75°C/W
Case 2 - - - - -	76°C/W
Junction temperature (T _J) - - - - -	+175°C

1.4 Recommended operating conditions.

Positive supply voltage (+V) - - - - -	+15 V dc
Negative supply voltage (-V) - - - - -	-15 V dc
Logic supply voltage (+V _L) - - - - -	+5.0 V dc
Logic reference voltage (-V _L) - - - - -	0 V dc
Ambient temperature range (T _A) - - - - -	-55°C to +125°C

1/ One amplifier shorted to ground.

2/ Derate linearly above T_A = +75°C at 13.4 mW/°C.

3/ Derate linearly above T_A = +75°C at 13.1 mW/°C.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A	5962-86860	
	REVISION LEVEL		SHEET 2

DESC FORM 103A
SEP 87

U. S. GOVERNMENT PRINTING OFFICE: 1968-549-904

2. APPLICABLE DOCUMENTS

2.1 Government specification, standard, and bulletin. Unless otherwise specified, the following specification, standard, and bulletin of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-38510 - Microcircuits, General Specification for.

STANDARD

MILITARY

MIL-STD-883 - Test Methods and Procedures for Microelectronics.

BULLETIN

MILITARY

MIL-BUL-103 - List of Standardized Military Drawings (SMD's).

(Copies of the specification, standard, and bulletin required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 and herein.

3.2.1 Terminal connections. The terminal connections shall be as specified on figure 1.

3.2.2 Case outlines. The case outlines shall be in accordance with 1.2.2 herein.

3.3 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in table I and shall apply over the full ambient operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table II. The electrical tests for each subgroup are described in table I.

3.5 Marking. Marking shall be in accordance with MIL-STD-883 (see 3.1 herein). The part shall be marked with the part number listed in 1.2 herein. In addition, the manufacturer's part number may also be marked as listed in MIL-BUL-103 (see 6.6 herein).

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-86860
		REVISION LEVEL	SHEET 3

DESC FORM 193A
SEP 87

© U. S. GOVERNMENT PRINTING OFFICE: 1988-549-904

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions 1/ -55°C < T _A < +125°C unless otherwise specified	Group A subgroups	Limits		Unit
				Min	Max	
Input offset voltage	V _{IO}	V _{CM} = 0 V, V _{OUT} = 1.4 V 2/	1		±5.0	mV
			2, 3		±8.0	
Input bias current	+I _B	V _{CM} = 0 V	1		±150	nA
			2, 3		±200	
	-I _B	V _{CM} = 0 V	1		±150	nA
			2, 3		±200	
Input offset current	I _{IO}	V _{CM} = 0 V	1		±35	nA
			2, 3		±45	
Input sensitivity	I _{SEN}		1		±0.5	mV
			2, 3		±0.6	
Output low voltage	V _{OL}	I _{SINK} = 3.0 mA	1, 2, 3		0.4	V
Output high voltage	V _{OH}	I _{SOURCE} = 3.0 mA	1, 2, 3	3.5		V
Output sink current	I _{SINK}	V _{OUT} ≤ 0.4 V	1, 2, 3	3.0		mA
Output source current	I _{SOURCE}	V _{OUT} ≥ 0.4 V	1, 2, 3	-3.0		mA
Supply current	+I _{CC}	V _{OUT} = V _{OL} and V _{OH}	1, 2, 3		20	mA
	-I _{CC}	V _{OUT} = V _{OL} and V _{OH}	1		8.0	
			2, 3		10	

See footnotes at end of table.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-86860
		REVISION LEVEL	SHEET 4

DESC FORM 193A
SEP 87

* U. S. GOVERNMENT PRINTING OFFICE: 1988-549 904

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions ^{1/} -55°C < T _A < +125°C unless otherwise specified	Group A subgroups	Limits		Unit
				Min	Max	
Logic current	I _L	V _{OUT} = V _{OL} and V _{OH}	1		6.0	mA
			2, 3		8.0	
Response time ^{3/}	t _{PDO}	100 mV input step, ^{4/} 10 mV overdrive, T _A = +25°C	9		200	ns
	t _{PD1}	-100 mV input step, ^{4/} -10 mV overdrive, T _A = +25°C	9		200	
Common mode voltage range ^{3/}	+V _{CM}	T _A = +25°C	1	-15	12.4	V
	-V _{CM}	T _A = +25°C	1	-15	12.4	V

^{1/} +V = 15 V, -V = -15 V, and V_L = 0 V unless otherwise specified.

^{2/} Offset voltage is measured when V_{OUT} = 1.4 V. Sensitivity is measured on the transition edge at 0.4 V and 3.5 V. Sensitivity is the change in differential input voltage required to change the output state. Sensitivity includes the effects of offset voltage, offset current, common mode rejection and voltage gain. See figure 2.

^{3/} If not tested, shall be guaranteed to the limits specified in table I.

^{4/} Duty cycle = 50%, f = 100 Hz, inverting input is driven, and all unused inverting inputs are tied to +5.0 V. See figure 3.

3.6 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-BUL-103 (see 6.6 herein). The certificate of compliance submitted to DESC-ECS prior to listing as an approved source of supply shall affirm that the manufacturer's product meets the requirements of MIL-STD-883 (see 3.1 herein) and the requirements herein.

3.7 Certificate of conformance. A certificate of conformance as required in MIL-STD-883 (see 3.1 herein) shall be provided with each lot of microcircuits delivered to this drawing.

3.8 Notification of change. Notification of change to DESC-ECS shall be required in accordance with MIL-STD-883 (see 3.1 herein).

3.9 Verification and review. DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A	5962-86860	
		REVISION LEVEL	SHEET 5

DESC FORM 193A
SEP 87

U. S. GOVERNMENT PRINTING OFFICE: 1988-549-904

Device type	01	01
Case outline	E	2
Terminal number	Terminal symbol	
1	+V _L	NC
2	OUT 1	+V _L
3	-IN 1	OUT 1
4	+IN 1	-IN 1
5	-V	+IN 1
6	+IN2	NC
7	-IN2	-V
8	OUT 2	+IN 2
9	-V _L	-IN 2
10	OUT 3	OUT 2
11	-IN 3	NC
12	+IN 3	-V _L
13	+V	OUT 3
14	+IN 4	-IN 3
15	-IN 4	+IN 3
16	OUT 4	NC
17	---	+V
18	---	+IN 4
19	---	-IN 4
20	---	OUT 4

FIGURE 1. Terminal connections.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-86860
		REVISION LEVEL	SHEET 6

DESC FORM 193A
SEP 87

U. S. GOVERNMENT PRINTING OFFICE: 1968-549-904






FIGURE 2. Offset voltage and sensitivity waveforms.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A	5962-86860
	REVISION LEVEL	SHEET 7

DESC FORM 193A
SEP 87

U.S. GOVERNMENT PRINTING OFFICE: 1988 550 547



NOTE: Response time testing is done after V_{I0} testing to acquire device offset voltage. Ten millivolts overdrive is then added (or subtracted depending on state) to this measured V_{I0} value.

FIGURE 3. Response time waveforms.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-86860
		REVISION LEVEL	SHEET 8

DESC FORM 193A
SEP 87

© U. S. GOVERNMENT PRINTING OFFICE: 1988 - 549-904

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein).

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

a. Burn-in test, method 1015 of MIL-STD-883.

(1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.6 herein).

(2) $T_A = +125^{\circ}\text{C}$, minimum.

b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

TABLE II. Electrical test requirements.

MIL-STD-883 test requirements	Subgroups (per method 5005, table I)
Interim electrical parameters (method 5004)	---
Final electrical test parameters (method 5004)	1*, 2, 3
Group A test requirements (method 5005)	1, 2, 3, 9, 10**, 11**
Groups C and D end-point electrical parameters (method 5005)	1

* PDA applies to subgroup 1.

** Subgroups 10 and 11 shall be guaranteed if not tested.

**STANDARDIZED
MILITARY DRAWING**

DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-86860

REVISION LEVEL

SHEET

9

DESC FORM 193A
SEP 87

U. S. GOVERNMENT PRINTING OFFICE: 1988 - 545-934

4.3.1 Group A inspection.

- a. Tests shall be as specified in table II herein.
- b. Subgroups 4, 5, 6, 7, and 8 in table I, method 5005 of MIL-STD-883 shall be omitted.

4.3.2 Groups C and D inspections.

- a. End-point electrical parameters shall be as specified in table II herein.
- b. Steady-state life test conditions, method 1005 of MIL-STD-883:
 - (1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.6 herein).
 - (2) $T_A = +125^{\circ}\text{C}$, minimum.
 - (3) Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use when military specifications do not exist and qualified military devices that will perform the required function are not available for OEM application. When a military specification exists and the product covered by this drawing has been qualified for listing on QPL-38510, the device specified herein will be inactivated and will not be used for new design. The QPL-38510 product shall be the preferred item for all applications.

6.2 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.3 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished in accordance with MIL-STD-481 using DD Form 1693, Engineering Change Proposal (Short Form).

6.4 Record of users. Military and industrial users shall inform Defense Electronics Supply Center when a system application requires configuration control and the applicable SMD. DESC will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronics devices (FSC 5962) should contact DESC-ECS, telephone (513) 296-6022.

6.5 Comments. Comments on this drawing should be directed to DESC-ECS, Dayton, Ohio 45444, or telephone 513-296-5375.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-86860
		REVISION LEVEL	SHEET 10

DESC FORM 193A
SEP 87

U. S. GOVERNMENT PRINTING OFFICE: 1988-549-904

6.6 Approved source of supply. An approved source of supply is listed in MIL-BUL-103. Additional sources will be added as they become available. The vendor listed in MIL-BUL-103 has agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DESC-ECS. The approved source of supply listed below is for information purposes only and is current only to the date of the last action of this document.

Military drawing part number	Vendor CAGE number	Vendor similar part number <u>1/</u>
5962-8686001EX	34371	HA1-4902/883
5962-86860012X	34371	HA4-4902/883

1/ Caution. Do not use this number for item acquisition.
Items acquired to this number may not satisfy the
performance requirements of this drawing.

Vendor CAGE
number

34371

Vendor name
and address

Harris Semiconductor
P.O. Box 883
Melbourne, FL 32901

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A	5962-86860	
		REVISION LEVEL	SHEET 11

DESC FORM 193A
SEP 87

• U. S. GOVERNMENT PRINTING OFFICE 1988-549-904