



EMI Filters with ESD Protection for Data Line Applications


CM6400A

Product Description


The CM6400A is a 24-bump EMI filter with ESD protection device for data line application in a 0.4mm pitch, 5x5 CSP form factor. It is fully compliant with IEC 61000-4-2 Level 4. The CM6400A is RoHS II compliant.

Electrical Schematic / Pin Description


Electrical Schematic



Package Pinout



TOP VIEW
(Bumps Down View)



BOTTOM VIEW
(Bumps Up View)

Notes:

1) These drawings are not to scale.

Pin Information

PIN DESCRIPTIONS				
A5=Line 1	A4=Line 2	A3=GND	A2=Line 1	A1=Line 2
B5=Line 3	B4=Line 4		B2=Line 3	B1=Line 4
C5=Line 5	C4=Line 6	C3=GND	C2=Line 5	C1=Line 6
D5=Line 7	D4=Line 8	D3=GND	D2=Line 7	D1=Line 8
E5=Line 9	E4=Line 10	E3=GND	E2=Line 9	E1=Line 10

Ordering Information

PART NUMBERING INFORMATION				
Bumps	Package	Variation	Ordering Part Number ¹	Part Marking
24	CSP	CSP-SAC105	CM6400A	64P3

Note 1: Parts are shipped in Tape and Reel form unless otherwise specified.

Electrical Specifications and Conditions

PARAMETERS AND OPERATING CONDITIONS		
PARAMETER	RATING	UNITS
Storage Temperature Range	-55 to +150	°C
Operating Temperature Range	-40 to +85	°C
Power dissipation at 70°C per channel	60	mW

ELECTRICAL OPERATING CHARACTERISTICS (SEE NOTE 1)

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
R	Resistance		100	125	150	Ω
L	Inductance	Note 2		35		nH
C	Capacitance per Channel	At 1 MHz, $V_{IN} = 0V$; Notes 2 and 3	19	24	29	pF
		At 1 MHz, $V_{IN} = 2.5V$		15		pF
Att(5)	Passband Attenuation at 5MHz			-7		dB
F_C	Cut-off Frequency	$Z_{SOURCE} = 50\Omega, Z_{LOAD} = 50\Omega$		250		MHz
V_{BR}	Breakdown Voltage	$I_R = \pm 1mA$	± 6	± 7.8	± 10	V
I_{LEAK}	Leakage Current per Channel	$V_{IN} = 3.0V$		10	100	nA
V_{ESD}	ESD Peak Discharge Voltage Protection at All Pins: a) Contact discharge per IEC 61000-4-2 standard b) Air discharge per IEC 61000-4-2 standard	Notes 2, 3, and 4	± 15			kV
			± 15			kV

Note 1: All parameters specified at $T_A = 25^\circ C$ unless otherwise noted.

Note 2: These parameters guaranteed by design.

Note 3: These parameters guaranteed by characterization.

Note 4: Standard IEC 61000-4-2 ($C_{Discharge} = 150pF, R_{Discharge} = 330\Omega$).

RF Characteristics




Figure 1. Typical Insertion Loss (Bias=0V, T_A= 25°C, 50 Ohm Environment)


CM6400A

Mechanical Specification

CSP-24 Mechanical Specifications

The CM6400A is supplied in a 24 bump, 5x5 Chip Scale Package (CSP).

Package Dimensions						
Package	Custom CSP					
Bumps	24					
Dim	Millimeters			Inches		
	Min	Nom	Max	Min	Nom	Max
A1	1.915	1.960	2.005	0.0754	0.0772	0.0789
A2	1.915	1.960	2.005	0.0754	0.0772	0.0789
B1	0.395	0.400	0.405	0.0156	0.0157	0.0159
B2	0.395	0.400	0.405	0.0156	0.0157	0.0159
C1	0.130	0.180	0.230	0.0051	0.0071	0.0091
C2	0.130	0.180	0.230	0.0051	0.0071	0.0091
D1	0.570	0.600	0.630	0.0224	0.0236	0.0248
D2	0.394	0.406	0.419	0.0155	0.0160	0.0165
Controlling dimension: millimeters						



**Package Dimensions for
CM6400A Chip Scale Package**

Vertical Structure Specification*




Figure 2. Sectional View

*Daisy Chain CM6000

Vertical Structure Dimensions (nominal)

REF.	Parameter	Material	Dimension
a	Die Thickness	Silicon	396µm
h	Repassivation	Polyimide	10µm
d	UBM-(Ti/Cu)	Plated Cu	7µm
		Sputtered Cu	0.4µm
		Sputtered Ti	0.1µm
e	UBM Wetting Area Diameter		240µm
b	Bump Standoff		194µm
f	Solder Bump Diameter after Bump Reflow		270µm
c	Metal Pad Height	AlSiCu	1.5µm
g	Metal Pad Diameter		284µm
D2			0.406mm
D1	Finished Thickness		0.600mm

CM6400A

Mechanical Specification (cont'd)

CSP Tape and Reel Specifications

PART NUMBER	CHIP SIZE (mm)	POCKET SIZE (mm) $B_0 \times A_0 \times K_0$	TAPE WIDTH W	REEL DIA.	QTY PER REEL	P_0	P_1
CM6400A	1.96 X 1.96 X 0.60	2.20 x 2.20 x 0.68	8mm	178mm (7")	5000	4mm	4mm





Figure 3. Tape and Reel Mechanical Data

**REVISION RECORD FOR NOKIA PRODUCT DATASHEET
CM6400A**

ISSUE	DATE	DETAILS OF CHANGE	ORIGINATOR
X-1	5/21/09	<ul style="list-style-type: none"> Preliminary release of datasheet 	Tim Micun
X-2	8/03/09	<ul style="list-style-type: none"> Product name change from CM6400-P3 to CM6400A Changed Vertical Structure drawing to match CM6000/CM6100 on page 4. 	Tim Micun
X-3	9/15/09	<ul style="list-style-type: none"> Replaced RF characteristics graph (Figure 1 "Typical Insertion Loss") on page 3. 	Tim Micun
A	10/2/09	<ul style="list-style-type: none"> Datasheet is now at "production" status (Issue A). No other changes made. 	Tim Micun

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855
Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5773-3850

ON Semiconductor Website: www.onsemi.com

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative