

- 3. TERMINAL TO BE USED WITH 22-24 AWG STRANDED WIRE WITH .064 DIA. MAX. INSULATION.
- 4. REFER TO MOLEX OPERATIONAL AND SERVICE MANUAL FOR DETAILS.
- 5. REFER TO PRODUCT SPECIFICATION NO. PS-70021.

8

6. PARTS SUPPLIED IN REEL FORM.

PLATING:

В

A

.000150 MIN. TIN/LEAD PLATE OVER NICKEL PLATE.

							MFG. SI
	DIMENSIONS SHOWN (METRIC) INCH				V = 0	V	= 0
	UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR # 1/2°				TITLE		
		INCH	METRIC			T	NATE I
	3 PLACE	± .010				IEH	MIN
	2 PLACE	± .015	± 0.25				
	I PLACE		± 0.35		molex M	OLEX	INCO
	DRAFT WHERE APPLICABLE MUST					LE,ILL.	6053
	DRWG. NA IF CHK'D. AA IAA				16-02-0107		
BY		JF BY	n. MJM	1	FILE NAM	F	
	P'D. \\/ /		LE ∅:	Ι	S7002IX	∧.l IH	IS DRAWING C K INC. AND SH

10