

EKI-6311G

802.11 b/g Wireless Access Point/Client Bridge

NEW



RoHS
COMPLIANT
2002/95/EC

CE FCC

Features

- IEEE 802.11 b/g compatible
- IEEE 802.3 af Power over Ethernet (PoE) support
- High speed data rates (up to 54 Mbps)
- Output power up to 19dBm (80mW)
- Point-to-Point, Point-to-Multipoint wireless connectivity
- WEP/WPA/WPA2/ IEEE 802.1x authentication support
- WDS (Wireless Distribution System) support
- IP65 compliance protects against dust and water
- Multi-SSID (up to 4 SSID) support

Introduction

EKI-6311G features enhanced wireless transmission capabilities to provide a reliable wireless environment for industrial building systems. Moreover, a detachable antenna can collocate with any high gain antenna to enhance wireless connections even further. To protect wireless connections, EKI-6311G can encrypt transmissions through 64/128-bit WEP data encryption and also supports WPA2/WPA/802.1x for powerful security authentication.

Specifications

General

- **Chipset** Atheros solution
- **Data Rates** 802.11 b: 1, 2, 5.5, 11Mbps
802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
- **Standards** IEEE802.11 b/g, IEEE802.1x, IEEE802.3, IEEE802.3u
- **Certifications** IP65, FCC Part 15B
CE EN60950/EN300328/EN301489-1-17

RF Information

- **Frequency Band** 2.400 ~ 2.484 GHz
- **Media Access Protocol** Carrier sense multiple access with collision avoidance (CSMA/CA)
- **Modulation Technology**
802.11b: Direct-Sequence Spread Spectrum (DSSS)
DBPSK @ 1Mbps
DQPSK @ 2Mbps
CCK @ 5.5 and 11Mbps
802.11g: Orthogonal Frequency Division Multiplexing (OFDM)
BPSK @ 6 and 9 Mbps
QPSK @ 12 and 18 Mbps
6-QAM @ 24 and 36 Mbps
64-QAM @ 48 and 54 Mbps
- **Receive Sensitivity**
2.412~2.472G (IEEE802.11g)
-92dBm@6Mbps
-76dBm@54Mbps
2.412 ~ 2.472G (IEEE802.11b)
-92dBm@11Mbps
-96dBm@1Mbps
- **Transmit Output Power (Typical)**
IEEE802.11g: 14dBm+2
IEEE802.11b: 17dBm+2
- **Antennas** 5dBi dipole antenna x 2 (external)
- **RF Connector** SMA female

Power

- **Power Consumption** Max. 12 W
- **Power Input** Active Ethernet (Power over Ethernet): 48 V_{DC}/0.375A

Networking Information

- **Topology** Infrastructure, Ad-hoc
- **Operation Mode** Point-to-Point/ Point-to-Multipoint AP/Client Bridge/ WDS Repeater
- **Interface** 1 x 10/100 Mbps RJ-45 LAN Port (Auto Switch)
- **Security** IEEE802.1x / RADIUS Client (EAP-MD5/TLS/TTLS, PEAP) Support in AP Mode
IEEE802.1x Supplicant (EAP-MD5/TLS/TTLS, PEAP) support in Client Bridge Mode
WEP 64/128 bits
WPA/WPA2 Personal
PSK (Pre Share Key) with TKIP/AES
WPA/WPA2 Enterprise
EAP-MD5/TLS/TTLS authenticator with TKIP/AES
MAC address filtering
Layer2 Isolation
VLAN tunneling support
Hide SSID in beacons
- **IP Auto-configuration** DHCP client/server

Management

- **Remote Configuration** Web-based configuration (HTTP)
Telnet configuration
- **Firmware Upgrade** Upgrade firmware via web-browser

Physical

- **Dimensions (L x W x H)** 209.1 x 165.4 x 61.5 mm
- **Weight** 500g

Environment

- **Operating Temperature** -10 ~ 60° C (14 ~ 158° F)
- **Storing Temperature** -40 ~ 85° C (-40 ~ 185° F)
- **Humidity** 5 ~ 95% (non-condensing)

Ordering Information

- **EKI-6311G** 802.11b/g Wireless AP/Client Bridge (US)
- **EKI-6311G/EU** 802.11b/g Wireless AP/Client Bridge (EU)