

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 (818) 701-4939 Fax:

Features

- Intended for use in power linear and switching applications
- Lead Free Finish/RoHS Compliant (Note1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisure Sensitivity Level 1

Maximum Ratings


Symbol	Rating	Rating	Unit
V _{CEO}	Collector-Emitter Voltage	80	V
V _{CBO}	Collector-Base Voltage	80	V
V _{EBO}	Emitter-Base Voltage	5.0	V
I _{CP}	Peak Collector Current	15	А
l _c	Collector Current	12	А
Pc	Collector power dissipation	80	W
TJ	Junction Temperature	-55 to +150	°C
T _{STG}	Storage Temperature	-55 to +150	Oo

Electrical Characteristics @ 25°C Unless Otherwise Specified					
Symbol	Parameter	Min	Max	Units	
OFF CHARACTERISTICS					
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage (l_c =100mAdc, l_B =0)	80	Vdc		
I _{сво}	Collector-Base Cutoff Current (V _{CB} =80Vdc,I _E =0)		0.1 mAdc		
I _{EBO}	Emitter-Base Cutoff Current2.0 $(V_{EB}=5.0Vdc, b=0)$				
ON CHARACTERISTICS					
h _{FE-1}	Forward Current Transfer ratio (L=3.0Adc, V _{CE} =3.0Vdc)	1000			
h _{FE-2}	Forward Current Transfer ratio (t _c =5.0Adc, V _{CE} =3.0Vdc)	750	20000		
h _{FE-3}	Forward Current Transfer ratio (L=10Adc, V _{CE} =3.0Vdc)	100			
V _{CE(sat)-1}	Collector-Emitter Saturation Voltage ($L=5.0$ Adc, $B=20$ mAdc)		2.0	Vdc	
V _{CE(sat)-2}	Collector-Emitter Saturation Voltage (L =10Adc, I_B =100mAdc)		3.0	Vdc	
V _{BE(sat)-1}	Base-Emitter Saturation Voltage (b=5.0Adc,l ₈ =20Adc)		2.5	Vdc	
V _{BE(sat)-2}	Base-Emitter Saturation Voltage (b=10Adc,la=100Adc)		4.0	Vdc	

Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.

BDW93B

NPN Silicon Power Transistors



			1 114 0.	ENNITE	
		DIME	INSIONS		
	INCHES MM				
DIM	MIN	MAX	MIN	MAX	NOTE
А	.560	.625	14.22	15.88	
В	.380	.420	9.65	10.67	
С	.140	.190	3.56	4.82	
D	.020	.045	0.51	1.14	
F	.139	.161	3.53	4.09	Ø
G	.190	.110	2.29	2.79	
Н		.250		6.35	
J	.012	.025	0.30	0.64	
К	.500	.580	12.70	14.73	
L	.045	.060	1.14	1.52	
Ν	.190	.210	4.83	5.33	
Q	.100	.135	2.54	3.43	
R	.080	.115	2.04	2.92	
S	.045	.055	1.14	1.39	
Т	.230	.270	5.84	6.86	
U		.050		1.27	
V	.045		1.15		

www.mccsemi.com



Ordering Information :

Device	Packing
Part Number-BP	Bulk; 1Kpcs/Box

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com