

Dialight

PW SERIES

CIRCULAR LED MODULES

MR16/MR16-LV



APPLICATION

- ▲ Spot lighting
- ▲ Accent lighting
- ▲ General illumination
- ▲ Interior use only
- ▲ Architectural lighting
- ▲ Machine vision
- ▲ Display cases

*Product designed to fit the majority of front MR16 housings.
Depth of housing should be checked for compatibility.*

ORDERING INFORMATION

MR16-LV-AA-BB	
(LV) Options	(AA) Typical Colour Temperature
Blank = no onboard driver	CW = 5000K – 6350K NW = 3800K – 4100K WW = 2850K – 3250K
LV = with onboard driver	(BB) Optic
	SP = 7 degree spot WD = 13 degree wide <i>All angles are half divergence</i>


FEATURES / BENEFITS

- ▲ Utilizes 4 premium flux LUXEON® Rebel™ LEDs, 100+ lumens for cool white, 100+ lumens for neutral white and 50+ lumens for warm white
- ▲ ETL recognized to UL standards (pending)
- ▲ Available in choice of colours & colour temperatures
- ▲ Quick connect terminal blocks for easy installation
- ▲ >70% lumen maintenance @ 50,000 hours at max operating temperature. Better at lower operating temps!

MATERIALS / FINISH

- ▲ **Connection** - Cage Clamp Connectors
- ▲ **Optics** - Dialight Optics
- ▲ **Lens Cover** - Polycarbonate 143R
- ▲ **Rear Cover** - Polycarbonate 143R
- ▲ **Heatsink** - ADC10 Aluminum Alloy, Black Anodised Finish

MECHANICAL DIMENSIONS



Diameter x H
 49.75mm x 52.25mm (1.959" x 2.06")
 Maximum Cable Dia - 1.5mm² / 16 AWG

OPERATING CHARACTERISTICS

Model / Color	Typical Total Lumen Output		Power Consumption		Drive Current / Operating Current	Input Voltage
	350mA / LV	700mA	350mA / LV	700mA	mA	
MR16 / CW	400	720	4.8W	9.6W	350 - 700	*13.5 -16VDC
MR16 / NW	400	720				
MR16 / WW	200	380				
MR16-LV / CW	400	-	5.0W	-	**300mA	24VDC +/- 10%
MR16-LV / NW	400	-				
MR16-LV / WW	200	-				

Note: Lumen output based on manufacturers data

*Based on max Vf of 4.0V

**1.2A for initial switch on

COMPATIBLE DRIVERS

Compatible Constant Current Dialight Drivers

Driver	350mA	700mA	No. of units
MDU 9 (MDU9-35-70)	x	x	1** / 2*
VARILED (MDU-18-V-25-100)	x	x	2** / 4*
MULTIDRIVER (MLD8-C-35-70)		x	2
MINIDIM 70 (MND70)	x	x	1** / 2*

*at 350mA / **at 700mA

Compatible Dialight Constant Voltage DC Drivers

Driver	24V	No. of units
MULTIDRIVER (MLD8-C-35-70)	x	1
MVDU100-24-P	X	1-16


Check with Dialight website for updates on LED drivers

OPERATING CONDITIONS

- ▲ Operating ambient temperature -20°C to +40°C
- ▲ MR16 requires constant current driver
MR16-LV requires constant voltage driver
(See compatibility list)
- ▲ Max drive current 700mA (constant current version)
- ▲ IP20 rating

PHOTOMETRIC DATA

Relative
Light
Output



Degrees

Dialight reserves the right to make changes at any time in order to supply the best product possible.

The most current version of this document will always be available at:

www.dialight.com/Assets/Brochures_And_Catalogs/Illumination/MDEXLUMMR16.pdf

MDEXLUMMR16_D