

# ROHM's Selection Operational Amplifier/Comparator Series

## Low Voltage Operation CMOS Operational Amplifiers




**BU7261G, BU7261S G, BU7241G, BU7241S G**  
**BU7262F/FVM, BU7262S F/FVM, BU7242F/FVM, BU7242S F/FVM**  
**BU7461G, BU7461S G, BU7441G, BU7441S G**  
**BU7462F/FVM, BU7462S F/FVM, BU7442F/FVM, BU7442S F/FVM**

No.09049EAT07

### ●Description

Low Voltage CMOS Op-Amp integrate one or two independent output full swing Op-Amps and phase compensation capacitors on a single chip. Especially, this series is operable with low voltage, low supply current and low input bias current.


- Input-Output Full Swing : BU7261/BU7241 family , BU7262/BU7242 family
- Ground Sense : BU7461/BU7441 family , BU7462/BU7442 family




### ●Features

- 1) Operable with low voltage  
 Input-Output Full Swing : +1.8 [V]~+5.5 [V] (single supply): BU7261/BU7241 family , BU7262/BU7242 family  
 Ground Sense : +1.7 [V]~+5.5 [V] (single supply): BU7461/BU7441 family , BU7462/BU7442 family
- 2) Internal phase compensation
- 3) High large signal voltage gain
- 4) Internal ESD protection  
 Human body model (HBM) ±4000[V] (Typ.)
- 5) Low input bias current 1[pA] (Typ.)

● Pin Assignments



SSOP5



SOP8

MSOP8

Input type	Package		
	SSOP5	SOP8	MSOP8
Input-output Full Swing	BU7261G BU7261SG BU7241G BU7241SG	BU7262F BU7262SF BU7242F BU7242SF	BU7262FVM BU7262SFVM BU7242FVM BU7242SFVM
Ground Sense	BU7461G BU7461SG BU7441G BU7441SG	BU7462F BU7462SF BU7442F BU7442SF	BU7462FVM BU7462SFVM BU7442FVM BU7442SFVM

● Absolute maximum rating(Ta=25[°C])

Parameter	Symbol	Rating		Unit
		BU7261G, BU7262 F/FVM BU7241G, BU7242 F/FVM BU7461G, BU7462 F/FVM BU7441G, BU7442 F/FVM	BU7261SG, BU7262S F/FVM BU7241SG, BU7242S F/FVM BU7461SG, BU7462S F/FVM BU7441SG, BU7442S F/FVM	
Supply Voltage	VDD-VSS	+7		V
Differential Input Voltage(*1)	Vid	VDD-VSS		V
Input Common-mode Voltage Range	Vicm	(VSS-0.3)~(VDD+0.3)		V
Operating Temperature	Topr	-40~+85	-40~+105	°C
Storage Temperature	Tstg	-55~+125		°C
Maximum Junction Temperature	Tjmax	+125		°C

Note: Absolute maximum rating item indicates the condition which must not be exceeded.

Application of voltage in excess of absolute maximum rating or use out absolute maximum rated temperature environment may cause deterioration of characteristics.

(\*1) The voltage difference between inverting input and non-inverting input is the differential input voltage.  
 Then input terminal voltage is set to more than VSS.

## Input-Output Full Swing

### BU7261G, BU7261SG, BU7241G, BU7241SG

### BU7262F/FVM, BU7262S F/FVM, BU7242F/FVM, BU7242S F/FVM

#### ●Features

- 1) Operable low power supply +1.8[V]~+5.5[V]
- 2) +1.8 [V]~+5.5[V](single supply)  
±0.9[V]~±2.75[V](split supply)
- 3) Operable input-Output full swing
- 4) High slew rate (BU7261 family , BU7262 family)
- 5) Low supply current (BU7241 family , BU7242 family)
- 6) Wide temperature range  
-40[°C]~+85[°C]  
(BU7261G,BU7262 family , BU7241G,BU7242 family)  
-40[°C]~+105[°C]  
(BU7261SG,BU7262S family,BU7241SG,BU7242S family)

#### ●Electrical characteristics

OBU7261 family , BU7262 family (Unless otherwise specified VDD=+3[V], VSS=0[V], Ta=25[°C])

Parameter	Symbol	Temperature Range	Guaranteed limit			Unit	Condition
			BU7261G,BU7261SG				
			Min.	Typ.	Max.		
Input Offset Voltage <sup>(*)</sup> <sup>(*)</sup>	Vio	25°C	-	1	9	mV	VDD=1.8~5.5[V], VOUT=VDD/2
		Full range	-	-	10		
Input Offset Current <sup>(*)</sup>	Iio	25°C	-	1	-	pA	-
Input Bias Current <sup>(*)</sup>	Ib	25°C	-	1	-	pA	-
Supply Current <sup>(*)</sup>	IDD	25°C	-	250	550	µA	RL=∞ All Op-Amps AV=0[dB],VIN=1.5[V]
		Full range	-	-	600		
High Level Output Voltage	VOH	25°C	VDD-0.1	-	-	V	RL=10[kΩ]
Low Level Output Voltage	VOL	25°C	-	-	VSS+0.1	V	RL=10[kΩ]
Large Single Voltage Gain	AV	25°C	70	95	-	dB	RL=10[kΩ]
Input Common-mode Voltage Range	Vicm	25°C	0	-	3	V	VDD-VSS=3[V]
Common-mode Rejection Ratio	CMRR	25°C	45	60	-	dB	-
Power Supply Rejection Ratio	PSRR	25°C	60	80	-	dB	-
Output Source Current <sup>(*)</sup>	IOH	25°C	4	10	-	mA	VDD-0.4[V]
Output Sink Current <sup>(*)</sup>	IOL	25°C	5	12	-	mA	VSS+0.4[V]
Slew Rate	SR	25°C	-	1.1	-	V/µs	CL=25[pF]
Gain Bandwidth Product	FT	25°C	-	2	-	MHz	CL=25[pF], AV=40[dB]
Phase Margin	θ	25°C	-	50°	-	-	CL=25[pF], AV=40[dB]
Total Harmonic Distortion	THD	25°C	-	0.05	-	%	VOUT=1[Vp-p],f=1[kHz]
Channel Separation	CS	25°C	-	-	-	dB	Av=40[dB]

Parameter	Symbol	Temperature Range	Guaranteed limit			Unit	Condition
			BU7262 F/FVM BU7262S F/FVM				
			Min.	Typ.	Max.		
Input Offset Voltage <sup>(*)</sup> <sup>(*)</sup>	Vio	25°C	-	1	9	mV	VDD=1.8~5.5[V], VOUT=VDD/2
		Full range	-	-	10		
Input Offset Current <sup>(*)</sup>	Iio	25°C	-	1	-	pA	-
Input Bias Current <sup>(*)</sup>	Ib	25°C	-	1	-	pA	-
Supply Current <sup>(*)</sup>	IDD	25°C	-	550	1100	µA	RL=∞ All Op-Amps AV=0[dB],VIN=1.5[V]
		Full range	-	-	1200		
High Level Output Voltage	VOH	25°C	VDD-0.1	-	-	V	RL=10[kΩ]
Low Level Output Voltage	VOL	25°C	-	-	VSS+0.1	V	RL=10[kΩ]
Large Single Voltage Gain	AV	25°C	70	95	-	dB	RL=10[kΩ]
Input Common-mode Voltage Range	Vicm	25°C	0	-	3	V	VDD-VSS=3[V]
Common-mode Rejection Ratio	CMRR	25°C	45	60	-	dB	-
Power Supply Rejection Ratio	PSRR	25°C	60	80	-	dB	-
Output Source Current <sup>(*)</sup>	IOH	25°C	4	10	-	mA	VDD-0.4[V]
Output Sink Current <sup>(*)</sup>	IOL	25°C	5	12	-	mA	VSS+0.4[V]
Slew Rate	SR	25°C	-	1.1	-	V/µs	CL=25[pF]
Gain Bandwidth Product	FT	25°C	-	2	-	MHz	CL=25[pF], AV=40[dB]
Phase Margin	θ	25°C	-	50°	-	-	CL=25[pF], AV=40[dB]
Total Harmonic Distortion	THD	25°C	-	0.05	-	%	VOUT=1[Vp-p],f=1[kHz]
Channel Separation	CS	25°C	-	100	-	dB	Av=40[dB]

(\*) Absolute value

(\*) Full range : BU7261, BU7262 : Ta=-40[°C] to +85[°C] BU7261S, BU7262S : Ta=-40[°C] to +105[°C]

(\*) Under the high temperature environment, consider the power dissipation of IC when selecting the output current.

When the terminal short circuits are continuously output, the output current is reduced to climb to the temperature inside IC.

●Electrical characteristics

OBU7241 family , BU7242 family (Unless otherwise specified VDD=+3[V], VSS=0[V], Ta=25[°C])

Parameter	Symbol	Temperature Range	Guaranteed limit			Unit	Condition
			BU7241G,BU7241SG				
			Min.	Typ.	Max.		
Input Offset Voltage <sup>(*5)(*6)</sup>	Vio	25°C	-	1	9	mV	VDD=1.8~5.5[V], VOUT=VDD/2
		Full range	-	-	10		
Input Offset Current <sup>(*5)</sup>	Iio	25°C	-	1	-	pA	-
Input Bias Current <sup>(*5)</sup>	Ib	25°C	-	1	-	pA	-
Supply Current <sup>(*6)</sup>	IDD	25°C	-	70	150	µA	RL=∞ All Op-Amps AV=0[dB],VIN=1.5[V]
		Full range	-	-	250		
High Level Output Voltage	VOH	25°C	VDD-0.1	-	-	V	RL=10[kΩ]
Low Level Output Voltage	VOL	25°C	-	-	VSS+0.1	V	RL=10[kΩ]
Large Single Voltage Gain	AV	25°C	70	95	-	dB	RL=10[kΩ]
Input Common-mode Voltage Range	Vicm	25°C	0	-	3	V	VDD-VSS=3[V]
Common-mode Rejection Ratio	CMRR	25°C	45	60	-	dB	-
Power Supply Rejection Ratio	PSRR	25°C	60	80	-	dB	-
Output Source Current <sup>(*7)</sup>	IOH	25°C	4	10	-	mA	VDD-0.4[V]
Output Sink Current <sup>(*7)</sup>	IOL	25°C	5	12	-	mA	VSS+0.4[V]
Slew Rate	SR	25°C	-	0.4	-	V/µs	CL=25[pF]
Gain Bandwidth Product	FT	25°C	-	0.9	-	MHz	CL=25[pF], AV=40[dB]
Phase Margin	θ	25°C	-	50°	-	-	CL=25[pF], AV=40[dB]
Total Harmonic Distortion	THD	25°C	-	0.05	-	%	VOUT=1[Vp-p],f=1[kHz]
Channel Separation	CS	25°C	-	-	-	dB	Av=40[dB]

Parameter	Symbol	Temperature Range	Guaranteed limit			Unit	Condition
			BU7242F/FVM BU7242S F/FVM				
			Min.	Typ.	Max.		
Input Offset Voltage <sup>(*5)(*6)</sup>	Vio	25°C	-	1	9	mV	VDD=1.8~5.5[V], VOUT=VDD/2
		Full range	-	-	10		
Input Offset Current <sup>(*5)</sup>	Iio	25°C	-	1	-	pA	-
Input Bias Current <sup>(*5)</sup>	Ib	25°C	-	1	-	pA	-
Supply Current <sup>(*6)</sup>	IDD	25°C	-	180	360	µA	RL=∞ All Op-Amps AV=0[dB],VIN=1.5[V]
		Full range	-	-	600		
High Level Output Voltage	VOH	25°C	VDD-0.1	-	-	V	RL=10[kΩ]
Low Level Output Voltage	VOL	25°C	-	-	VSS+0.1	V	RL=10[kΩ]
Large Single Voltage Gain	AV	25°C	70	95	-	dB	RL=10[kΩ]
Input Common-mode Voltage Range	Vicm	25°C	0	-	3	V	VDD-VSS=3[V]
Common-mode Rejection Ratio	CMRR	25°C	45	60	-	dB	-
Power Supply Rejection Ratio	PSRR	25°C	60	80	-	dB	-
Output Source Current <sup>(*7)</sup>	IOH	25°C	4	10	-	mA	VDD-0.4[V]
Output Sink Current <sup>(*7)</sup>	IOL	25°C	5	12	-	mA	VSS+0.4[V]
Slew Rate	SR	25°C	-	0.4	-	V/µs	CL=25[pF]
Gain Bandwidth Product	FT	25°C	-	0.9	-	MHz	CL=25[pF], AV=40[dB]
Phase Margin	θ	25°C	-	50°	-	-	CL=25[pF], AV=40[dB]
Total Harmonic Distortion	THD	25°C	-	0.05	-	%	VOUT=1[Vp-p],f=1[kHz]
Channel Separation	CS	25°C	-	100	-	dB	Av=40[dB]

(\*5) Absolute value

(\*6) Full range : BU7241, BU7242 : Ta=-40[°C] to +85[°C] BU7241S, BU7242S : Ta=-40[°C] to +105[°C]

(\*7) Under the high temperature environment, consider the power dissipation of IC when selecting the output current.

When the terminal short circuits are continuously output, the output current is reduced to climb to the temperature inside IC.

## Ground Sense

### BU7461G,BU7461SG,BU7441G,BU7441SG

### BU7462F/FVM,BU7462S F/FVM, BU7442F/FVM,BU7442S F/FVM

#### ●Features

- 1) Operable low power supply +1.7[V]~+5.5[V]
- 2) +1.7[V]~+5.5[V](single supply)  
±0.85[V]~2.75[V](split supply)
- 3) Operable input-ground sense, output-full swing
- 4) High slew rate (BU7461 family , BU7462 family)
- 5) Low supply current (BU7441 family , BU7442 family)
- 6) Wide temperature range  
-40[°C]~+85[°C]  
(BU7461G,BU7462 family , BU7441G,BU7442 family)  
-40[°C]~+105[°C]  
(BU7461SG,BU7462S family , BU7441SG,BU7442S family)

#### ●Electrical characteristics

OBU7461 family , BU7462 family (Unless otherwise specified VDD=+3[V], VSS=0[V], Ta=25[°C])

Parameter	Symbol	Temperature Range	Guaranteed limit			Unit	Condition
			BU7461G,BU7461SG				
			Min.	Typ.	Max.		
Input Offset Voltage <sup>(*)8)(*)9)</sup>	Vio	25°C	-	1	6	mV	-
Input Offset Current <sup>(*)8)</sup>	Iio	25°C	-	1	-	pA	-
Input Bias Current <sup>(*)8)</sup>	Ib	25°C	-	1	-	pA	-
Supply Current <sup>(*)9)</sup>	IDD	25°C	-	150	350	µA	RL=∞ All Op-Amps AV=0[dB],VIN=0.9[V]
		Full range	-	-	450		
High Level Output Voltage	VOH	25°C	VDD-0.1	-	-	V	RL=10[kΩ]
Low Level Output Voltage	VOL	25°C	-	-	VSS+0.1	V	RL=10[kΩ]
Large Single Voltage Gain	AV	25°C	70	95	-	dB	RL=10[kΩ]
Input Common-mode Voltage Range	Vicm	25°C	0	-	1.8	V	VSS~VDD-1.2[V]
Common-mode Rejection Ratio	CMRR	25°C	45	60	-	dB	-
Power Supply Rejection Ratio	PSRR	25°C	60	80	-	dB	-
Output Source Current <sup>(*)10)</sup>	IOH	25°C	4	8	-	mA	VDD-0.4[V]
Output Sink Current <sup>(*)10)</sup>	IOL	25°C	6	12	-	mA	VSS+0.4[V]
Slew Rate	SR	25°C	-	1.0	-	V/µs	CL=25[pF]
Gain Bandwidth Product	FT	25°C	-	1	-	MHz	CL=25[pF], AV=40[dB]
Phase Margin	θ	25°C	-	50°	-	-	CL=25[pF], AV=40[dB]
Total Harmonic Distortion	THD	25°C	-	0.05	-	%	VOUT=1[Vp-p],f=1[kHz]

Parameter	Symbol	Temperature Range	Guaranteed limit			Unit	Condition
			BU7462 F/FVM BU7462S F/FVM				
			Min.	Typ.	Max.		
Input Offset Voltage <sup>(*)8)(*)9)</sup>	Vio	25°C	-	1	6	mV	-
Input Offset Current <sup>(*)8)</sup>	Iio	25°C	-	1	-	pA	-
Input Bias Current <sup>(*)8)</sup>	Ib	25°C	-	1	-	pA	-
Supply Current <sup>(*)9)</sup>	IDD	25°C	-	300	700	µA	RL=∞ All Op-Amps AV=0[dB],VIN=0.9[V]
		Full range	-	-	900		
High Level Output Voltage	VOH	25°C	VDD-0.1	-	-	V	RL=10[kΩ]
Low Level Output Voltage	VOL	25°C	-	-	VSS+0.1	V	RL=10[kΩ]
Large Single Voltage Gain	AV	25°C	70	95	-	dB	RL=10[kΩ]
Input Common-mode Voltage Range	Vicm	25°C	0	-	1.8	V	VSS~VDD-1.2[V]
Common-mode Rejection Ratio	CMRR	25°C	45	60	-	dB	-
Power Supply Rejection Ratio	PSRR	25°C	60	80	-	dB	-
Output Source Current <sup>(*)10)</sup>	IOH	25°C	4	8	-	mA	VDD-0.4[V]
Output Sink Current <sup>(*)10)</sup>	IOL	25°C	6	12	-	mA	VSS+0.4[V]
Slew Rate	SR	25°C	-	1.0	-	V/µs	CL=25[pF]
Gain Bandwidth Product	FT	25°C	-	1	-	MHz	CL=25[pF], AV=40[dB]
Phase Margin	θ	25°C	-	50°	-	-	CL=25[pF], AV=40[dB]
Total Harmonic Distortion	THD	25°C	-	0.05	-	%	VOUT=1[Vp-p],f=1[kHz]

(\*)8) Absolute value

(\*)9) Full range : BU7461, BU7462 : Ta=-40[°C] to +85[°C] BU7461S, BU7462S : Ta=-40[°C] to +105[°C]

(\*)10) Under the high temperature environment, consider the power dissipation of IC when selecting the output current.

When the terminal short circuits are continuously output, the output current is reduced to climb to the temperature inside IC.

●Electrical characteristics

OBU7441 family , BU7442 family (Unless otherwise specified VDD=+3[V], VSS=0[V], Ta=25[°C])

Parameter	Symbol	Temperature Range	Guaranteed limit			Unit	Condition
			BU7441G,BU7441SG				
			Min.	Typ.	Max.		
Input Offset Voltage <sup>(*)</sup> <sup>(*)</sup>	Vio	25°C	-	1	6	mV	-
Input Offset Current <sup>(*)</sup>	Iio	25°C	-	1	-	pA	-
Input Bias Current <sup>(*)</sup>	Ib	25°C	-	1	-	pA	-
Supply Current <sup>(*)</sup>	IDD	25°C	-	50	120	μA	RL=∞ All Op-Amps AV=0[dB],VIN=0.9[V]
		Full range	-	-	240		
High Level Output Voltage	VOH	25°C	VDD-0.1	-	-	V	RL=10[kΩ]
Low Level Output Voltage	VOL	25°C	-	-	VSS+0.1	V	RL=10[kΩ]
Large Single Voltage Gain	AV	25°C	70	95	-	dB	RL=10[kΩ]
Input Common-mode Voltage Range	Vicm	25°C	0	-	1.8	V	VSS~VDD-1.2[V]
Common-mode Rejection Ratio	CMRR	25°C	45	60	-	dB	-
Power Supply Rejection Ratio	PSRR	25°C	60	80	-	dB	-
Output Source Current <sup>(*)</sup>	IOH	25°C	3	6	-	mA	VDD-0.4[V]
Output Sink Current <sup>(*)</sup>	IOL	25°C	5	10	-	mA	VSS+0.4[V]
Slew Rate	SR	25°C	-	0.3	-	V/μs	CL=25[pF]
Gain Bandwidth Product	FT	25°C	-	0.6	-	MHz	CL=25[pF], AV=40[dB]
Phase Margin	θ	25°C	-	50°	-	-	CL=25[pF], AV=40[dB]
Total Harmonic Distortion	THD	25°C	-	0.05	-	%	VOUT=1[Vp-p],f=1[kHz]

Parameter	Symbol	Temperature Range	Guaranteed limit			Unit	Condition
			BU7442F/FVM BU7442S F/FVM				
			Min.	Typ.	Max.		
Input Offset Voltage <sup>(*)</sup> <sup>(*)</sup>	Vio	25°C	-	1	6	mV	-
Input Offset Current <sup>(*)</sup>	Iio	25°C	-	1	-	pA	-
Input Bias Current <sup>(*)</sup>	Ib	25°C	-	1	-	pA	-
Supply Current <sup>(*)</sup>	IDD	25°C	-	100	240	μA	RL=∞ All Op-Amps AV=0[dB],VIN=0.9[V]
		Full range	-	-	480		
High Level Output Voltage	VOH	25°C	VDD-0.1	-	-	V	RL=10[kΩ]
Low Level Output Voltage	VOL	25°C	-	-	VSS+0.1	V	RL=10[kΩ]
Large Single Voltage Gain	AV	25°C	70	95	-	dB	RL=10[kΩ]
Input Common-mode Voltage Range	Vicm	25°C	0	-	1.8	V	VSS~VDD-1.2[V]
Common-mode Rejection Ratio	CMRR	25°C	45	60	-	dB	-
Power Supply Rejection Ratio	PSRR	25°C	60	80	-	dB	-
Output Source Current <sup>(*)</sup>	IOH	25°C	3	6	-	mA	VDD-0.4[V]
Output Sink Current <sup>(*)</sup>	IOL	25°C	5	10	-	mA	VSS+0.4[V]
Slew Rate	SR	25°C	-	0.3	-	V/μs	CL=25[pF]
Gain Bandwidth Product	FT	25°C	-	0.6	-	MHz	CL=25[pF], AV=40[dB]
Phase Margin	θ	25°C	-	50°	-	-	CL=25[pF], AV=40[dB]
Total Harmonic Distortion	THD	25°C	-	0.05	-	%	VOUT=1[Vp-p],f=1[kHz]

(\*) Absolute value

(\*) Full range : BU7441, BU7442 : Ta=-40[°C] to +85[°C] BU7441S, BU7442S : Ta=-40[°C] to +105[°C]

(\*) Under the high temperature environment, consider the power dissipation of IC when selecting the output current.

When the terminal short circuits are continuously output, the output current is reduced to climb to the temperature inside IC.

● Example of electrical characteristics

○ BU7261 family




Fig. 1 Derating curve




Fig. 2 Derating curve




Fig. 3 Supply Current - Supply Voltage




Fig. 4 Supply Current - Ambient Temperature




Fig. 5 Output Voltage High - Supply Voltage (RL=10[kΩ])




Fig. 6 Output Voltage High - Ambient Temperature (RL=10[kΩ])




Fig. 7 Output Voltage Low - Supply Voltage (RL=10[kΩ])




Fig. 8 Output Voltage Low - Ambient Temperature (RL=10[kΩ])




Fig. 9 Output Source Current - Output Voltage (VDD=3.0[V])




Fig. 10 Output Source Current - Ambient Temperature (VOUT=VDD-0.4[V])




Fig. 11 Output Sink Current - Output Voltage (VDD=3[V])




Fig. 12 Output Sink Current - Ambient Temperature (VOUT=VSS+0.4[V])

(\*) The above data is ability value of sample, it is not guaranteed. BU7261G : -40[°C]~+85[°C] BU7261SG : -40[°C]~+105[°C]






Fig. 13  
 Input Offset Voltage – Supply Voltage  
 (Vicm=VDD, VOUT=1.5[V])




Fig. 14  
 Input Offset Voltage – Ambient Temperature  
 (Vicm=VDD, VOUT=1.5[V])




Fig. 15  
 Input Offset Voltage – Input Voltage  
 (VDD=3[V])




Fig. 16  
 Large Signal Voltage Gain  
 – Supply Voltage




Fig. 17  
 Large Signal Voltage Gain  
 – Ambient Temperature




Fig. 18  
 Common Mode Rejection Ratio  
 – Supply Voltage




Fig. 19  
 Common Mode Rejection Ratio  
 – Ambient Temperature




Fig. 20  
 Power Supply Rejection Ratio  
 – Ambient Temperature




Fig. 21  
 Slew Rate L-H – Ambient Temperature




Fig. 22  
 Slew Rate H-L – Ambient Temperature




Fig. 23  
 Gain - Frequency

(\*) The above data is ability value of sample, it is not guaranteed. BU7261G : -40[°C]~+85[°C] BU7261SG : -40[°C]~+105[°C]



OBU7262 family




Fig. 24  
Derating curve




Fig. 25  
Derating curve




Fig. 26  
Supply Current - Supply Voltage




Fig. 27  
Supply Current - Ambient Temperature




Fig. 28  
Output Voltage High - Supply Voltage  
(RL=10[kΩ])




Fig. 29  
Output Voltage High - Ambient Temperature  
(RL=10[kΩ])




Fig. 30  
Output Voltage Low - Supply Voltage  
(RL=10[kΩ])




Fig. 31  
Output Voltage Low - Ambient Temperature  
(RL=10[kΩ])




Fig. 32  
Output Source Current - Output Voltage  
(VDD=3.0[V])




Fig. 33  
Output Source Current - Ambient Temperature  
(VOUT=VDD-0.4[V])




Fig. 34  
Output Sink Current - Output Voltage  
(VDD=3[V])




Fig. 35  
Output Sink Current - Ambient Temperature  
(VOUT=VSS+0.4[V])

(\*) The above data is ability value of sample, it is not guaranteed. BU7262 F/FVM : -40[°C]~+85[°C] BU7262S F/FVM : -40[°C]~+105[°C]

○BU7262 family




Fig. 36

Input Offset Voltage – Supply Voltage  
 (Vicm=VDD, VOuT=1.5[V])




Fig. 37

Input Offset Voltage – Ambient Temperature  
 (Vicm=VDD, VOuT=1.5[V])




Fig. 38

Input Offset Voltage – Input Voltage  
 (VDD=3[V])




Fig. 39

Large Signal Voltage Gain  
 – Supply Voltage




Fig. 40

Large Signal Voltage Gain  
 – Ambient Temperature




Fig. 41

Common Mode Rejection Ratio  
 – Supply Voltage




Fig. 42

Common Mode Rejection Ratio  
 – Ambient Temperature




Fig. 43

Power Supply Rejection Ratio  
 – Ambient Temperature




Fig. 44

Slew Rate L-H – Ambient Temperature




Fig. 45

Slew Rate H-L – Ambient Temperature




Fig. 46

Gain - Frequency

(\*) The above data is ability value of sample, it is not guaranteed. BU7262 F/FVM : -40[°C]~+85[°C] BU7262S F/FVM : -40[°C]~+105[°C]

OBU7241 family




Fig. 47 Derating curve




Fig. 48 Derating curve




Fig. 49 Supply Current - Supply Voltage




Fig. 50 Supply Current - Ambient Temperature




Fig. 51 Output Voltage High - Supply Voltage (RL=10[kΩ])




Fig. 52 Output Voltage High - Ambient Temperature (RL=10[kΩ])




Fig. 53 Output Voltage Low - Supply Voltage (RL=10[kΩ])




Fig. 54 Output Voltage Low - Ambient Temperature (RL=10[kΩ])




Fig. 55 Output Source Current - Output Voltage (VDD=3.0[V])




Fig. 56 Output Source Current - Ambient Temperature (VOUT=VDD-0.4[V])




Fig. 57 Output Sink Current - Output Voltage (VDD=3[V])




Fig. 58 Output Sink Current - Ambient Temperature (VOUT=VSS+0.4[V])

(\*) The above data is ability value of sample, it is not guaranteed. BU7241G : -40[°C]~+85[°C] BU7241SG : -40[°C]~+105[°C]




Fig. 59

Input Offset Voltage – Supply Voltage  
 (V<sub>icm</sub>=V<sub>DD</sub>, V<sub>OUT</sub>=1.5[V])




Fig. 60

Input Offset Voltage – Ambient Temperature  
 (V<sub>icm</sub>=V<sub>DD</sub>, V<sub>OUT</sub>=1.5[V])




Fig. 61

Input Offset Voltage – Input Voltage  
 (V<sub>DD</sub>=3[V])




Fig. 62

Large Signal Voltage Gain  
 – Supply Voltage




Fig. 63

Large Signal Voltage Gain  
 – Ambient Temperature




Fig. 64

Common Mode Rejection Ratio  
 – Supply Voltage




Fig. 65

Common Mode Rejection Ratio  
 – Ambient Temperature




Fig. 66

Power Supply Rejection Ratio  
 – Ambient Temperature




Fig. 67

Slew Rate L-H – Ambient Temperature




Fig. 68

Slew Rate H-L – Ambient Temperature




Fig. 69

Gain - Frequency

(\*) The above data is ability value of sample, it is not guaranteed. BU7241G : -40[°C]~+85[°C] BU7241SG : -40[°C]~+105[°C]

OBU7242 family




Fig. 70  
Derating curve




Fig. 71  
Derating curve




Fig. 72  
Supply Current - Supply Voltage




Fig. 73  
Supply Current - Ambient Temperature




Fig. 74  
Output Voltage High - Supply Voltage  
(RL=10[kΩ])




Fig. 75  
Output Voltage High - Ambient Temperature  
(RL=10[kΩ])




Fig. 76  
Output Voltage Low - Supply Voltage  
(RL=10[kΩ])




Fig. 77  
Output Voltage Low - Ambient Temperature  
(RL=10[kΩ])




Fig. 78  
Output Source Current - Output Voltage  
(VDD=3.0[V])




Fig. 79  
Output Source Current - Ambient Temperature  
(VOUT=VDD-0.4[V])




Fig. 80  
Output Sink Current - Output Voltage  
(VDD=3[V])




Fig. 81  
Output Sink Current - Ambient Temperature  
(VOUT=VSS+0.4[V])

(\*) The above data is ability value of sample, it is not guaranteed. BU7242F/FVM : -40[°C]~+85[°C] BU7242SF/FVM : -40[°C]~+105[°C]

OBU7242 family




Fig. 82

Input Offset Voltage – Supply Voltage  
 (Vicm=VDD, VOUT=1.5[V])




Fig. 83

Input Offset Voltage – Ambient Temperature  
 (Vicm=VDD, VOUT=1.5[V])




Fig. 84

Input Offset Voltage – Input Voltage  
 (VDD=3[V])




Fig. 85

Large Signal Voltage Gain  
 – Supply Voltage




Fig. 86

Large Signal Voltage Gain  
 – Ambient Temperature




Fig. 87

Common Mode Rejection Ratio  
 – Supply Voltage




Fig. 88

Common Mode Rejection Ratio  
 – Ambient Temperature




Fig. 89

Power Supply Rejection Ratio  
 – Ambient Temperature




Fig. 90

Slew Rate L-H – Ambient Temperature




Fig. 91

Slew Rate H-L – Ambient Temperature




Fig. 92

Gain - Frequency

(\*) The above data is ability value of sample, it is not guaranteed. BU7242F/FVM : -40[°C]~+85[°C] BU7242SF/FVM : -40[°C]~+105[°C]

BU7461 family




Fig. 93  
Derating curve




Fig. 94  
Derating curve




Fig. 95  
Supply Current - Supply Voltage




Fig. 96  
Supply Current - Ambient Temperature




Fig. 97  
Output Voltage High - Supply Voltage




Fig. 98  
Output Voltage High - Ambient Temperature




Fig. 99  
Output Voltage Low - Supply Voltage  
( $R_L=10[k\Omega]$ )




Fig. 100  
Output Voltage Low - Ambient Temperature  
( $R_L=10[k\Omega]$ )




Fig. 101  
Output Source Current - Output Voltage  
( $V_{DD}=3.0[V]$ )




Fig. 102  
Output Source Current - Ambient Temperature  
( $V_{OUT}=V_{DD}-0.4[V]$ )




Fig. 103  
Output Sink Current - Output Voltage  
( $V_{DD}=3[V]$ )




Fig. 104  
Output Sink Current - Ambient Temperature  
( $V_{OUT}=V_{SS}+0.4[V]$ )

(\*) The above data is ability value of sample, it is not guaranteed. BU7461G : -40[°C] ~ +85[°C] BU7461SG : -40[°C] ~ +105[°C]



OBU7461 family




Fig. 105

Input Offset Voltage – Supply Voltage  
 (Vicm=VDD-1.2[V], VOUT=VDD/2)




Fig. 106

Input Offset Voltage – Ambient Temperature  
 (Vicm=VDD-1.2[V], VOUT=VDD/2)




Fig. 107

Input Offset Voltage – Input Voltage  
 (VDD=3[V])




Fig. 108

Large Signal Voltage Gain  
 – Supply Voltage




Fig. 109

Large Signal Voltage Gain  
 – Ambient Temperature




Fig. 110

Common Mode Rejection Ratio  
 – Supply Voltage




Fig. 111

Common Mode Rejection Ratio  
 – Ambient Temperature




Fig. 112

Power Supply Rejection Ratio  
 – Ambient Temperature




Fig. 113

Slew Rate L-H – Ambient Temperature




Fig. 114

Slew Rate H-L – Ambient Temperature




Fig. 115

Gain - Frequency

(\*) The above data is ability value of sample, it is not guaranteed. BU7461G : -40[°C]~+85[°C] BU7461SG : -40[°C]~+105[°C]

BU7462 family




Fig. 116 Derating curve




Fig. 117 Derating curve




Fig. 118 Supply Current - Supply Voltage




Fig. 119 Supply Current - Ambient Temperature




Fig. 120 Output Voltage High - Supply Voltage (RL=10[kΩ])




Fig. 121 Output Voltage High - Ambient Temperature (RL=10[kΩ])




Fig. 122 Output Voltage Low - Supply Voltage (RL=10[kΩ])




Fig. 123 Output Voltage Low - Ambient Temperature (RL=10[kΩ])




Fig. 124 Output Source Current - Output Voltage (VDD=3.0[V])




Fig. 125 Output Source Current - Ambient Temperature (VOUT=VDD-0.4[V])




Fig. 126 Output Sink Current - Output Voltage (VDD=3[V])




Fig. 127 Output Sink Current - Ambient Temperature (VOUT=VSS+0.4[V])

(\*) The above data is ability value of sample, it is not guaranteed. BU7461G : -40[°C]~+85[°C] BU7461SG : -40[°C]~+105[°C]

OBU7462 family




Fig. 128  
 Input Offset Voltage – Supply Voltage  
 (Vicm=VDD-1.2[V], VOUT=VDD/2)




Fig. 129  
 Input Offset Voltage – Ambient Temperature  
 (Vicm=VDD-1.2[V], VOUT=VDD/2)




Fig. 130  
 Input Offset Voltage – Input Voltage  
 (VDD=3[V])




Fig. 131  
 Large Signal Voltage Gain – Supply Voltage




Fig. 132  
 Large Signal Voltage Gain – Ambient Temperature




Fig. 133  
 Common Mode Rejection Ratio – Supply Voltage




Fig. 134  
 Common Mode Rejection Ratio – Ambient Temperature




Fig. 135  
 Power Supply Rejection Ratio – Ambient Temperature




Fig. 136  
 Slew Rate L-H – Ambient Temperature




Fig. 137  
 Slew Rate H-L – Ambient Temperature




Fig. 138  
 Gain - Frequency

(\*) The above data is ability value of sample, it is not guaranteed. BU7462F/FVM : -40[°C]~+85[°C] BU7462SF/FVM : -40[°C]~+105[°C]

OBU7441 family




Fig. 139  
Derating curve




Fig. 140  
Derating curve




Fig. 141  
Supply Current - Supply Voltage




Fig. 142  
Supply Current - Ambient Temperature




Fig. 143  
Output Voltage High - Supply Voltage  
( $R_L=10[k\Omega]$ )




Fig. 144  
Output Voltage High - Ambient Temperature  
( $R_L=10[k\Omega]$ )




Fig. 145  
Output Voltage Low - Supply Voltage  
( $R_L=10[k\Omega]$ )




Fig. 146  
Output Voltage Low - Ambient Temperature  
( $R_L=10[k\Omega]$ )




Fig. 147  
Output Source Current - Output Voltage  
( $V_{DD}=3.0[V]$ )




Fig. 148  
Output Source Current - Ambient Temperature  
( $V_{OUT}=V_{DD}-0.4[V]$ )




Fig. 149  
Output Sink Current - Output Voltage  
( $V_{DD}=3[V]$ )




Fig. 150  
Output Sink Current - Ambient Temperature  
( $V_{OUT}=V_{SS}+0.4[V]$ )

(\*) The above data is ability value of sample, it is not guaranteed. BU7441G :  $-40[^\circ C] \sim +85[^\circ C]$  BU7441SG :  $-40[^\circ C] \sim +105[^\circ C]$

OBU7441 family




Fig. 151

Input Offset Voltage – Supply Voltage  
 (Vicm=VDD-1.2[V], VOUT=VDD/2)




Fig. 152

Input Offset Voltage – Ambient Temperature  
 (Vicm=VDD-1.2[V], VOUT=VDD/2)




Fig. 153

Input Offset Voltage – Input Voltage  
 (VDD=3[V])




Fig. 154

Large Signal Voltage Gain  
 – Supply Voltage




Fig. 155

Large Signal Voltage Gain  
 – Ambient Temperature




Fig. 156

Common Mode Rejection Ratio  
 – Supply Voltage




Fig. 157

Common Mode Rejection Ratio  
 – Ambient Temperature




Fig. 158

Power Supply Rejection Ratio  
 – Ambient Temperature




Fig. 159

Slew Rate L-H – Ambient Temperature




Fig. 160

Slew Rate H-L – Ambient Temperature




Fig. 161

Gain - Frequency

(\*) The above data is ability value of sample, it is not guaranteed. BU7441G : -40[°C]~+85[°C] BU7441SG : -40[°C]~+105[°C]




Fig. 162 Derating curve




Fig. 163 Derating curve




Fig. 164 Supply Current - Supply Voltage




Fig. 165 Supply Current - Ambient Temperature




Fig. 166 Output Voltage High - Supply Voltage (RL=10[kΩ])




Fig. 167 Output Voltage High - Ambient Temperature (RL=10[kΩ])




Fig. 168 Output Voltage Low - Supply Voltage (RL=10[kΩ])




Fig. 169 Output Voltage Low - Ambient Temperature (RL=10[kΩ])




Fig. 170 Output Source Current - Output Voltage (VDD=3.0[V])




Fig. 171 Output Source Current - Ambient Temperature (VOUT=VDD-0.4[V])




Fig. 172 Output Sink Current - Output Voltage (VDD=3[V])




Fig. 173 Output Sink Current - Ambient Temperature (VOUT=VSS+0.4[V])

(\*) The above data is ability value of sample, it is not guaranteed. BU7442F/FVM : -40[°C]~+85[°C] BU7442SF/FVM : -40[°C]~+105[°C]

○BU7442 family




Fig. 174

Input Offset Voltage – Supply Voltage  
 (Vicm=VDD-1.2[V], VOUT=VDD/2)




Fig. 175

Input Offset Voltage – Ambient Temperature  
 (Vicm=VDD-1.2[V], VOUT=VDD/2)




Fig. 176

Input Offset Voltage – Input Voltage  
 (VDD=3[V])




Fig. 177

Large Signal Voltage Gain – Supply Voltage




Fig. 178

Large Signal Voltage Gain – Ambient Temperature




Fig. 179

Common Mode Rejection Ratio – Supply Voltage




Fig. 180

Common Mode Rejection Ratio – Ambient Temperature




Fig. 181

Power Supply Rejection Ratio – Ambient Temperature




Fig. 182

Slew Rate L-H – Ambient Temperature




Fig. 183

Slew Rate H-L – Ambient Temperature




Fig. 184

Gain - Frequency

(\*) The above data is ability value of sample, it is not guaranteed. BU7442F/FVM : -40[°C]~+85[°C] BU7442SF/FVM : -40[°C]~+105[°C]



● Test circuit1 NULL method

○ Input-Output Full Swing BU7261/BU7241 family , BU7262/BU7242 family

VDD,VSS,EK,Vicm Unit : [V]

Parameter	VF	S1	S2	S3	VDD	VSS	EK	Vicm	Calculation
Input Offset Voltage	VF1	ON	ON	OFF	3	0	-1.5	3	1
Large Signal Voltage Gain	VF2	ON	ON	ON	3	0	-0.5	1.5	2
	VF3						-2.5		
Common-mode Rejection Ratio (Input Common-mode Voltage Range)	VF4	ON	ON	OFF	3	0	-1.5	0	3
	VF5						-1.5	3	
Power Supply Rejection Ratio	VF6	ON	ON	OFF	1.8	0	-0.9	0	4
	VF7				5.5				

○ Ground Sense BU7461/BU7441 family , BU7462/BU7442 family

VDD,VSS,EK,Vicm Unit : [V]

Parameter	VF	S1	S2	S3	VDD	VSS	EK	Vicm	Calculation
Input Offset Voltage	VF1	ON	ON	OFF	3	0	-1.5	1.8	1
Large Signal Voltage Gain	VF2	ON	ON	ON	3	0	-0.5	0.9	2
	VF3						-2.5		
Common-mode Rejection Ratio (Input Common-mode Voltage Range)	VF4	ON	ON	OFF	3	0	-1.5	0	3
	VF5						-1.5	1.8	
Power Supply Rejection Ratio	VF6	ON	ON	OFF	1.7	0	-0.9	0	4
	VF7				5.5				

-Calculation-

1. Input Offset Voltage (Vio)

$$V_{io} = \frac{|VF1|}{1+R_f/R_s} \text{ [V]}$$

2. Large Signal Voltage Gain (Av)

$$A_v = 20\text{Log} \frac{2 \times (1+R_f/R_s)}{|VF2-VF3|} \text{ [dB]}$$

3. Common-mode Rejection Ratio (CMRR)

$$\text{CMRR} = 20\text{Log} \frac{1.8 \times (1+R_f/R_s)}{|VF4-VF5|} \text{ [dB]}$$

4. Power Supply Rejection Ratio (PSRR)

$$\text{PSRR} = 20\text{Log} \frac{3.8 \times (1+R_f/R_s)}{|VF6-VF7|} \text{ [dB]}$$




Fig. 185 Test circuit 1 (one channel only)

● Test circuit2 switch condition

Unit : [V]

SW No.	SW 1	SW 2	SW 3	SW 4	SW 5	SW 6	SW 7	SW 8	SW 9	SW 10	SW 11	SW 12
Supply Current	OFF	OFF	ON	OFF	ON	OFF	OFF	OFF	OFF	OFF	OFF	OFF
Maximum Output Voltage RL=10 [kΩ]	OFF	ON	OFF	OFF	ON	OFF	OFF	ON	OFF	OFF	ON	OFF
Output Current	OFF	ON	OFF	OFF	ON	OFF	OFF	OFF	OFF	ON	OFF	OFF
Slew Rate	OFF	OFF	ON	OFF	OFF	OFF	ON	OFF	ON	OFF	OFF	ON
Maximum Frequency	ON	OFF	OFF	ON	ON	OFF	OFF	OFF	ON	OFF	OFF	ON




Fig. 186. Test circuit2




Fig. 187. Slew rate input output wave

(Input-Output Full Swing BU7261/7241 family , BU7262/7242 family)




Fig. 188. Slew rate input output wave

(Ground Sense BU7461/7441 family , BU7462/7442 family)

● Test circuit3 Channel separation






Fig. 189. Test circuit3

● Schematic diagram


○ Input-Output Full Swing : BU7261/BU7241 family , BU7262/BU7242 family



○ Ground Sense : BU7461/BU7441 family , BU7462/BU7442 family




- Examples of circuit
- Voltage follower




Voltage gain is 0 [dB].  
 This circuit controls output voltage ( $V_{out}$ ) equal input voltage ( $V_{in}$ ), and keeps  $V_{out}$  with stable because of high input impedance and low output impedance.  
 $V_{out}$  is shown next formula.  
 $V_{out} = V_{in}$

- Inverting amplifier



For inverting amplifier,  $V_{in}$  is amplified by voltage gain decided  $R1$  and  $R2$ , and phase reversed voltage is outputed.  
 $V_{out}$  is shown next formula.  
 $V_{out} = -(R2/R1) \cdot V_{in}$   
 Input impedance is  $R1$ .

- Non-inverting amplifier



For non-inverting amplifier,  $V_{in}$  is amplified by voltage gain decided  $R1$  and  $R2$ , and phase is same with  $V_{in}$ .  
 $V_{out}$  is shown next formula.  
 $V_{out} = (1 + R2/R1) \cdot V_{in}$   
 This circuit realizes high input impedance because Input impedance is operational amplifier's input Impedance.

**● Description of electrical characteristics**

Described here are the terms of electric characteristics used in this technical note. Items and symbols used are also shown. Note that item name and symbol and their meaning may differ from those on another manufacture's document or general document.

**1. Absolute maximum ratings**

Absolute maximum rating item indicates the condition which must not be exceeded. Application of voltage in excess of absolute maximum rating or use out of absolute maximum rated temperature environment may cause deterioration of characteristics.

**1.1 Power supply voltage (VDD/VSS)**

Indicates the maximum voltage that can be applied between the positive power supply terminal and negative power supply terminal without deterioration or destruction of characteristics of internal circuit.

**1.2 Differential input voltage (Vid)**

Indicates the maximum voltage that can be applied between non-inverting terminal and inverting terminal without deterioration and destruction of characteristics of IC.

**1.3 Input common-mode voltage range (Vicm)**

Indicates the maximum voltage that can be applied to non-inverting terminal and inverting terminal without deterioration or destruction of characteristics. Input common-mode voltage range of the maximum ratings not assure normal operation of IC. When normal operation of IC is desired, the input common-mode voltage of characteristics item must be followed.

**1.4 Power dissipation (Pd)**

Indicates the power that can be consumed by specified mounted board at the ambient temperature 25°C (normal temperature). As for package product, Pd is determined by the temperature that can be permitted by IC chip in the package (maximum junction temperature) and thermal resistance of the package.

**2. Electrical characteristics item****2.1 Input offset voltage (Vio)**

Indicates the voltage difference between non-inverting terminal and inverting terminal. It can be translated into the input voltage difference required for setting the output voltage at 0 [V].

**2.2 Input offset current (Iio)**

Indicates the difference of input bias current between non-inverting terminal and inverting terminal.

**2.3 Input bias current (Ib)**

Indicates the current that flows into or out of the input terminal. It is defined by the average of input bias current at non-inverting terminal and input bias current at inverting terminal.

**2.4 Circuit current (ICC)**

Indicates the IC current that flows under specified conditions and no-load steady status.

**2.5 High level output voltage / Low level output voltage (VOH/VOL)**

Indicates the voltage range that can be output by the IC under specified load condition. It is typically divided into high-level output voltage and low-level output voltage. High-level output voltage indicates the upper limit of output voltage. Low-level output voltage indicates the lower limit.

**2.6 Large signal voltage gain (AV)**

Indicates the amplifying rate (gain) of output voltage against the voltage difference between non-inverting terminal and inverting terminal. It is normally the amplifying rate (gain) with reference to DC voltage.

$$A_v = (\text{Output voltage fluctuation}) / (\text{Input offset fluctuation})$$

**2.7 Input common-mode voltage range (Vicm)**

Indicates the input voltage range where IC operates normally.

**2.8 Common-mode rejection ratio (CMRR)**

Indicates the ratio of fluctuation of input offset voltage when in-phase input voltage is changed. It is normally the fluctuation of DC.

$$CMRR = (\text{Change of Input common-mode voltage}) / (\text{Input offset fluctuation})$$

**2.9 Power supply rejection ratio (PSRR)**

Indicates the ratio of fluctuation of input offset voltage when supply voltage is changed. It is normally the fluctuation of DC.

$$PSRR = (\text{Change of power supply voltage}) / (\text{Input offset fluctuation})$$

**2.10 Channel separation (CS)**

Indicates the fluctuation of input offset voltage or that of output voltage with reference to the change of output voltage of driven channel.

2.11 Slew rate (SR)

Indicates the time fluctuation ratio of voltage output when step input signal is applied.

2.12 Unity gain frequency (ft)

Indicates a frequency where the voltage gain of Op-Amp is 1.

2.13 Total harmonic distortion + Noise (THD+N)

Indicates the fluctuation of input offset voltage or that of output voltage with reference to the change of output voltage of driven channel.

2.14 Input referred noise voltage (Vn)

Indicates a noise voltage generated inside the operational amplifier equivalent by ideal voltage source connected in series with input terminal.

●Derating curve

Power dissipation (total loss) indicates the power that can be consumed by IC at Ta=25°C(normal temperature).

IC is heated when it consumed power, and the temperature of IC chip becomes higher than ambient temperature.

The temperature that can be accepted by IC chip depends on circuit configuration, manufacturing process, and consumable power is limited.

Power dissipation is determined by the temperature allowed in IC chip (maximum junction temperature) and thermal resistance of package (heat dissipation capability).

The maximum junction temperature is typically equal to the maximum value in the storage package (heat dissipation capability).

The maximum junction temperature is typically equal to the maximum value in the storage temperature range. Heat generated by consumed power of IC radiates from the mold resin or lead frame of the package.

The parameter which indicates this heat dissipation capability (hardness of heat release) is called thermal resistance, represented by the symbol  $\theta_{ja}$ [°C/W].

The temperature of IC inside the package can be estimated by this thermal resistance.

Fig.190 (a) shows the model of thermal resistance of the package. Thermal resistance  $\theta_{ja}$ , ambient temperature Ta, junction temperature Tj, and power dissipation Pd can be calculated by the equation below :

$$\theta_{ja} = (T_j - T_a) / P_d \quad [^{\circ}\text{C}/\text{W}] \quad \dots \dots (I)$$

Derating curve in Fig.190(b) indicates power that can be consumed by IC with reference to ambient temperature.

Power that can be consumed by IC begins to attenuate at certain ambient temperature.

This gradient is determined by thermal resistance  $\theta_{ja}$ . Thermal resistance  $\theta_{ja}$  depends on chip size, power consumption, package, ambient temperature, package condition, wind velocity, etc even when the same of package is used.

Thermal reduction curve indicates a reference value measured at a specified condition. Fig191(c)-(f) show a derating curve for an example of BU7261/41family,BU7262/42family,7461/7441family,7462/7442family.







Fig. 190 Thermal resistance and derating




(c) BU7261G BU7241G  
 BU7461G BU7441G



(d) BU7262F/FVM BU7242F/FVM  
 BU7462F/FVM BU7442F/FVM



(e) BU7261SG BU7241SG  
 BU7461SG BU7441SG



(f) BU7262S F/FVM BU7242S F/FVM  
 BU7462S F/FVM BU7442S F/FVM

(*14)	(*15)	(*16)	Unit
5.4	6.2	4.8	[mW/°C]

When using the unit above Ta=25[°C], subtract the value above per degree[°C]. Permissible dissipation is the value when FR4 glass epoxy board 70[mm]×70[mm]×1.6[mm] (cooper foil area below 3[%]) is mounted.

Fig. 191 Derating Curve



●Cautions on use

1) Absolute maximum ratings

Absolute maximum ratings are the values which indicate the limits,within which the given voltage range can be safely charged to the terminal.However, it does not guarantee the circuit operation.

2) Applied voltage to the input terminal

For normal circuit operation of voltage comparator, please input voltage for itsinput terminal within input common mode voltage  $V_{DD}+0.3[V]$ .

Then, regardless of power supply voltage,  $V_{SS}-0.3[V]$  can be applied to input terminals without deterioration or destruction of its characteristics.

3) Operating power supply (split power supply/single power supply)

The voltage comparator operates if a given level of voltage is applied between VDD and VSS.

Therefore, the operational amplifier can be operated under single power supply or split power supply.

4) Power dissipation (pd)

If the IC is used under excessive power dissipation. An increase in the chip temperature will cause deterioration of the radical characteristics of IC.

For example, reduction of current capability. Take consideration of the effective power dissipation and thermal design with a sufficient margin. Pd is reference to the provided power dissipation curve.

5) Short circuits between pins and incorrect mounting

Short circuits between pins and incorrect mounting when mounting the IC on a printed circuits board, take notice of the direction and positioning of the IC.

If IC is mounted erroneously, It may be damaged. Also, when a foreign object is inserted between output, between output and VDD terminal or VSS terminal which causes short circuit, the IC may be damaged.

6) Using under strong electromagnetic field

Be careful when using the IC under strong electromagnetic field because it may malfunction.

7) Usage of IC

When stress is applied to the IC through warp of the printed circuit board, The characteristics may fluctuate due to the piezo effect. Be careful of the warp of the printed circuit board.

8) Testing IC on the set board

When testing IC on the set board, in cases where the capacitor is connected to the low impedance,make sure to discharge per fabrication because there is a possibility that IC may be damaged by stress.

When removing IC from the set board, it is essential to cut supply voltage.As a countermeasure against the static electricity, observe proper grounding during fabrication process and take due care when carrying and storage it.

9) The IC destruction caused by capacitive load

The transistors in circuits may be damaged when VDD terminal and VSS terminal is shorted with the charged output terminal capacitor.When IC is used as a operational amplifier or as an application circuit,where oscillation is not activated by an output capacitor,the output capacitor must be kept below  $0.1[\mu F]$  in order to prevent the damage mentioned above.

10)Decoupling capacitor

Insert the decoupling capacitance between VDD and VSS, for stable operation of operational amplifier.

11)Latch up

Be careful of input voltage that exceed the VDD and VSS. When CMOS device have sometimes occur latch up operation. And protect the IC from abnormaly noise

**B U**

**7 2 6 2**

**F V M**

**- T R**


Part No.

Part No.  
 · Input-Output Full Swing  
 7261 , 7261S  
 7241 , 7241S  
 7262 , 7262S  
 7242 , 7242S  
 · Ground Sense  
 7461 , 7461S  
 7441 , 7441S  
 7462 , 7462S  
 7442 , 7442S

Package  
 G: SSOP5  
 F: SOP8  
 FVM: MSOP8


Packaging and forming specification  
 E2: Embossed tape and reel  
 (SOP8)  
 TR: Embossed tape and reel  
 (SSOP5/MSOP8)

**SOP8**




<Tape and Reel information>

Tape	Embossed carrier tape
Quantity	2500pcs
Direction of feed	E2 ( The direction is the 1pin of product is at the upper left when you hold reel on the left hand and you pull out the tape on the right hand )




**SSOP5**




<Tape and Reel information>

Tape	Embossed carrier tape
Quantity	3000pcs
Direction of feed	TR ( The direction is the 1pin of product is at the upper right when you hold reel on the left hand and you pull out the tape on the right hand )




**MSOP8**



<Tape and Reel information>

Tape	Embossed carrier tape
Quantity	3000pcs
Direction of feed	TR ( The direction is the 1pin of product is at the upper right when you hold reel on the left hand and you pull out the tape on the right hand )



## Notes

No copying or reproduction of this document, in part or in whole, is permitted without the consent of ROHM Co.,Ltd.

The content specified herein is subject to change for improvement without notice.

The content specified herein is for the purpose of introducing ROHM's products (hereinafter "Products"). If you wish to use any such Product, please be sure to refer to the specifications, which can be obtained from ROHM upon request.

Examples of application circuits, circuit constants and any other information contained herein illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.

Great care was taken in ensuring the accuracy of the information specified in this document. However, should you incur any damage arising from any inaccuracy or misprint of such information, ROHM shall bear no responsibility for such damage.

The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM and other parties. ROHM shall bear no responsibility whatsoever for any dispute arising from the use of such technical information.

The Products specified in this document are intended to be used with general-use electronic equipment or devices (such as audio visual equipment, office-automation equipment, communication devices, electronic appliances and amusement devices).

The Products specified in this document are not designed to be radiation tolerant.

While ROHM always makes efforts to enhance the quality and reliability of its Products, a Product may fail or malfunction for a variety of reasons.

Please be sure to implement in your equipment using the Products safety measures to guard against the possibility of physical injury, fire or any other damage caused in the event of the failure of any Product, such as derating, redundancy, fire control and fail-safe designs. ROHM shall bear no responsibility whatsoever for your use of any Product outside of the prescribed scope or not in accordance with the instruction manual.

The Products are not designed or manufactured to be used with any equipment, device or system which requires an extremely high level of reliability the failure or malfunction of which may result in a direct threat to human life or create a risk of human injury (such as a medical instrument, transportation equipment, aerospace machinery, nuclear-reactor controller, fuel-controller or other safety device). ROHM shall bear no responsibility in any way for use of any of the Products for the above special purposes. If a Product is intended to be used for any such special purpose, please contact a ROHM sales representative before purchasing.

If you intend to export or ship overseas any Product or technology specified herein that may be controlled under the Foreign Exchange and the Foreign Trade Law, you will be required to obtain a license or permit under the Law.



Thank you for your accessing to ROHM product informations.  
More detail product informations and catalogs are available, please contact us.

## ROHM Customer Support System

<http://www.rohm.com/contact/>