

CUTTER, INTERFACE BOARD & CPU

ACU6205 AUTO CUTTER

The ACU6205 is a compact and lightweight circular cut type automatic cutter developed for the LTP1245 thermal line printer mechanism.

- Full cut is available
- Easily mounts on printer mechanism, opens for easy maintenance



ACU6205

IF1001-01B INTERFACE BOARD FOR LTP1245 SERIES

The IF1001-01B is an interface board used specifically for the LTP1245 Series. It is equipped with 8-bit parallel and serial TTL data input terminals. The IF1001-01B brings its printing functions into full play using a wide variety of characters and function commands.

PT100P01/PT101P01 CPU FOR LTP1245 SERIES

- Prints with less current using dynamic division control in accordance with the number of dots to be activated
- Supports both parallel and serial input
- Ensures high-quality print by measuring the temperature and voltage, and adjusting the print density
- Provides a wide variety of user-defined character functions including double-width/double-height, inverse print, underlining, and character spacing control; character string
- Supports bit image graphics and characters
- Provides a ruler line function which enables ruler lines and characters to be easily superimposed
- Stamp function
- Auto paper loading function

Model	IF1001-01B
Applicable mechanism	All LTP1245 Series
CPU	PT100P01/PT500GA1
Input control method	8-bit parallel (modified Centronics)
	Serial (TTL level)
Character type	222-IBM compatible
	126-Japanese kana
Dimensions (WxDxH) mm	70.0 x 100.0 x 12.0
Weight (g)	40
Operating voltage (Vcc)	-5 VDC \pm 0.5
Current consumption (Icc)	Max. 20 mA @ 5 VDC (standby)
	Max. 200 mA @ 5 VDC (printing)
Operating temperature ($^{\circ}$ C)	-5 to 50
Storage temperature ($^{\circ}$ C)	-20 to 60
Model	PT100P01 / PT101P01
Applicable mechanism	All LTP1245 Series
Package form	80-pin flat package
Dimensions (WxDxH) mm	22.8 x 16.8 x 3.05
Configuration	C-MOS LSI
Input method	8-bit parallel (Centronics), Asynchronous serial
Operating voltage (Vcc)	5 VDC \pm 0.5
Operating frequency (MHz)	16 \pm 0.5%
Remarks	Use these CPUs and a gate array (PT500GA1) as a pair PT101P01 for use with auto cutter
Model	ACU6205
Cut Method	Circular cutter type
Cut width (mm)	58 mm
Cut condition	full cut
Drive voltage (VDC)	Motor 4.2V to 6.0V Detector 5V \pm 10%
Starting current (A)	1.2A max.
Operating time (ms/cycle)	0.6 sec. (max.) at 6.0 V
Cut frequency (cuts/minute)	30 max.
Life (cuts)	300,000 (M.C.B.F.)
Dimensions (WxDxH) mm	81.9 x 54 x 12
Weight (g)	50
Operating temperature ($^{\circ}$ C)	0 to 50
Storage temperature ($^{\circ}$ C)	-20 to 60
Paper thickness (μ m)	75