

FU-624SHL-10M21/10M22/12M21/12M22

1.55 μ m LD MODULE WITH SINGLEMODE FIBER PIGTAIL

DESCRIPTION

Module type FU-624SHL-XXMXX has been developed for coupling a singlemode optical fiber and a 1.55 μ m wavelength InGaAsP LD (Laser diode). FU-624SHL-XXMXX is suitable to light source for measuring instruments.(especially, OTDR)

FEATURES

- High optical output power
- Emission wavelength is in 1.55 μ m band
- Built-in thermal electric cooler
- Dual-in-line package

APPLICATION

OTDR

ABSOLUTE MAXIMUM RATINGS (T_{LD} = 25°C)


Parameter	Symbol	Conditions	Rating	Unit
Laser diode	Reverse voltage	V _{RL}	—	2
	Forward current	I _{FL}	Pulse (Note 1)	1
Cooler	Voltage	V _{pem}	—	2.4
	Current	I _{pem}	—	1.2
Operating case temperature	T _c	—	—20~+65	°C
Storage temperature	T _{stg}	—	—40~+70	°C

Note 1. Pulse condition : Pulse width $\leq 10\mu$ s, Duty ratio $\leq 1\%$


2. Even if the thermo-electric cooler (TEC) is operated within the rated conditions, uncontrolled current loading or operation without heatsink may easily damage the module by exceeding the storage temperature range. Thermistor resistance should be properly monitored by the feedback circuit during TEC operation to avoid the catastrophic damage.

OUTLINE DIAGRAM

(Unit : mm)



PIN	FUNCTION
1	COOLER ANODE
2	NC
3	NC
4	NC
5	LASER ANODE, GND
6	NC
7	NC
8	NC
9	LASER CATHODE
10	LASER ANODE, GND
11	THERMISTOR
12	THERMISTOR
13	NC
14	COOLER CATHODE



FU-624SHL-10M21/10M22/12M21/12M22

BOTTOM VIEW

FU-624SHL-10M21/10M22/12M21/12M22

1.55 μm LD MODULE WITH SINGLEMODE FIBER PIGTAIL

CHARACTERISTICS (TLD = 25 °C, Tc = 25 °C, Unless otherwise noted)


Parameter		Symbol	Test conditions	Limits						Unit
				FU-624SHL-10M2X (Note 4)			FU-624SHL-12M2X (Note 4)			
				Min.	Typ.	Max.	Min.	Typ.	Max.	
Threshold current		I _{th}	—	—	30	50	—	30	50	mA
Operating current		I _{OP}	Pulse (Note 1)	500	700	900	500	700	900	mA
Operating voltage		V _{OP}	I _F = I _{OP} , Pulse (Note 1)	—	—	5	—	—	5	V
Optical output power from fiber end (Note 4)		P _F	I _F = I _{OP} , Pulse (Note 1)	100	—	—	120	—	—	mW
-XXM21	Central wavelength (Note 4)	λ _c	I _F = I _{OP} , Pulse (Note 1)	1540	1550	1560	1540	1550	1560	nm
-XXM22				1530	1550	1570	1530	1550	1570	
Spectral width (RMS)		Δλ	I _F = I _{OP} , Pulse (Note 1)	—	—	15	—	—	15	nm
Pulse droop (Note 3)		ΔP _F	I _F = I _{OP} , Pulse (Note 1)	—	—	20	—	—	20	%
Rise and fall time		t _r , t _f	I _B = I _{th} , 10~90 % (Note 2)	—	1	2	—	1	2	ns

Note 1. Pulse condition : Pulse width ≤ 10 μs, Duty ratio ≤ 1 %

2. Ia : Bias current (LD)

3.

$$\Delta P_f = \frac{P_{f1} - P_{f2}}{P_{f1}} \times 100$$



4.

Type number	Pf(25 °C)	λc(25 °C)
FU-624SHL-10M21	100mW(min)	1310 ± 10nm
FU-624SHL-10M22		1310 ± 20nm
FU-624SHL-12M21	120mW(min)	1310 ± 10nm
FU-624SHL-12M22		1310 ± 20nm

THERMAL CHARACTERISTICS (TLD = 25 °C, Tc = - 20 ~ + 65 °C)

Parameter	Symbol	Test conditions	Limits			Unit
			Min.	Typ.	Max.	
Thermistor resistance	Rth	TLD = 25 °C	9	10	11	kΩ
B constant of thermistor resistance	B	—	—	3950	—	K
Cooking capacity	ΔT	TLD = 65 °C	40	—	—	°C
Cooler current	Ipe	ΔT = 40 °C	—	0.6	1	A
Cooler voltage	Vpe	ΔT = 40 °C	—	1.6	2	V

OPTICAL-FIBER SPECIFICATIONS

Parameter	Limits	Unit
Type	SM	—
Mode field dia.	10 ± 1	μm
Cladding dia.	125 ± 2	μm
Jacket dia.	0.9 typ.	mm



FU-624SHL-10M21/10M22/12M21/12M22

1.55 μ m LD MODULE WITH SINGLEMODE FIBER PIGTAIL

TYPICAL CHARACTERISTICS

