

## KVR100X72C3/256 256MB PC100 CL3 168-Pin ECC SDRAM DIMM Module


### DESCRIPTION:

This document describes ValueRAM's 32M x 72-bit (256MB), CAS Latency 3 (CL3) SDRAM (Synchronous DRAM) PC100 ECC memory module. The components on this module include eighteen 16M x 8-bit (4M x 8-bit x 4 Bank / PC100 components) SDRAM in TSOP packages. This 168-pin DIMM uses gold contact fingers and requires +3.3V. The electrical and mechanical specifications are as follows:

### FEATURES:

|                          |                                               |
|--------------------------|-----------------------------------------------|
| ✓ CLK Cycle Time (tCC)   | min. = 10ns (CAS Latency = 3) / max. = 1000ns |
| ✓ Row Cycle Time (tRC)   | 70ns                                          |
| ✓ CLK to Output (tSAC)   | max. = 6ns (CAS Latency = 3)                  |
| ✓ Single Power Supply of | +3.3V (+/- .3V)                               |
| ✓ Power                  | 4.728 W (operating)                           |
| ✓ UL Rating              | 94 V - 0                                      |

**Note:** The module defined in this data sheet is one of several configurations available under this part number. While all configurations are compatible, the DRAM combination and/or the module height may vary from what is described here. However, in no configuration will the module height exceed 1.375" (34.92mm).



**Figure 1: KVR100X72C3/256 168-Pin SDRAM Module**