# PPE

# **PPC-7500**

10.4" Panel PC with Pentium<sup>®</sup> M Solution

# Features and Benefits:

- Supports Intel<sup>®</sup> Pentium<sup>®</sup> M / Celeron<sup>®</sup> M CPU up to 1.8 GHz
- Intel<sup>®</sup> 855GME Chipset
- Low power consumption and economical solution
- Compact size with high performance
- High speed Gigabit LAN
- On-board IDE interface, Type II
  CompactFlash slot
- High precision touchscreen
- Built-in PC/104-Plus support



PROTECH SYSTEMS

No. 24, Lane 365, Yang Guang St., Nei Hu District, Taipei 114, Taiwan, R.O.C. Tel: +886-2-8751-1111 Fax: +886-2-8751-1199 Email: sales@protech.com.tw http://www.protech.com.tw






emperature Meni		. Je	e Inj	1.00	? Temp			J-AE			oni 108
Temp.	1	2	3	4	5	6	7	8	9	Temp.	Oil
Present	0	0	0	0	0	0	0	0	0	Present	0
Setting	0	0	0	0	0	0	0	0	0	Pre - Heat	0
Preserve	0	0	0	0	0	0	0	0	0	Cooling	0
Up Limit	0	0	0	0	0	0	0	0	0	Stop	0
Down Limit	0	0	0	0	0	0	0	0	0	101000000000000000000000000000000000000	in second
Power										Pre - Heat	Off
Thermo							1	1			
Heat Ratio( 1: 0 2: 0 1:Temp		70 E	: Disable : Disable 3:Hop	٠	0 0 4:	с С	1023	Start Ti Temp Dr		01 0 7:	°C 8:Expert
	6	Act Alar		0.0	)		Sci	Max Min rew Pos ep Time			100 100 100 0 / 100 100


# **PPC-7500** 10.4" Panel PC with Pentium<sup>®</sup> M Solution

# Front View

## Rear View

### Side View






**Digital I/O** 

**Brightness Control** 

LAN

VGA



Unit: mm

Specification	
Systems	
CPU Support	Intel <sup>®</sup> Pentium <sup>®</sup> M / Celeron <sup>®</sup> M up to 1.8GHz
Memory Support	1 x 200pin DDR SO-DIMM,
	Support DDR 333 SDRAM up to 1GB
Front Bazel	Aluminum
IP65 / NEMA4	Yes
Power Supply	AC 110W power supply
O.S. Support	Win 98SE / 2000 / XP / CE.net, Linux Redhat 8.0/9.0
Dimension (W x H x D)	280 x 232 x 80 mm (11.02" x 9.13" x 3.15")
System Weight	6 Kg (13.22lb)
VESA Mounting Support	75mm / 100mm
Certificate	CE / FCC

2 x USB2.0

Line in / Line out / MIC in

1 x parallel port (SPP / EPP / ECP)

2 x COMs, COM1 supports +5V or +12V, COM2 for RS232/422/485, supports +5V only

2

Drive Bay	1 x 2.5" HDD, 1 x IDE CF slot on board
Expansion Slots	PC104+ / 1 x USB CF slot on back cove
Display	
LCD	10.4" SVGA TFT LCD
Touch Screen	5W Analog resistive (USB interface)
Environment	
Operating Temp	$0^{\circ} \sim 40^{\circ}$ C

N/A

N/A

10/100/1000Mbps

VR on rear panel

Linvironment	
Operating Temp.	$0^{\circ} \sim 40^{\circ} C$
Storage Temp.	-20° ~ 60°C
Humidity	20% ~ 90%

Ordering	
PPC-7500	Panel PC with 10.4" LCD, S478 Pentium
	M CPU board, resistive touchscreen ,
	110W AC power supply

USB

Audio

Parallel

KB / Mouse

Serial Port

All of trademarks and brand names are the property of their owners. Trademark "Protech" is the property of Protech Systems Co., Ltd. All information contained in this document is subject to change without any prior notice. This catalog is copyrighted in DEC. 2006.

