

SPECIFICATION SHEET

JFW MODEL 50P-1778

SOLID STATE PROGRAMMABLE ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	800-2200 MHz
Impedance	50 Ohms nominal
Attenuation Range	0-127 dB in 1 dB steps
Attenuation Steps	1, 2, 4, 8, 16, 32 and 64 dB
VSWR	1.4:1 maximum
Attenuation Accuracy	± 0.3 dB or 2% of programmed (whichever is greater)
Insertion Loss	5.2 dB maximum 3.1 dB typical @ 800 MHz 4.8 dB typical @ 2200 MHz
RF Input Power	+20 dBm operating +24 dBm (1 dB compression)
Switching Speed	5 microseconds
DC Supply	+5 Vdc @ 250 mA maximum
Control Logic (7 Lines)	TTL Low for Thru Path TTL High for Attenuation
RF Connector	SMA female
Physical Size	See outline drawing 092-5410-01

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	05/04/2007		TRS 05/04/2007				
15807	05/02/2008	A	TRS 05/02/2008				