

5962-E1551

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

1. SCOPE

1.1 Scope. This drawing describes device requirements for class B microcircuits in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices".

1.2 Part number. The complete part number shall be as shown in the following example:



1.2.1 Device types. The device types shall identify the circuit function as follows:

Device type	Generic number	Circuit function
01	35074	Quad operational amplifier
02	35074A	Quad operational amplifier

1.2.2 Case outline. The case outline shall be as designated in appendix C of MIL-M-38510, and as follows:

Outline letter	Case outline
C	D-1 (14-lead, .785" x .310" x .200"), dual-in-line package

1.3 Absolute maximum ratings.

Power supply voltage (from V+ to V-)	- - - - - +44 V
Input differential range	- - - - - 1/
Input voltage range	- - - - - 1/
Power dissipation (P _D)	- - - - - 250 mW
Output short circuit duration (T _S)	- - - - - Indefinite
Ambient operating temperature range (T _A)	- - - - - -55°C to +125°C
Storage temperature range (T _{STG})	- - - - - -65°C to +150°C
Junction temperature (T _J)	- - - - - 160°C
Thermal resistance, junction-to-case (θ _{JC})	- - - - - See MIL-M-38510, appendix C
Thermal resistance, junction-to-ambient (θ _{JA})	- - - - - 120°C/W

1.4 Recommended operating conditions.

Single supply	- - - - - V- = GND, V+ = 3.0 V to 44 V
Dual supply (from V+ to V-)	- - - - - 44 V
Ambient operating temperature range (T _A)	- - - - - -55°C to +125°C

1/ Either or both voltages must not exceed the magnitude of the V+ or V-.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A	5962-89969	
		REVISION LEVEL	SHEET 2

DESC FORM 193A
SEP 87

U. S. GOVERNMENT PRINTING OFFICE: 1968-550-547

2. APPLICABLE DOCUMENTS

2.1 Government specification, standard, and bulletin. Unless otherwise specified, the following specification, standard, and bulletin of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-38510 - Microcircuits, General Specification for.

STANDARD

MILITARY

MIL-STD-883 - Test Methods and Procedures for Microelectronics.

BULLETIN

MILITARY

MIL-BUL-103 - List of Standardized Military Drawings (SMD's).

(Copies of the specification, standard, and bulletin required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 and herein.

3.2.1 Terminal connections. The terminal connections shall be as specified on figure 1.

3.2.2 Case outline. The case outline shall be in accordance with 1.2.2 herein.

3.3 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in table I and shall apply over the full ambient operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table II. The electrical tests for each subgroup are described in table I.

3.5 Marking. Marking shall be in accordance with MIL-STD-883 (see 3.1 herein). The part shall be marked with the part number listed in 1.2 herein. In addition, the manufacturer's part number may also be marked as listed in MIL-BUL-103 (see 6.6 herein).

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-89969
		REVISION LEVEL	SHEET 3

DESC FORM 193A
SEP 87

U.S. GOVERNMENT PRINTING OFFICE: 1988-550-547

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions $-55^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$ unless otherwise specified $V_+ = +15\text{ V}$, $V_- = -15\text{ V}$, and R_L connected to ground	Device type	Group A subgroups	Limits		Unit
					Min	Max	
Source current	I_{O+}	From output to GND, $T_A = +25^{\circ}\text{C}$	All	1		-10.0	mA
Sink current	I_{O-}	From output to GND $T_A = +25^{\circ}\text{C}$	All	1	20		mA
Supply current at 5 V	I_+	$V_+ = 5\text{ V}$, $V_- = 0\text{ V}$ $T_A = +25^{\circ}\text{C}$	All	1		8	mA
Input offset voltage	V_{IO}	$V_+ = 5\text{ V}$, $V_- = 0\text{ V}$ $V_0 = 1.4\text{ V}$ $T_A = +25^{\circ}\text{C}$	01	1		5.0	mV
			02	1		3.5	
Input offset voltage	V_{IO}		01	1		4.5	mV
				2, 3		6.5	
			02	1		3.0	
				2, 3		5.0	
Input offset current	I_{IO}	$V_0 = 0\text{ V}$	01	1		75	nA
				2, 3		300	
			02	1		50	
				2, 3		300	
Input bias current	I_{IB}	$V_0 = 0\text{ V}$	All	1		500	nA
				2, 3		700	
Positive supply current	I_+	$V_0 = 0$, $R_L = \text{no load}$	All	1		10	mA
				2, 3		11	
Negative supply current	I_-	$V_0 = 0$, $R_L = \text{no load}$	All	1		-10	mA
				2, 3		-11	

**STANDARDIZED
MILITARY DRAWING**

DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-89969

REVISION LEVEL

SHEET 4

DESC FORM 193A
SEP 87

U.S. GOVERNMENT PRINTING OFFICE: 1986-550-547

TABLE 1. Electrical performance characteristics - Continued.

Test	Symbol	Conditions $-55^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$ unless otherwise specified $V_+ = +15\text{ V}$, $V_- = -15\text{ V}$, and R_L connected to ground	Device type	Group A subgroups	Limits		Unit
					Min	Max	
Power supply rejection ratio	PSRR+	$\Delta V = 13.5\text{ V to }16.5\text{ V}$	01	4	70		dB
			02	4	80		
	PSRR-	$\Delta V = -13.5\text{ V to }-16.5\text{ V}$	01	4	70		
			02	4	80		
Common mode rejection ratio	CMRR+	$R_S \leq 10\text{ k}\Omega$ $V_{ICR} = 13.2\text{ V}$	01	4, 5, 6	70		dB
			02		80		
Common mode rejection ratio	CMRR-	$R_S \leq 10\text{ k}\Omega$ $V_{ICR} = -15\text{ V}$	01	4, 5, 6	70		dB
			02		80		
Large signal voltage gain	A_{VOL}	$V_O = 0\text{ V to } \pm 10\text{ V}$ $R_L = 2\text{ k}\Omega$	01	4		25	V/mV
				5, 6		20	
		$V_O = 0\text{ V to } 10\text{ V}$ $R_L = 2\text{ k}\Omega$	02	4		50	
				5, 6		25	
Output voltage swing	V_{OH1}	$R_L = 2\text{ k}\Omega$	All	4	13.5		V
				5, 6	13.5		
Output voltage swing	V_{OL1}	$R_L = 2\text{ k}\Omega$	All	4		-13.8	V
				5, 6		-13.8	
Output voltage swing	V_{OH2}	$R_L = 10\text{ k}\Omega$, $T_A = +25^{\circ}\text{C}$	All	4	13.7		V
Output voltage swing	V_{OL2}	$R_L = 10\text{ k}\Omega$, $T_A = +25^{\circ}\text{C}$	All	4		-14.4	V
Output voltage swing	V_{OL3}	$V_+ = 5\text{ V}$, $V_- = 0\text{ V}$ $R_L = 2\text{ k}\Omega$, $T_A = +25^{\circ}\text{C}$	All	1		0.2	V
Output voltage swing	V_{OH3}	$V_+ = 5\text{ V}$, $V_- = 0\text{ V}$ $R_L = 2\text{ k}\Omega$, $T_A = +25^{\circ}\text{C}$	All	1	3.7		V

**STANDARDIZED
MILITARY DRAWING**

DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-89969

REVISION LEVEL

SHEET 5

TABLE 1. Electrical performance characteristics - Continued.

Test	Symbol	Conditions $-55^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$ unless otherwise specified $V_+ = +15\text{ V}$, $V_- = -15\text{ V}$, and $R_L = \text{connected to ground}$	Device type	Group A subgroups	Limits		Unit
					Min	Max	
Slew rate	SR	Delta V = -10 V to 10 V $R_L = 2\text{ k}\Omega$, $A_V = 1$ $C_L = 500\text{ pF}$, $T_A = +25^{\circ}\text{C}$	ALL	4	8		V/ μs
Gain bandwidth product	GBW	$f = 100\text{ kHz}$, $T_A = +25^{\circ}\text{C}$	ALL	4	3.5		MHz

3.6 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-BUL-103 (see 6.6 herein). The certificate of compliance submitted to DESC-ECS prior to listing as an approved source of supply shall affirm that the manufacturer's product meets the requirements of MIL-STD-883 (see 3.1 herein) and the requirements herein.

3.7 Certificate of conformance. A certificate of conformance as required in MIL-STD-883 (see 3.1 herein) shall be provided with each lot of microcircuits delivered to this drawing.

3.8 Notification of change. Notification of change to DESC-ECS shall be required in accordance with MIL-STD-883 (see 3.1 herein).

3.9 Verification and review. DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-89969
		REVISION LEVEL	SHEET 6

DESC FORM 193A
SEP 87

U. S. GOVERNMENT PRINTING OFFICE: 1988-550-547

Device types	01 and 02
Case outline	C
Terminal number	Terminal symbol
1	Output 1
2	Input 1-
3	Input 1+
4	V+
5	Input 2+
6	Input 2-
7	Output 2
8	Output 3
9	Input 3-
10	Input 3+
11	V-/GND
12	Input 4+
13	Input 4-
14	Output 4

FIGURE 1. Terminal connections.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-89969
		REVISION LEVEL	SHEET 7

DESC FORM 193A
SEP 87

U. S. GOVERNMENT PRINTING OFFICE: 1988-550-547

TABLE II. Electrical test requirements.

MIL-STD-883 test requirements	Subgroups (per method 5005, table I)
Interim electrical parameters (method 5004)	1
Final electrical test parameters (method 5004)	1*,2,3,4,5,6
Group A test requirements (method 5005)	1,2,3,4,5,6
Groups C and D end-point electrical parameters (method 5005)	1, 2, 3,

*PDA applies to subgroup 1.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein).

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

- a. Burn-in test, method 1015 of MIL-STD-883.
 - (1) Test condition A using the circuit submitted with the certificate of compliance (see 3.6 herein).
 - (2) $T_A = +125^{\circ}\text{C}$, minimum.
- b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

4.3.1 Group A inspection.

- a. Tests shall be as specified in table II herein.
- b. Subgroups 7, 8, 9, 10, and 11 in table I, method 5005 of MIL-STD-883 shall be omitted.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-89969
		REVISION LEVEL	SHEET 8

DESC FORM 193A
SEP 87

☆ U. S. GOVERNMENT PRINTING OFFICE: 1968-550-547

4.3.2 Groups C and D inspections.

a. End-point electrical parameters shall be as specified in table II herein.

b. Steady-state life test conditions, method 1005 of MIL-STD-883.

(1) Test condition A using the circuit submitted with the certificate of compliance (see 3.6 herein).

(2) $T_A = +125^{\circ}\text{C}$, minimum.

(3) Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use when military specifications do not exist and qualified military devices that will perform the required function are not available for OEM application. When a military specification exists and the product covered by this drawing has been qualified for listing on QPL-38510, the device specified herein will be inactivated and will not be used for new design. The QPL-38510 product shall be the preferred item for all applications.

6.2 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.3 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished in accordance with MIL-STD-481 using DD Form 1693, Engineering Change Proposal (Short Form).

6.4 Record of users. Military and industrial users shall inform Defense Electronics Supply Center when a system application requires configuration control and the applicable SMD. DESC will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronics devices (FSC 5962) should contact DESC-ECS, telephone (513) 296-6022.

6.5 Comments. Comments on this drawing should be directed to DESC-ECS, Dayton, Ohio 45444, or telephone (513) 296-5375.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-89969
		REVISION LEVEL	SHEET 9

DESC FORM 193A
SEP 87

U S GOVERNMENT PRINTING OFFICE 1988-550-547

6.6 Approved source of supply. An approved source of supply is listed in MIL-BUL-103. Additional sources will be added to MIL-BUL-103 as they become available. The vendor listed in MIL-BUL-103 has agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DESC-ECS. The approved source of supply listed below is for information purposes only and is current only to the date of the last action of this document.

Military drawing part number	Vendor CAGE number	Vendor similar part number 1/
5962-8996901CX	04713	35074/BCAJC
5962-8996902CX	04713	35074A/BCAJC

1/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE
number

04713

Vendor name
and address

Motorola Incorporated
5005 E. McDowell
Phoenix, AZ 85008
Point of contact: 2100 E. Elliot Road
Tempe, AZ 85284

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-89969
		REVISION LEVEL	SHEET 10

DESC FORM 193A
SEP 87

* U S GOVERNMENT PRINTING OFFICE: 1988-550-547

019122