

12 Watt Dual Output DC/DC Converters

3355 Vincent Road, Pleasant Hill, CA 94523-4389 800-542-3355 Telephone (415)932-3911 FAX: (415)932-6017

CALEX


FEATURES

- Low Noise Output
- LC Type Input Filter
- Six-Sided Shielded Steel Case
- Very Wide Input Voltage Ranges (9-27, 12-36, 18-54, and 24-72)
- High Efficiency Operation
- Long Term Output Fault Survival
- 5 Year Warranty

T-57-11

SELECTION CHART


MODEL	INPUT RANGE VDC		OUTPUTS VDC	OUTPUTS mA	CASE
	MIN	MAX			
12D12.500	9.00	27.00	±12.0	±500	B1
12D15.400	9.00	27.00	±15.0	±400	B1
24D12.500	12.00	36.00	±12.0	±500	B1
24D15.400	12.00	36.00	±15.0	±400	B1
28D5.1000	18.00	54.00	±5.0	±1000	B1
48D12.500	24.00	72.00	±12.0	±500	B1
48D15.400	24.00	72.00	±15.0	±400	B1

DESCRIPTION

These 10 and 12 Watt Dual Output DC/DC converters are designed for telecommunications, medical or industrial equipment and instrumentation systems. The converters feature very wide input voltage ranges.

The converter consists of a hi-speed chopper circuit using state of the art MOSFET technology, isolation transformer, and high regulation linear post regulator. This provides for very low noise and ultra stable output voltages.

12 WATT DUAL SERIES BLOCK DIAGRAM





T-57-11

1-57-11

INPUT PARAMETERS (1)						
MODEL		12D12.500	12D15.400	24D12.500	24D15.400	UNITS
Voltage Range	MIN	9.00		12.00		VDC
	MAX	27.00		36.00		
Reflected Ripple, 0-20MHz BW	TYP	30		20		mA p-p
	MAX	75		45		
Input Current Full Load No Load	TYP	1480	1440	710	700	mA
	TYP	68	68	40	40	
Efficiency	TYP	70				%
Switching Frequency	TYP	85		100		kHz
Maximum Input Over Voltage, 100mS No Damage	MAX	33		40		VDC
Turn-on Time, 1% Output Error	TYP	60				mSec
Recommended Fuse		(2)				
MODEL		28D5.1000	48D12.500	48D15.400		UNITS
Voltage Range	MIN	18.00	24.00			VDC
	MAX	54.00	72.00			
Reflected Ripple, 0-20MHz BW	TYP	20	15			mA p-p
	MAX	50	30			
Input Current Full Load No Load	TYP	600	360	350		mA
	TYP	40	24	24		
Efficiency	TYP	60	70			%
Switching Frequency	TYP	87	100			kHz
Maximum Input Over Voltage, 100mS No Damage	MAX	60	80			VDC
Turn-on Time, 1% Output Error	TYP	60				mSec
Recommended Fuse		(2)				

OUTPUT PARAMETERS (1)						
MODEL		28D5.1000	12D12.500 48D12.500	24D12.500 48D15.400	24D15.400 48D15.400	UNITS
Output Voltage		±5	±12	±15		VDC
Rated Current (3)	MIN MAX	0 +1100/-900	0 ±500	0 ±400		mA
Voltage Range 100% Load	MIN TYP MAX	4.95 5.00 5.05	11.90 12.00 12.10	14.90 15.00 15.10		VDC
Output Balance (Plus to Minus Output, Full Load)	TYP MAX	0.6 1.0				%
Load Regulation 0-100% Load	TYP MAX	0.05 0.10	0.02 0.07	0.02 0.07		%
Line Regulation Vin = Min-Max VDC	TYP MAX	0.02 0.07				%
Short Term Stability (4)	TYP	0.02				%
Long Term Stability	TYP	0.3				%/kHrs
Transient Response (5)	TYP	20				µSec
Dynamic Response (6)	TYP	20				mV peak
Input Ripple Rejection (7)	TYP	60				dB
Noise, 0-20MHz BW	TYP MAX	10 40				mV p-p
Temperature Coefficient	TYP MAX	100 300	50 150	50 150		ppm/°C
Short Circuit Protection to Common for all Outputs		Continuous, 8 Hours Minimum Current Limit				

NOTES


- (1) All parameters measured at 25°C, nominal input voltage and full rated load unless otherwise noted. Refer to the Calnex Application Notes for the definition of terms, measurement circuits and other information.
- (2) Determine the correct fuse size by calculating the maximum DC current drain at low line input, maximum load then adding 20 to 25 percent.
- (3) No minimum load required.
- (4) Short term stability is specified after a 30 minute warm-up at full load.
- (5) Transient response is defined as the time for the output to settle from a 100% step load change to a 1% error band (rise time of step = 2 μSec).
- (6) Dynamic response is defined as the peak overshoot during a transient as defined in note 6 above.
- (7) The input ripple rejection is specified for DC to 120Hz ripple with a modulation amplitude of 1% of Vin.

12 Watt Dual Output DC/DC Converters

3355 Vincent Road, Pleasant Hill, CA 94523-4389 800-542-3355 Telephone (415)932-3911 FAX: (415)932-6017



GENERAL SPECIFICATIONS (1)			
MODEL		ALL MODELS	UNITS
ISOLATION			
Isolation Voltage	MIN	500	VDC
Input-Output 10µA Leakage			
Input to Output Capacitance	TYP	120	pF
ENVIRONMENTAL			
Case Operating Range, No Derating	MIN MAX	-25 80	°C
Case Functional Range (8)	MIN MAX	-40 85	°C
Storage Range	MIN MAX	-55 100	°C
Thermal Impedance (9)	TYP	6	°C/Watt
Unit Weight	TYP	6.5	oz
Case		B1	
Mounting Kits		MK215-022 & MK215-08B	



Mechanical tolerances unless otherwise noted:

X.XX dimensions: ± 0.020 inches







X.XXX dimensions: ± 0.005 inches

Seal around terminals is not hermetic. Do not immerse units in any liquid.

- (8) The functional temperature range is intended to give an additional data point for use in evaluating this power supply. At the low functional temperature the power supply will function with no side effects, however sustained operation at the high functional temperature will reduce expected operational life. The data sheet specifications are not guaranteed over the functional temperature range.

- (9) The case thermal impedance is specified as the case temperature rise over ambient per package watt dissipated.

PIN	FUNCTION
1	+INPUT
2	-INPUT
3	+OUTPUT
4	CMN
5	-OUTPUT



12 Watt Dual Output DC/DC Converters



3355 Vincent Road, Pleasant Hill, CA 94523-4389 800-542-3355 Telephone (415)932-3911 FAX: (415)932-6017

Typical Performance ($T_c=25^\circ\text{C}$; Full Rated Load).

T-57-11

