


1. SCOPE

1.1 Scope. This drawing describes device requirements for class B microcircuits in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices".

1.2 Part number. The complete part number shall be as shown in the following example:



1.2.1 Device types. The device types shall identify the circuit function as follows:

Device type	Generic number	Circuit function
01	OP14A	Dual matched high performance operational amplifiers
02	OP14B	Dual matched high performance operational amplifiers

1.2.2 Case outlines. The case outlines shall be as designated in appendix C of MIL-M-38510, and as follows:

Outline letter	Case outline
G	A-1 (8-lead can) <i>TO-5/TO-99, 3</i>
P	D-4 (8-lead 1/4" x 3/8"), dual-in-line package <i>pic 8</i>

1.3 Absolute maximum ratings.

Supply voltage	-----	±22 V
Power dissipation (P _D)	-----	500 mW
Differential input voltage	-----	±30 V
Input voltage	-----	Supply voltage
Output short-circuit duration	-----	Indefinite
Storage temperature range	-----	-65°C to +150°C
Lead temperature range (soldering, 60 seconds)	-----	+300°C
Junction temperature (T _J)	-----	-65°C to +150°C

1.4 Recommended operating conditions.

Supply voltage (V _{CC})	-----	±15 V
Ambient operating temperature range	-----	-55°C to +125°C

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 67268	DWG NO. 5962-87714
		REV	PAGE 2

DESC FORM 193A
FEB 86

2. APPLICABLE DOCUMENTS

2.1 Government specification and standard. Unless otherwise specified, the following specification and standard, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-38510 - Microcircuits, General Specification for.

STANDARD

MILITARY

MIL-STD-883 - Test Methods and Procedures for Microelectronics.

(Copies of the specification and standard required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 and herein.

3.2.1 Terminal connections and logic diagrams. The terminal connections and logic diagrams shall be as specified on figure 1.

3.2.2 Case outlines. The case outlines shall be in accordance with 1.2.2 herein.

3.3 Electrical performance characteristics. Unless otherwise specified, the electrical performance characteristics are as specified in table I and apply over the full recommended ambient operating temperature range.

3.4 Marking. Marking shall be in accordance with MIL-STD-883 (see 3.1 herein). The part shall be marked with the part number listed in 1.2 herein. In addition, the manufacturer's part number may also be marked as listed in 6.4 herein.

3.5 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in 6.4. The certificate of compliance submitted to DESC-ECS prior to listing as an approved source of supply shall state that the manufacturer's product meets the requirements of MIL-STD-883 (see 3.1 herein) and the requirements herein.

3.6 Certificate of conformance. A certificate of conformance as required in MIL-STD-883 (see 3.1 herein) shall be provided with each lot of microcircuits delivered to this drawing.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE	CODE IDENT. NO.	DWG NO.
	A	67268	5962-87714
		REV	PAGE 3

DESC FORM 193A
FEB 86

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions -55°C < T _A < +125°C unless otherwise specified V _S = ±15 V	Device type	Group A subgroups	Limits		Unit
					Min	Max	
Input offset voltage	V _{OS}	R _S ≤ 20 kΩ	01	1	-0.75	0.75	mV
				2,3	-1.5	1.5	
Input offset current	I _{OS}			1	-5	5	nA
				2,3	-10	10	
Input bias current	I _B			1	-50	50	nA
				2,3	-60	60	
Input voltage range	IVR	1/		1	±10		V
				2,3	±10		
Common mode rejection ratio	CMRR	V _{CM} = IVR = ±10 V R _S ≤ 20 kΩ		1	85		dB
				2,3	80		
Power supply rejection ratio	PSRR	R _S ≤ 20 kΩ V _S = 15 V to ±20 V		1		60	μV/V
				2,3		60	
Output voltage swing	V _O	R _L ≥ 2 kΩ		4	±12		V
				5,6	±12		
Large signal voltage gain	A _{V0}	R _L ≥ 2 kΩ V _O = ±10 V		4	100		V/mV
				5,6	50		
Power supply current	I _{SY}	No load each amplifier T _A = +25°C		1		3	mA
Power dissipation	P _D	No load each amplifier T _A = +25°C		1		90	mW
Channel separation	CS			7	100		dB
Output short circuit current	I _{SC-}			1	-60		mA
	I _{SC+}			2,3		60	

See footnotes at end of table.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE	CODE IDENT. NO.	DWG NO.
	A	67268	5962-87714
	REV	PAGE	4

DESC FORM 193A
FEB 86

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions -55°C < T _A < +125°C unless otherwise specified V _S = ±15 V	Device type	Group A subgroups	Limits		Unit
					Min	Max	
Input resistance differential mode	R _{IN}	<u>2/</u>	01	1	2.0		MΩ
Rise time	t _r	A _{VCL} = +1, V _{IN} = 50 mV R _L ≥ 2 kΩ, R _S = 50Ω, C _L = 50 pF		9		350	ns
Overshoot	OS	A _{VCL} = +1, V _{IN} = 50 mV R _L ≥ 2 kΩ, R _S = 50Ω, C _L = 50 pF		9		10	%
Slew rate	SR	R _L ≥ 2 kΩ, R _S = 50 kΩ C _L = 100 pF		7	0.25		V/μs
Bandwidth	BW	A _{VCL} = +1 <u>3/</u>		7	1		MHz
Large signal bandwidth	LSBW	V _O = 20 V _p - p <u>4/</u>		7	4		kHz
Input offset voltage match	Delta V _{OS}			1	-1	1	mV
				2,3	-1.5	1.5	
Common mode rejection ratio match	Delta CMRR	V _{CM} = ±10 V, R _S ≤ 100Ω		1	94		dB
				2,3	90		

See footnotes at end of table.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE	CODE IDENT. NO.	DWG NO.
	A	67268	5962-87714
	REV	PAGE	5

DESC FORM 193A
FEB 86

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions -55°C < T _A < +125°C unless otherwise specified V _S = ±15 V	Device type	Group A subgroups	Limits		Unit
					Min	Max	
Input offset voltage	V _{OS}	R _S ≤ 20 kΩ	02	1	-5	5	mV
				2,3	-6	6	
Input offset current	I _{OS}			1	-25	25	nA
				2,3	-50	50	
Input bias current	I _B			1	-100	100	nA
				2,3	-200	200	
Input voltage range	IVR	1/		1	±10		V
				2,3	±10		
Common mode rejection ratio	CMRR	V _{CM} = IVR = ±10 V R _S ≤ 20 kΩ		1	70		dB
				2,3	70		
Power supply rejection ratio	PSRR	R _S ≤ 20 kΩ V _S = 15 V to ±20 V		1		150	uV/V
				2,3		150	
Output voltage swing	V _O	R _L ≥ 2 kΩ		4	±12		V
				5,6	±10		
Large signal voltage gain	A _{VO}	R _L ≥ 2 kΩ V _O = ±10 V		4	50		V/mV
				5,6	25		
Power supply current	I _{SY}	No load each amplifier T _A = +25°C		1		3	mA
Power dissipation	P _D	No load each amplifier T _A = +25°C		1		90	mW
Channel separation	CS			7	80		dB
Output short circuit current	I _{SC-}			1	-60		mA
	I _{SC+}			2,3		60	

See footnotes at end of table.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE	CODE IDENT. NO.	DWG NO.
	A	67268	5962-87714
		REV	PAGE 6

DESC FORM 193A
FEB 86

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions -55°C < T _A < +125°C unless otherwise specified V _S = ±15 V	Device type	Group A subgroups	Limits		Unit
					Min	Max	
Input resistance differential mode	R _{IN}	2/	02	1	1.0		MΩ
Rise time	t _r	A _{VCL} = +1, V _{IN} = 50 mV R _L ≥ 2 kΩ, R _S = 50Ω, C _L = 50 pF		9		350	ns
Overshoot	OS	A _{VCL} = +1, V _{IN} = 50 mV R _L ≥ 2 kΩ, R _S = 50Ω, C _L = 50 pF		9		10	%
Slew rate	SR	R _L ≥ 2 kΩ, R _S = 50 kΩ C _L = 100 pF		7	0.25		V/μs
Bandwidth	BW	A _{VCL} = +1 3/		7	1		MHz
Large signal bandwidth	LSBW	V _O = 20 V _p - p 4/		7	4		kHz
Input offset voltage match	Delta V _{OS}			1	-1	1	mV
				2,3	-1.5	1.5	
Common mode rejection ratio match	Delta CMRR	V _{CM} = ±10 V, R _S ≤ 100Ω		1	94		dB
				2,3	90		

1/ IVR is guaranteed by CMRR test.

2/ R_{IN} is guaranteed by I_B test. R_{IN} = 4KT/qI_B where KT/q = .026 V at +25°C.

3/ Bandwidth is guaranteed by t_r test. BW = .35/t_r.


4/ Large signal bandwidth is guaranteed by SR test. LSBW = SR/2/(V_{peak}).

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE	CODE IDENT. NO.	DWG NO.
	A	67268	5962-87714
	REV	PAGE	7

DESC FORM 193A
FEB 86

Device types 01 and 02

Case P



Case G




FIGURE 1. Terminal connections and logic diagrams.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 67268	DWG NO. 5962-87714
		REV	PAGE 8

DESC FORM 193A
FEB 86

3.7 Notification of change. Notification of change to DESC-ECS shall be required in accordance with MIL-STD-883 (see 3.1 herein).

3.8 Verification and review. DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein).

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

a. Burn-in test (method 1015 of MIL-STD-883).

(1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.5 herein).

(2) $T_A = +125^\circ\text{C}$, minimum.

b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

4.3.1 Group A inspection.

a. Tests shall be as specified in table II herein.

b. Subgroups 8, 10, and 11 in table I, method 5005 of MIL-STD-883 shall be omitted.

4.3.2 Groups C and D inspections.

a. End-point electrical parameters shall be as specified in table II herein.

b. Steady-state life test (method 1005 of MIL-STD-883) conditions:

(1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.5 herein).

(2) $T_A = +125^\circ\text{C}$, minimum.

(3) Test duration: 1,000 hours, except as permitted by appendix B of MIL-M-38510 and method 1005 of MIL-STD-883.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE	CODE IDENT. NO.	DWG NO.
	A	67268	5962-87714
		REV	PAGE 9

DESC FORM 193A
FEB 86

TABLE II. Electrical test requirements.

MIL-STD-883 test requirements	Subgroups (per method 5005, table I)
Interim electrical parameters (method 5004)	1
Final electrical test parameters (method 5004)	1*,2,3,4,5,6
Group A test requirements (method 5005)	1,2,3,4,5,6, 7,9
Groups C and D end-point electrical parameters (method 5005)	1

*PDA applies to subgroup 1.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use when military specifications do not exist and qualified military devices that will perform the required function are not available for OEM application. When a military specification exists and the product covered by this drawing has been qualified for listing on QPL-38510, the device specified herein will be inactivated and will not be used for new design. The QPL-38510 product shall be the preferred item for all applications.

6.2 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.3 Comments. Comments on this drawing should be directed to DESC-ECS, Dayton, Ohio 45444, or telephone 513-296-5375.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE	CODE IDENT. NO.	DWG NO.
	A	67268	5962-87714
	REV	PAGE	10

DESC FORM 193A
FEB 86

6.4 Approved source of supply. An approved source of supply is listed herein. Additional sources will be added as they become available. The vendor listed herein has agreed to this drawing and a certificate of compliance (see 3.5 herein) has been submitted to DESC-ECS.

Military drawing part number	Vendor CAGE number	Vendor similar part number <u>1/</u>
5962-8771401GX 5962-8771401PX	06665 06665	OP14AZ/883 OP14AJ/883
5962-8771402GX 5962-8771402PX	06665 06665	OP14BZ/883 OP14BJ/883

1/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE number

06665

Vendor name and address

Precision Monolithics, Incorporated
1500 Space Park Drive
P.O. Box 58020
Santa Clara, CA 95050

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE	CODE IDENT. NO.	DWG NO.
	A	67268	5962-87714
	REV	PAGE	11

DESC FORM 193A
FEB 86