



APT PART NUMBER	DRAIN- SOURCE VOLTAGE BVDSS (VOLTS)	ON RESIS- TANCE RDS(ON) (OHMS)	DRAIN CURRENT		INPUT CAPAC- ITANCE CISS (pF)	POWER DISSI- PATION PD(MAX) (WATTS)	NOTES	CASE STYLE AND DEVICE TYPE
			ID (CONT) (AMPS)	IDM (PULSED) (AMPS)				
APT1001RBN	1000	1.00	11.0	44.0	2450	310	3	TO-3P (TO-247 AD PROPOSED)
APT1001R2BN	1000	1.20	10.0	40.0	2450	310	3	
APT1002RBN	1000	2.00	7.0	28.0	1750	240	3	 COMMERCIAL PLASTIC N-CHANNEL MOSFET 
APT1002R4BN	1000	2.40	6.5	26.0	1750	240	3	
APT1003R5BN	1000	3.50	4.5	18.0	880	180	3	
APT1004R2BN	1000	4.20	4.0	16.0	880	180	3	
APT901RBN	900	1.00	11.0	44.0	2450	310	3	
APT901R2BN	900	1.20	10.0	40.0	2450	310	3	
APT902RBN	900	2.00	7.0	28.0	1750	240	3	
APT902R4BN	900	2.40	6.5	26.0	1750	240	3	
APT903R5BN	900	3.50	4.5	18.0	880	180	3	
APT904R2BN	900	4.20	4.0	16.0	880	180	3	
APT8075BN	800	0.75	13.0	52.0	2450	310	3	
APT8090BN	800	0.90	12.0	48.0	2450	310	3	
APT801R2BN	800	1.20	9.0	36.0	1750	240	3	
APT801R4BN	800	1.40	8.5	34.0	1750	240	3	
APT802RBN	800	2.00	6.0	24.0	880	180	3	
APT802R4BN	800	2.40	5.5	22.0	880	180	3	
APT7575BN	750	0.75	13.0	52.0	2450	310	3	
APT7590BN	750	0.90	12.0	48.0	2450	310	3	
APT751R2BN	750	1.20	9.0	36.0	1750	240	3	
APT751R4BN	750	1.40	8.5	34.0	1750	240	3	
APT752RBN	750	2.00	6.0	24.0	880	180	3	
APT752R4BN	750	2.40	5.5	22.0	880	180	3	
APT6040BN	600	0.40	18.0	72.0	2400	310	1	
APT6045BN	600	0.45	17.0	68.0	2400	310	1	
APT6060BN	600	0.60	13.0	52.0	1700	240	1	
APT6070BN	600	0.70	12.0	48.0	1700	240	1	
APT601R2BN	600	1.20	8.0	32.0	850	180	1	
APT601R6BN	600	1.60	6.5	26.0	850	180	1	
APT5540BN	550	0.40	18.0	72.0	2400	310	1	
APT5545BN	550	0.45	17.0	68.0	2400	310	1	
APT5560BN	550	0.60	13.0	52.0	1700	240	1	
APT5570BN	550	0.70	12.0	48.0	1700	240	1	
APT551R2BN	550	1.20	8.0	32.0	850	180	1	
APT551R6BN	550	1.60	6.5	26.0	850	180	1	
APT5025BN	500	0.25	23.0	92.0	2400	310	1	
APT5030BN	500	0.30	21.0	84.0	2400	310	1	
APT5040BN	500	0.40	16.0	64.0	1700	240	1	
APT5050BN	500	0.50	14.0	56.0	1700	240	1	
APT5085BN	500	0.85	9.5	38.0	850	180	1	
APT501R1BN	500	1.10	8.0	32.0	850	180	1	
APT4525BN	450	0.25	23.0	92.0	2400	310	1	
APT4530BN	450	0.30	21.0	84.0	2400	310	1	
APT4540BN	450	0.40	16.0	64.0	1700	240	1	
APT4550BN	450	0.50	14.0	56.0	1700	240	1	
APT4585BN	450	0.85	9.5	38.0	850	180	1	
APT451R1BN	450	1.10	8.0	32.0	850	180	1	
APT4020BN	400	0.20	26.0	104.0	2400	310	1	
APT4025BN	400	0.25	23.0	92.0	2400	310	1	
APT4030BN	400	0.30	18.5	74.0	1700	240	1	
APT4040BN	400	0.40	16.0	64.0	1700	240	1	
APT4055BN	400	0.55	12.0	48.0	850	180	1	
APT4080BN	400	0.80	10.0	40.0	850	180	1	
APT3520BN	350	0.20	26.0	104.0	2400	310	1	
APT3525BN	350	0.25	23.0	92.0	2400	310	1	
APT3530BN	350	0.30	18.5	74.0	1700	240	1	
APT3540BN	350	0.40	16.0	64.0	1700	240	1	
APT3555BN	350	0.55	12.0	48.0	850	180	1	
APT3580BN	350	0.80	10.0	40.0	850	180	1	

NOTE 1. - CURRENTLY AVAILABLE
 NOTE 3. - AVAILABLE DECEMBER 1988