

FM IF System


Unit	R in Ω	C in F
------	-----------------	----------

■ ABSOLUTE MAXIMUM RATINGS

Item	Symbol	Rating	Unit
Supply Voltage	V_{CC}	16	V
Power Dissipation	P_T	624*	W
Operating Temperature	T_{opr}	-20 to +70	°C
Storage Temperature	T_{stg}	-55 to +125	°C

* at $T_a=60^\circ\text{C}$

DELATING CURVE



■ ELECTRICAL CHARACTERISTICS


● DC CHARACTERISTICS ($T_a=25^\circ\text{C}$, $V_{CC}=8\text{V}$, $V_{in}=0\text{dB}\mu$)

Item	Symbol	min.	typ.	max.	Unit
DC Voltage at Pin 1	V1	—	1.95	—	V
DC Voltage at Pin 2	V2	—	1.95	—	V
DC Voltage at Pin 3	V3	—	1.95	—	V
DC Voltage at Pin 6	V6	—	5.60	—	V
DC Voltage at Pin 7	V7	—	5.60	—	V
DC Voltage at Pin 10	V10	—	5.60	—	V

● AC CHARACTERISTICS ($T_a=25^\circ\text{C}$, $V_{CC}=8\text{V}$, $f_c=10.7\text{MHz}$, $f_m=1\text{kHz}$, $\Delta f=75\text{kHz}$ dev.)


Item	Symbol	Test Conditions	min.	typ.	max.	Unit
Operating Current	I_{CC}	$V_{in}=100\text{dB}\mu$, Mute ON	—	32	39	mA
Limiting Sensitivity	$V_{in}(\text{lim})$	at -3dB	—	31	37	dB μ
Recovered Output	$V_o(\text{AF})$	$V_{in}=100\text{dB}\mu$	230	300	390	mVrms
Total Harmonic Distortion	$T.H.D$	$V_{in}=100\text{dB}\mu$	—	0.06	0.3	%
Signal-to-Noise Ratio	S/N	$V_{in}=100\text{dB}\mu$	67	75	—	dB
AM Rejection	AMR	$V_{in}=100\text{dB}\mu$, $f_m(\text{AM})=1\text{kHz}$, 30% mod.	45	55	—	dB
Muting Attenuation	Mute(ATT)	$V_{in}=100\text{dB}\mu$, $V_s=2\text{V}$	68	75	—	dB
Muting Band Width	$BW(\text{Mute})$	Detuned frequency under 1.4V of Pin=12 voltage, $V_{in}=100\text{dB}\mu$	—	100	—	kHz
Muting Sensitivity	$V_{in}(\text{Mute})$	V_{in} under 1.4V of Pin-12 voltage	—	35	—	dB μ
Analogue Control Voltage	V_{13-0}	Pin-13 voltage under $V_{in}=0\text{dB}\mu$	—	0.2	—	V
	V_{13-60}	Pin-13 voltage under $V_{in}=60\text{dB}\mu$	—	1.65	—	V
	V_{13-100}	Pin-13 voltage under $V_{in}=100\text{dB}\mu$	—	4.7	—	V
AGC Control Voltage	V_{15}	Pin-15 voltage under $V_{in}=86\text{dB}\mu$	—	3.7	—	V

TEST CIRCUIT




PRINTED CIRCUIT BOARD LAYOUT PATTERN

HA12411




(bottom view)







HA12418




(bottom view)




(top view)

V_{12} , V_{13} , V_{15} , VS. V_{in} T.H.D, NOISE, V_{out} , I_{CC} , AMR VS. V_{in}  V_{12} VS. DETUNED FREQUENCYMute(ATT), T.H.D VS. V_s VOLTAGES/N, V_o (AF), AMR, T.H.D, V_{in} (lim), V_{in} (Mute) VS. V_{CC}  $(V_7 - V_{10})$, V_{12-100} , V_{12-0} , V_{15-80} , V_{13-70} , V_{13-54} , V_{13-0} VS. V_{CC} 

Mute(ATT), S/N, V_o(AF), AMR VS. AMBIENT TEMPERATURE



V_{in}(Mute), V_{in}(lim) VS. AMBIENT TEMPERATURE



T.H.D, BW(Mute) VS. AMBIENT TEMPERATURE

