


高压二极管  
反向电压 4000V  
正向电流 0.2 A

High Voltage Rectifier  
Reverse Voltage 4000V  
Forward Current 0.2 A



### 特征 Features

- 反向漏电流低 Low reverse leakage
- 正向浪涌承受能力较强 High forward surge capability
- 高温焊接保证 High temperature soldering guaranteed:  
260°C/10 秒, 0.375" (9.5mm)引线长度。  
260°C/10 seconds, 0.375" (9.5mm) lead length,
- 引线可承受5 磅 (2.3kg) 拉力。 5 lbs. (2.3kg) tension
- 引线 and 管体皆符合RoHS标准。  
Lead and body according with RoHS standard

### 机械数据 Mechanical Data

- 端子: 镀锡轴向引线 Terminals: Plated axial leads
- 极性: 色环端为负极 Polarity: Color band denotes cathode end
- 安装位置: 任意 Mounting Position: Any

极限值和温度特性 TA = 25°C 除非另有规定。

Maximum Ratings & Thermal Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

	符号 Symbols	R4000	单位 Unit
最大可重复峰值反向电压 Maximum repetitive peak reverse voltage	$V_{RRM}$	4000	V
最大均方根电压 Maximum RMS voltage	$V_{RMS}$	2800	V
最大直流阻断电压 Maximum DC blocking voltage	$V_{DC}$	4000	V
最大正向平均整流电流 Maximum average forward rectified current	$I_{F(AV)}$	0.2	A
峰值正向浪涌电流 8.3ms 单一正弦半波 Peak forward surge current 8.3 ms single half sine-wave	$I_{FSM}$	30	A
典型热阻 Typical thermal resistance	$R_{\theta j-a}$	45	°C/W
工作结温和存储温度 Operating junction and storage temperature range	$T_j, T_{STG}$	-55--- +150	°C


电特性 TA = 25°C 除非另有规定。

Electrical Characteristics Ratings at 25°C ambient temperature unless otherwise specified.


	符号 Symbols	R4000	单位 Unit
最大正向电压 $I_F = 0.2A$ Maximum forward voltage	$V_F$	5.0	V
最大反向电流 TA= 25°C Maximum reverse current TA= 100°C	$I_R$	5.0 50	μA
典型结电容 $V_R = 4.0V, f = 1MHz$ Type junction capacitance	$C_j$	30	pF

特性曲线 Characteristic Curves

正向特性曲线 (典型值)  
TYPICAL FORWARD CHARACTERISTIC



正向电流降额曲线  
FORWARD CURRENT DERATING CURVE



浪涌特性曲线 (最大值)  
MAXIMUM NON REPETITIVE  
PEAK FORWARD SURGE CURRENT

