Cirrus

- Splash oil lubrication For better wear resistance.
- Cast valve plates For durability.
- Rust proof stainless steel valves For extended life.
- **Special compression ring** For longer life.
- Trapped reed valves Eliminating severe pump damage.
- Strip stainless steel valves For higher output and durability.
- Dynamically balanced crankshaft For improved smoothness.
- Die piece con-rod and piston Lightweight and high efficiency.
- High performance fan With specially designed fan blades for maximum forced air cooling.
- Professional aftercooler For better efficiency.
- Integral air filter To avoid accidental damage.
- Larger oil sump For better lubrication.
- Needs little maintenance For added convenience.
- **Low oil consumption** Highly efficient
- Thermal protection against overheating With automatic reset.
- Tough cover For safety and protection.
- High efficiency pump For more air.
- Powerful 3.0HP motor Superb power from domestic supply.
- Large 12.0cfm displacement.
- Easy to use Ideal for home DIY use.
- Over 100 service agents nationwide For easy servicing.
- **100% production line tested** For greater reliability.
- Equipped with automatic stop/start control, pressure regulator, gauges and drain valve - Added value.
- Done year warranty For peace of mind.





	us J	9402	3
WHEEL	24 Litre AIR RECEIVER	13 AMP SUPPLY	Thermal UNIC OVERIOAD

Wheel mounted 24 litre receiver - With safety valve for worry free operation.

Item N° 01639	Airmate
Cirrus 34050	
WHEEL SO Lifre AR RECEIVER IS AMP SUPPLY	

 Wheel mounted 50 litre receiver - With safety valve, gives even greater air storage when required.

Item N° 01622	Airmate
Cirrus 340100	

Wheel mounted massive 100 litre receiver - With safety valve, gives even greater air storage when required.

MODEL	CIRRUS 34025	CIRRUS 34050	CIRRUS 340100
	01/00	01/00	01/00
ITEM NO	01638	01639	01622
PISTON DISP. L/MIN	340	340	340
PISTON DISP. CFM	12	12	12
F.A.D. L/MIN	213	213	213
F.A.D. CFM	7.5	7.5	7.5
HP	3	3	3
PHASE	1 - 13A	1 -13A	1 - 13A
R.P.M	2800	2800	2800
NO. CYLINDERS	1	1	1
NO. STAGES	1	1	1
MAX. PRESSURE BAR	8	8	8
MAX. PRESSURE PSI	118	118	118
RECEIVER CAPACITY LITRES	24	50	100
PACKED DIMENSIONS (HxWxL) MM	590x275x600	720x380x830	800x390x1070
WEIGHT KGS	27	39	55



Cirrus

- V-twin pump design For smoother performance and longer lasting pump.
- **Splash oil lubrication** For better wear resistance.
- Cast valve plates For durability.
- **Rust proof stainless steel valves** For extended life.
- **Special compression ring** For longer life.
- Trapped reed valves Eliminating severe pump damage.
- Strip stainless steel valves For higher output and durability.
- Dynamically balanced crankshaft For improved smoothness.
- One piece con-rod and piston Lightweight and high efficiency.
- High performance fan With specially designed fan blades for maximum forced air cooling.
- Integral air filter To avoid accidental damage.
- Larger oil sump For better lubrication.
- Needs little maintenance For added convenience.
- **Low oil consumption** Highly efficient.
- Thermal protection against overheating With automatic reset.
- Tough cover For safety and protection.
- High efficiency pump For more air.
- Powerful 3.0HP motor Superb power from domestic supply.
- Large 14.0 cfm displacement.
- Easy to use Ideal for home DIY use.
- Over 100 service agents nationwide For easy servicing.
- **100% production line tested** For greater reliability.
- Equipped with automatic stop/start control, pressure regulator, gauges and drain valve Added value.
- Done year warranty For peace of mind.









Wheel mounted 50 litre receiver - With safety valve, gives greater air storage.

Item N° 01607	Airmate
Cirrus 360100	

Wheel mounted 100 litre receiver - With safety valve, gives even greater air storage, when required.



 Wheel mounted 150 litre receiver - With safety valve, gives greatest air storage.

MODEL	CIRRUS 36050	CIRRUS 360100	CIRRUS 360150
ITEM NO	01606	01607	01608
PISTON DISP. L/MIN	400	400	400
PISTON DISP. CFM	14	14	14
F.A.D. L/MIN	255	255	255
F.A.D. CFM	9	9	9
HP	3	3	3
PHASE	1 - 13A	1 - 13A	1 - 13A
R.P.M	2800	2800	2800
NO. CYLINDERS	V 2	V 2	V 2
NO. STAGES	1	1	1
MAX. PRESSURE BAR	8	8	8
MAX. PRESSURE PSI	118	118	118
RECEIVER CAPACITY LITRES	50	100	150
PACKED DIMENSIONS (HxWxL) MM	760x380x875	800x380x1075	1070x430x1370
WEIGHT KGS	43	55	75

