

Memory Module Specification

KVR333X72RC25/512 512MB 64M x 72-Bit DDR333

CL2.5 Registered 184-Pin ECC DIMM

DESCRIPTION:

This document describes ValueRAM's 64M x 72-bit (512MB) DDR333 CL2.5 SDRAM (Synchronous DRAM) Registered ECC memory module. The components on this module include eighteen 64M x 4-bit (16M x 4-Bit x 4 Bank) DDR333 SDRAM in TSOP packages and three 16-bit drivers in TSSOP packages. This 184-pin DIMM uses gold contact fingers and requires +2.5V. The electrical and mechanical specifications are as follows:

FEATURES:

☑ Clock Cycle Time (tCK) 6ns (min.) / 12ns (max.)


✓ Row Cycle Time (tRC)✓ Refresh Row Cycle Time (tRFC)60ns (min.)72ns (min.)

☑ Row Active Time (tRAS) 42ns (min.) / 70,000ns (max.)


✓ Single Power Supply of +2.5V (+/-.2V) ✓ Power (IDD0) 7.225 W (operating)

☑ UL Rating 94 V - 0

Note: The module defined in this data sheet is one of several configurations available under this part number. While all configurations are compatible, the DRAM combination and/or the module height may vary from what is described here. However, in no configuration will the module height exceed 1.200" (30.48mm).



COMP SIDE



30.48

17.80

10.00

2.30

0.00

1.80

FULL RAD.

4.00
4 PLCS
2.5 DIA
2 PLCS

Figure 1: KVR333X72RC25/512 184-Pin DIMM