



PIN NO.	1	2	3	4	5	6	7	8
SYMBOL	VSS	VDD	V0	RS	R/W	E	DB0	DB1

PIN NO.	9	10	11	12	13	14	15	16
SYMBOL	DB2	DB3	DB4	DB5	DB6	DB7	LEDA	LEDK

NOTES:

1. DISPLAY TYPE: TN
2. DISPLAY MODE: REFLECTIVE/POSITIVE
3. VIEWING DIRECTION: 6 O'CLOCK
4. POWER SUPPLY FOR LOGIC: 5.0 V
5. OPERATING TEMP: 0°C TO 50°C
6. STORAGE TEMP: -20°C TO 70°C
7. DRIVER IC: S6A0069 Or Equ.
8. BACK LIGHT: NONE

TOLERANCE
>0~6 ±0.10
>6~80 ±0.20
>80~240 ±0.30
>240~400 ±0.50
// 1.0 ±0.10



HTDISPLAY CO., LTD.

DRAWING No.: HC160101C-TR60N-VA
 DRAWING TITLE : LCM DRAWING
 FILE No. : 8

REV. : A
 PROJECTION:
 SCALE : -
 UNIT : mm
 SHEET : 1/1

REV.	CHANGE CONTENT	BY	DATE