



PIN NO.	SYMBOL
1	RS
2	R/W
3	E
4	VDD
5	VSS
6	D0
7	D1
8	D2
9	D3
10	D4
11	D5
12	D6
13	D7
14	A
15	K

NOTE:
 1. DISPLAY TYPE: STN, POSITIVE, TRANSLLECTIVE, GRAY
 2. VIEWING DIR.: 6:00
 3. DRIVE METHOD: 1/16DUTY, 1/4BIAS, Vop6.4V, VDD4.5V
 4. OP. TEMP.: -20°C~70°C
 5. ST. TEMP.: -30°C~80°C
 6. BACKLIGHT: LED 2.0V, 40mA, AMBER
 7. DRIVER IC: S6A1070

REV.	CHANGE CONTENT	BY	DATE

TOLERANCE		HTDISPLAY CO., LTD.		DRAWING No.: HCl60103C-GF62L-VA	
>0~6	±0.10	DESIGN	ZOUJYS	06.09.22	STANDARD
>6~80	±0.20	CHECKED			TECHNOLOGY
>80~240	±0.30	APPROVED			QA
>240~400	±0.50				
// L ⊙ ±0.10					
REV. : A		SCALE : -		PROJECTION:	
FILE NO. : 7		UNIT : mm		SHEET : 1/1	