


SIPMOS® Power Transistor

BUZ 21

- N channel
- Enhancement mode
- Avalanche-rated



Type	V_{DS}	I_D	$R_{DS(on)}$	Package ¹⁾	Ordering Code
BUZ 21	100 V	21 A	0.085 Ω	TO-220 AB	C67078-S1308-A2

Maximum Ratings

Parameter	Symbol	Values	Unit
Continuous drain current, $T_C = 25^\circ\text{C}$	I_D	21	A
Pulsed drain current, $T_C = 25^\circ\text{C}$	$I_{D\text{ puls}}$	84	
Avalanche current, limited by $T_j\text{max}$	I_{AR}	21	
Avalanche energy, periodic limited by $T_j\text{(max)}$	E_{AR}	11	mJ
Avalanche energy, single pulse $I_D = 21\text{ A}$, $V_{DD} = 25\text{ V}$, $R_{GS} = 25\text{ }\Omega$ $L = 340\text{ }\mu\text{H}$, $T_j = 25^\circ\text{C}$	E_{AS}	100	
Gate-source voltage	V_{GS}	± 20	V
Power dissipation, $T_C = 25^\circ\text{C}$	P_{tot}	75	W
Operating and storage temperature range	T_j , T_{stg}	- 55 ... + 150	°C

Thermal resistance, chip-case	$R_{th\text{ JC}}$	≤ 1.67	K/W
DIN humidity category, DIN 40 040		E	-
IEC climatic category, DIN IEC 68-1		55/150/56	

1) See chapter Package Outlines.

Electrical Characteristicsat $T_j = 25^\circ\text{C}$, unless otherwise specified.

Parameter	Symbol	Values			Unit
		min.	typ.	max.	

Static characteristics

Drain-source breakdown voltage $V_{GS} = 0\text{ V}, I_D = 0.25\text{ mA}$	$V_{(BR)DSS}$	100	-	-	V
Gate threshold voltage $V_{GS} = V_{DS}, I_D = 1\text{ mA}$	$V_{GS(\text{th})}$	2.1	3.0	4.0	
Zero gate voltage drain current $V_{DS} = 100\text{ V}, V_{GS} = 0\text{ V}$	I_{DSS}				μA
$T_j = 25^\circ\text{C}$		-	0.1	1.0	
$T_j = 125^\circ\text{C}$		-	10	100	
Gate-source leakage current $V_{GS} = 20\text{ V}, V_{DS} = 0\text{ V}$	I_{GSS}	-	10	100	nA
Drain-source on-resistance $V_{GS} = 10\text{ V}, I_D = 13\text{ A}$	$R_{DS(\text{on})}$	-	0.065	0.085	Ω

Dynamic characteristics

Forward transconductance $V_{DS} \geq 2 \times I_D \times R_{DS(on)\text{max}}, I_D = 13\text{ A}$	g_{fs}	8	11	-	S
Input capacitance $V_{GS} = 0\text{ V}, V_{DS} = 25\text{ V}, f = 1\text{ MHz}$	C_{iss}	-	1000	1300	pF
Output capacitance $V_{GS} = 0\text{ V}, V_{DS} = 25\text{ V}, f = 1\text{ MHz}$	C_{oss}	-	300	530	
Reverse transfer capacitance $V_{GS} = 0\text{ V}, V_{DS} = 25\text{ V}, f = 1\text{ MHz}$	C_{rss}	-	150	240	
Turn-on time t_{on} , ($t_{on} = t_{d(on)} + t_f$) $V_{DD} = 30\text{ V}, V_{GS} = 10\text{ V}, I_D = 3\text{ A}, R_{GS} = 50\text{ }\Omega$	$t_{d(on)}$	-	25	40	ns
	t_f	-	50	75	
Turn-off time t_{off} , ($t_{off} = t_{d(off)} + t_f$) $V_{DD} = 30\text{ V}, V_{GS} = 10\text{ V}, I_D = 3\text{ A}, R_{GS} = 50\text{ }\Omega$	$t_{d(off)}$	-	160	210	
	t_f	-	80	110	


Electrical Characteristics (cont'd)
at $T_i = 25^\circ\text{C}$, unless otherwise specified.

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
Reverse diode					
Continuous reverse drain current $T_C = 25^\circ\text{C}$	I_S	—	—	21	A
Pulsed reverse drain current $T_C = 25^\circ\text{C}$	I_{SM}	—	—	84	
Diode forward on-voltage $I_S = 42 \text{ A}, V_{GS} = 0 \text{ V}$	V_{SD}	—	1.3	1.7	V
Reverse recovery time $V_R = 30 \text{ V}, I_F = I_S, di_F / dt = 100 \text{ A}/\mu\text{s}$	t_{rr}	—	150	—	ns
Reverse recovery charge $V_R = 30 \text{ V}, I_F = I_S, di_F / dt = 100 \text{ A}/\mu\text{s}$	Q_{rr}	—	0.48	—	μC

Characteristics at $T_i = 25^\circ\text{C}$, unless otherwise specified.

Total power dissipation


$$P_{\text{tot}} = f(T_C)$$



Typ. output characteristics

$$I_D = f(V_{DS})$$


parameter: $t_p = 80 \mu\text{s}$



Safe operating area

$$I_D = f(V_{DS})$$


parameter: $D = 0.01$, $T_C = 25^\circ\text{C}$



Typ. transfer characteristics


$$I_D = f(V_{GS})$$

parameter: $t_p = 80 \mu\text{s}$, $V_{DS} = 25 \text{ V}$




Typ. drain-source on-resistance


$$R_{DS(on)} = f(I_D)$$

parameter: V_{GS} **Drain-source on-resistance**


$$R_{DS(on)} = f(T_j)$$

parameter: $I_D = 13$ A, $V_{GS} = 10$ V, (spread)**Typ. forward transconductance**

$$g_{fs} = f(I_D)$$

parameter: $t_p = 80 \mu\text{s}$ **Gate threshold voltage**


$$V_{GS(th)} = f(T_j)$$

parameter: $V_{GS} = V_{DS}$, $I_D = 1$ mA, (spread)

Typ. capacitances

$$C = f(V_{DS})$$


parameter: $V_{GS} = 0 \text{ V}$, $f = 1 \text{ MHz}$



Drain current

$$I_D = f(T_C)$$


parameter: $V_{GS} \geq 10 \text{ V}$



Forward characteristics of reverse diode

$$I_F = f(V_{SD})$$


parameter: T_j , $t_p = 80 \mu\text{s}$, (spread)



Avalanche energy $E_{AS} = f(T_j)$

$$\text{parameter: } I_D = 21 \text{ A}, V_{DD} = 25 \text{ V}$$


$$R_{GS} = 25 \Omega, L = 340 \mu\text{H}$$



Transient thermal impedance

$$Z_{th\ JC} = f(t_p)$$

parameter: $D = t_p / T$

**Typ. gate charge**

$$V_{GS} = f(Q_{Gate})$$

parameter: $I_{D\ puls} = 36.0\text{ A}$

