

L-59EGW-TNR2.54	HIGH EFFICIENCY RED / GREEN
L-59EYW-TNR2.54	HIGH EFFICIENCY RED / YELLOW
L-59GYW-TNR2.54	GREEN / YELLOW

Features

- FOR THE USE OF AUTOMATIC INSERTION MACHINE.
- 2.54mm FORMED LEAD.
- LED LAMPS ALSO AVAILABLE IN TAPE & BOX PACKAGE.


Description

The High Efficiency Red source color devices are made with Gallium Arsenide Phosphide on Gallium Phosphide Orange Light Emitting Diode.

The Green source color devices are made with Gallium Phosphide Green Light Emitting Diode.

The Yellow source color devices are made with Gallium Arsenide Phosphide on Gallium Phosphide Yellow Light Emitting Diode.

Package Dimensions



Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is $\pm 0.25(0.01")$ unless otherwise noted.
3. Lead spacing is measured where the lead emerge package.
4. Specifications are subject to change without notice.

Selection Guide

Part No.	Dice	Lens Type	Iv (mcd) @ 20 mA		Viewing Angle
			Min.	Typ.	
L-59EGW-TNR2.54	HIGH EFFICIENCY RED (GaAsP/GaP)	WHITE DIFFUSED	18	60	60°
	GREEN (GaP)		18	50	
L-59EYW-TNR2.54	HIGH EFFICIENCY RED (GaAsP/GaP)	WHITE DIFFUSED	18	60	60°
	YELLOW (GaAsP/GaP)		18	40	
L-59GYW-TNR2.54	GREEN (GaP)	WHITE DIFFUSED	18	50	60°
	YELLOW (GaAsP/GaP)		18	40	

Note:

1. $\theta_{1/2}$ is the angle from optical centerline where the luminous intensity is 1/2 the optical centerline value.

Electrical / Optical Characteristics at T_A=25°C


Symbol	Parameter	Device	Typ.	Max.	Units	Test Conditions
λ_{peak}	Peak Wavelength	High Efficiency Red Green Yellow	627 565 590		nm	I _F =20mA
λ_D	Dominate Wavelength	High Efficiency Red Green Yellow	625 568 588		nm	I _F =20mA
$\Delta\lambda_{1/2}$	Spectral Line Half-width	High Efficiency Red Green Yellow	45 30 35		nm	I _F =20mA
C	Capacitance	High Efficiency Red Green Yellow	15 15 20		pF	V _F =0V;f=1MHz
V _F	Forward Voltage	High Efficiency Red Green Yellow	2.0 2.2 2.1	2.5 2.5 2.5	V	I _F =20mA
I _R	Reverse Current	All		10	uA	V _R = 5 V

Absolute Maximum Ratings at T_A=25°C






Parameter	High Efficiency Red	Green	Yellow	Units
Power dissipation	105	105	105	mW
DC Forward Current	30	25	30	mA
Peak Forward Current [1]	160	140	140	mA
Reverse Voltage	5	5	5	V
Operating/Storage Temperature	-40°C To +85°C			
Lead Solder Temperature [2]	260°C For 5 Seconds			






Notes:






- 1/10 Duty Cycle, 0.1ms Pulse Width.
- 2mm below package base.



High Efficiency Red / Green L-59EGW-TNR2.54









Reel Dimensions

L-59-TNR2.54



ANODE LEAD
LEAVES THE REEL FIRST

