

• Products

- O By Type
 - Connectors
 - Electromechanical Components
 - Electronic Modules
 - Fiber Optics
 - Filters
 - Identification & Labeling
 - Passive Components
 - Power Sources
 - RF & Microwave Products
 - Tooling Products
 - Touch Screen Displays
 - Tubing, Molded and Harnessing Products
 - Wire, Cable and Cable Assemblies
 - List all product types...
- O <u>By Industry</u>
 - Aerospace & Defense Products
 - Appliance
 - Automotive
 - Mutomotive
 - Communications
 - Computer & Consumer Electronics
 - Industrial & Commercial
 - Instrumentation & Medical
- O By Brand
- O A to Z
- O <u>Product News</u>

• **Documentation**

- O Find Documents & Drawings
- O Find CAD Models
- O SPICE/Electrical Models
- O NAFTA Certificate of Origin
- O White Papers

Resources

- O RoHS Compliance & Alternates
- O Cross Reference Products
- O Compare Multiple Products
- O Check Distributor Inventory
- O Find Authorized Distributors

• My Account

- O Sign In
- O Register

• Customer Support

- O Support
- O RoHS Support Center
- O Glossary of Terms
- O eBulletin Newsletter

OSZ-SS-124DM8,000 Product Details



OSZ-SS-124DM8,000
Active

Power PC Board Relays



Product Highlights:

- OSZ Series
- Contact Arrangement = 1 Form A, SPST-NO, 1 N/O
- Contact Current Rating = 16 Amps.
- Monostable Coil Magnetic System
- Without Coil Suppression Diode

View all Features | Find Similar Products



- Check Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Compare Products
- Contact Us About This Product

Documentation & Additional Information

Product Drawings:

• None Available

Catalog Pages/Data Sheets:

None Available

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

None Available

Additional Information:

Product Line Information

Additional Product Images:

- Schematic
- Wiring Diagram
- PCB Layout (Bottom Surface)

Related Products:

• Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- <u>Termination Type</u> = Through Hole
- Comment = Meets UL Tungsten TV-8 rating.

Electrical Characteristics:

- Contact Current Rating (Amps.) = 16
- Coil Resistance (?) = 1100
- <u>Coil Power, Nominal (mW)</u> = 540
- Actuating System = DC
- <u>Input Voltage (VDC)</u> = 24

Body Related Features:

- $\underline{Series} = OSZ$
- Polarized = No

Contact Related Features:

- Mounting Options = PC Board
- Enclosure = Flux-Tight
- FCC Part 68 Isolation = No
- Relay Type = PCB
- Contact Material = Silver Tin Oxide
- Approx. Dimensions (L x W x H) (mm [in]) = 24.40 x 12.90 x 24.80 [.961 x .508 x .977]
- Approved Standards = UL Recognized, CSA Certified

Configuration Related Features:

- Contact Arrangement = 1 Form A, SPST-NO, 1 N/O
- <u>Coil Magnetic System</u> = Monostable
- <u>Coil Suppression Diode</u> = Without
- <u>Coil Selection Criteria</u> = Nominal Voltage
- Coil Latching = Without
- <u>LED Indicator</u> = Without

Industry Standards

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240C, Wave solder capable to 260C, Wave solder capable to 265C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Other:

● Brand = OEG