



**GDCX-P Series**  
*Perpendicular Through Hole*

**Features**

- Available in 4, 6, and 8 position housings
- Vertical mount
- Through Hole contacts
- CSA certified File No. LR 78160

**Performance Specifications**

**Materials and Finish**

**Housing Material**

PBT thermoplastic UL 94V-0 rated Color: black

**Contact Material** : Phosphor bronze

**Electrical Characteristics**

**Insulation Resistance :**

500 Megohms min.

**Dielectric Withstanding Voltage :**

1000V rms, 60Hz

**Contact Resistance :**

20 milliohms max.

**Current Rating** : 1.5A

**Operating Temperature :**

-40°C to +85°C

**Durability Rating :**

500 mating cycles min.

**MODULAR JACKS AND PLUGS**

**GDCX-P Series**

**Documentation & Ordering Information**


Kycon Part # \_\_\_\_\_

**Part Number Builder**

Series	Panel Stop Option	Shield Option	Positions and Contacts	Plating Option		
Series GDCX-P - Perpendicular Through Hole Modular Jacks						
Panel Stop and Shield Options						
Panel Stop & Shield Option	No of Positions and Contacts K - Key Option					
PA With Panel Stops Non-Shielded	44	64	66	88	88K	-
PAS With Panel Stops Shielded	-	-	-	88	88K	-
PN With out Panel Stops Non-Shielded	44	64	66	88	88K	1010 *
PNS With out Panel Stop Shielded	-	-	-	88	88K	-
* Not Available with 50µ" Gold Plating						
Plating Option Blank - Standard 50 - 50µ" Gold Plating						

**GDCX-P Series Dimensions**

Dimensions in mm

