

PART NUMBER SELECTION GUIDE



	SERIES	COLOR CODE	ELECTRICAL CHARACTERISTICS	OPTIONS	
STANDARD	SINGLE CHIP PT301 PT302	TR5 TY5 TG5	VDC 2Vf 6V 14V 28V	T - WIRE TERMINAL W6 - 6" WIRE	

COLOR CODE LEGEND





LENS CHARACTERISTICS	LED COLOR	BRIGHTNESS CODE
T-TRANSLUCENT TW-TRANSLUCENT WHITE	R-RED Y-YELLOW G-GREEN B-BLUE O-ORANGE RG-RED/GREEN YG-YELLOW/GREEN	4-STANDARD 5-STANDARD 6-HIGH INTENSITY 3K-HIGH INTENSITY

	SERIES	COLOR CODE	ELECTRICAL CHARACTERISTICS		OPTIONS
CUSTOM	SINGLE CHIP PT301 PT302	TR6 TY3K TG6 TO5 TB5 TWRG4 - BICOLOR TWYG4 - BICOLOR	VDC 5V 12V 24V	VAC 5VAC 6VAC 12VAC 14VAC 24VAC 28VAC	W12 - 12" WIRE W18 - 18" WIRE W24 - 24" WIRE


PART SPECIFICATIONS


- 1. PART NUMBERS CONSISTING OF OPTIONS NOT FOUND IN THE STANDARD BOX ARE CUSTOM.
- 2. FOR COMPLETE PART NUMBER SELECT ONE OPTION FROM EACH OF THE FOUR COLUMNS FROM LEFT TO RIGHT.
- 3. BRIGHTNESS CODES LISTED ARE SET BY THE FACTORY FOR ALL COLORS. THE ABOVE CHART IS FOR REFERENCE ONLY.
- 4. MOUNTING DIAMETER 0.230 (5.8mm) TO 0.250 (7.9mm).
- 5. PANEL THICKNESSES FROM 0.031 (0.8mm) TO 0.125 (3.2mm).
- 6. HOUSING MATERIAL IS CHROME PLATED BRASS.
- 7. WIRE LEADS ARE RED FOR ANODE AND BLACK FOR CATHODE.
- 8. TERMINALS ARE .020 (0.5mm) SQUARE.





PT301-T





PT302-T