




Temperature Compensated Crystal Oscillator

TCXO and VCXO series are the Highly stable Crystal oscillators for mobile phones and automobile communications. Miniature type for smaller space can be flexibly applied for various customer requirements.

■ Features

- Miniature size 0.2cc , 0.1cc and 0.06cc
- Surface mounting
- Low power
- Low phase noise

■ Dimensions



■ Specifications

Item	TCXO – R1,R2	VCXO – R1	TCXO – R06	Unit	Note
Standard Frequency	12.8,13.0,19.2,19.44,19.68	13.0, 27.0	13.0, 19.20, 19.68	MHz	
Storage Temperature	-40 ~ +85	-40~ +85	-40~ +85	°C	
Operating Temperature	-30~ +75	-20~ +75	-30~ +75	°C	
Power Supply	DC +3.0, +2.7	DC +3.0, +2.7	DC +3.0, +2.8	V	
Current	1.5Max.	1.5Max.	1.5Max.	mA	
Output	0.8Min.	0.8Min.	0.8Min.	Vp-p	
Loading	10kΩ//10pF	10kΩ//10pF	10kΩ//10pF		
Frequency Control Range	± 7.0Min.	± 50Min., ± 20Min., ± 10Min.	± 10Min.		1.5 ± 1V
Frequency Stability				ppm	-30~ +75 °C
for Temperature	± 2.5	± 8.0	± 2.5		
for Power Supply	± 0.3	± 0.3	± 0.3		
for Loading	± 0.2	± 0.2	± 0.2		
for Aging	± 1.0	± 1.0	± 1.0		Year
Board Mount Area	1(TCXO – R2)	0.58	0.33		

Specifications which are different from those above may be acceptable.