

ELPAQ

A division of ELMO Semiconductor Corp.

EMS512K8B

70 - 100ns

4Mb CMOS STATIC SRAM

FEATURES

- High density SRAM module
- Organized as 512,288 x 8
- Access time 70 - 100ns
- Low power consumption
Standby: 50µW(typ.)
Operating: 200mW(typ.)
- Power supply voltage 5V±10%
- TTL compatible inputs and outputs
- Fully static operation
- 32 pin DIP package
- JEDEC standard pinout
- MIL or commercial temperature range

Pin Configuration

A18	1	32	VCC
A16	2	31	A15
A14	3	30	A17
A12	4	29	$\overline{WE}$
A7	5	28	A13
A6	6	27	A8
A5	7	26	A9
A4	8	25	A11
A3	9	24	$\overline{OE}$
A2	10	23	A10
A1	11	22	$\overline{CE}$
A0	12	21	I/O8
I/O1	13	20	I/O7
I/O2	14	19	I/O6
I/O3	15	18	I/O5
GND	16	17	I/O4

Pin Description

A0 - A18	Address Inputs
I/O1 - I/O8	Data Inputs/Outputs
$\overline{CE}$	Chip Enable
$\overline{OE}$	Output Enable
$\overline{WE}$	Write Enable
VCC	Power Supply
GND	Ground

GENERAL DESCRIPTION

The ELPAQ EMS512Kx8B is a high performance 4Mb CMOS SRAM module organized as 512,288 bytes of 8 bits each, using four 1Mb SRAMs and a decoder. The EMS512Kx8B is packaged in a 32 lead 600 mil wide ceramic or plastic DIP package. The module is offered in a variety of temperature and speed combinations.

The EMS512Kx8B is functionally equivalent and plug-in compatible to the 4Mb monolithic SRAM, and can therefore be used in new designs where the 4Mb monolithic will eventually be used.

All inputs and outputs are TTL compatible and the module operates from a single 5V power supply. The EMS512Kx8B is a fully asynchronous SRAM and requires no clocks for operation. The module is also available in Low Power and Low Power with Data Retention versions for applications where low current and low stand-by voltages are required.

Writing data to the module is accomplished by bringing the chip enable ($\overline{CE}$) and write enable ($\overline{WE}$) inputs LOW. Data present on the eight I/O pins (I/O₁ - I/O₈) of the device is then written into the memory location specified by the address inputs (A₀ - A₁₈). Reading data from the device is accomplished by bringing chip enable ($\overline{CE}$) and ($\overline{OE}$) LOW while write enable remains inactive or HIGH. The data in the location specified by the address inputs will then appear on the I/O pins.


ELPAQ

A division of ELMO Semiconductor Corp.


EMS512K8B

70 - 100ns


BLOCK DIAGRAM



PACKAGE OUTLINE



Package Type MO1, 32 Lead .600" Sidebrazed DIP



Package Type MO6, 32 Lead .600" Plastic DIP

ABSOLUTE MAXIMUM RATINGS

Storage Temperature

Ceramic Packages	-65°C to +150°C
Plastic Packages	-55°C to +125°C

Voltage and Current

Supply Voltage	-0.5 to +7.0V
Input Voltage	-0.5 to Vcc+0.5V
Input/Output Voltage	-0.5 to Vcc+0.5V
Allowable Power Dissipation	1W

Soldering Temperature*Time 260°C * 10s

OPERATING RANGES

Operating Temperature

Commercial	0°C to +70°C
Industrial	-40°C to +85°C
Military	-55°C to +125°C

Voltage and Current

Supply Voltage	4.5 to 5.5V
Input High Voltage	2.2 to Vcc+0.3V
Input Low Voltage	-0.3 to 0.8V

FUNCTIONAL TRUTH TABLE

$\overline{CE}$	$\overline{OE}$	$\overline{WE}$	Mode	I/O1 - 8	Vcc Current
H	X	X	Not Selected	High Z	ISB1, ISB2
L	H	H	Output Disable	High Z	ICC
L	L	H	Read	Data Out	ICC
L	X	L	Write	Data In	ICC

CAPACITANCE (Ta=25°C, f=1MHz)

Item	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Input Capacitance	CIN	VIN = 0V		30	50	pF
Input/Output Capacitance	CIO	VIO = 0V		40	50	pF

Note: This parameter is sample tested and not 100% tested

ELPAQ

A division of ELMO Semiconductor Corp.

EMS512K8B

70 - 100ns

DC CHARACTERISTICS ($V_{CC}=5V\pm 10\%$, $T_a=T_{opr}$)

Item	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Input Leakage Current	IIL	$V_{IN}=GND$ or V_{CC}	-10		10	μA
Output Leakage Current	IOL	$V_{I/O}=GND$ or V_{CC} , $\overline{CE}=V_{IH}$ $\overline{OE}=V_{IH}$ or $\overline{WE}=V_{IL}$	-10		10	μA
Average Operating Current	ICC	Min. Cycle, $I_{out}=0mA$		40	70	mA
Standby Current	ISB1	$\overline{CE}\geq V_{CC}-0.2V$, $V_{IN}\geq V_{CC}-0.2V$		0.01	1.5	mA
	ISB2	$\overline{CE}=V_{IH}$, $V_{IN}=V_{IL}$ or V_{IH}		2	5	mA
Output High Voltage	VOH	$I_{OH}=-1.0mA$	2.4			V
Output Low Voltage	VOL	$I_{OL}=2.1mA$			0.4	V

AC CHARACTERISTICS ($V_{CC}=5V\pm 10\%$, $T_a=T_{opr}$)

AC Test Conditions

Item	Condition
Input Pulse High Level	$V_{IH}=3V$
Input Pulse Low Level	$V_{IL}=0V$
Input Pulse Rise Time	$t_r=5ns$
Input Pulse Fall Time	$t_f=5ns$
Input and Output Timing Level	1.5V
Output Load	Fig. 1




Fig. 1

ELPAQ*A division of ELMO Semiconductor Corp.***EMS512K8B****70 - 100ns****Read Cycle**

Item	Symbol	-70		-85		-100		Unit
		Min.	Max.	Min.	Max.	Min.	Max.	
Read Cycle Time	TAVAV	70		85		100		ns
Address Access Time	TAVQV		70		85		100	ns
Chip Enable Access Time	TELQV		70		85		100	ns
Output Enable to Output Valid	TGLQV		40		45		50	ns
Chip Enable to Output in High Z	TEHQZ		30		30		35	ns
Chip Enable to Output in Low Z	TELOX	15		15		15		ns
Output Disable to Output in High Z	TGHQZ		25		25		35	ns
Output Enable to Output in Low Z	TGLQX	5		5		5		ns
Output Hold from Address Change	TAVQX	10		10			15	ns


Write Cycle

Item	Symbol	-70		-85		-100		Unit
		Min.	Max.	Min.	Max.	Min.	Max.	
Write Cycle Time	TAVAV	70		85		100		ns
Address Valid to End of Write	TAVWH	60		75		75		ns
Chip Enable to End of Write	TELWH	65		75		75		ns
	TWLEH	65		75		75		ns
Data to Write Time Overlap	TDVWH	30		30		40		ns
	TDVEH	30		30		40		ns
Data Hold Time from Write	TWHDX	0		0		0		ns
	TEHDX	0		0		0		ns
Write Pulse Width	TWLWH	50		60		70		ns
	TELEH	50		60		70		ns
Address Set-up Time	TAVWL	0		0		0		ns
	TAVEL	0		0		0		ns
Write Recovery Time	TWHAX	5		5		5		ns
	TEHAX	5		5		5		ns
Write to Output in High Z	TWLQZ		25		30		30	ns
Output Active from End of Write	TWHQX	5		5		10		ns


Timing Diagrams

Read Cycle Timing

Read Cycle 1: $\overline{CE}=\overline{OE}=V_{IL}$, $\overline{WE}=V_{IH}$




Read Cycle 2: $\overline{WE}=V_{IH}$




Write Cycle Timing

Write Cycle 1: $\overline{WE}$ Control



Write Cycle 2: $\overline{CE}$ Control



ELPAQ

A division of ELMO Semiconductor Corp.

EMS512K8B

70 - 100ns

NOTES:

ORDERING INFORMATION

EMS512K8B

MO1

-70

C

Temperature Range

C = Commercial (0 - 70°C)

I = Industrial (-40 - +85°C)

D = MIL Temp (-55 - +125°C)

M = MIL Screen (-55 - +125°C)

Speed

-70 = 70ns Access Time

-85 = 85ns Access Time

-100 = 100ns Access Time

Package

MO1 = .600" 32 Lead Ceramic DIP

MO6 = .600" 32 Lead Plastic DIP