


samtec

**MOLD-TO-POSITION
PRODUCT**

 Minimums or set-up charges
may apply. Call Samtec.

AP-314-G-A1



SCREW MOUNT ADAPTOR PLUGS

Mates with:
IC, ICS, ICO,
ICA, ICE, ICH

Machined pin DIP adaptor plugs

DIP adaptor plugs are
available in a wide
variety of lead counts
from 8 through 64 pins.

Samtec offers a choice
of many terminal styles
including solder, wire-
wrap, solder pot, and
others. Terminals can be
gold or tin plated.
AP & APS series adaptor
plugs feature a UL rated
G.F. polyester body with
mounting holes.

Low cost stamped pin
adaptor plugs and
mating covers are also
available from Samtec.

Specifications: AP & APS



Insulator Material:

Black Glass Filled Polyester

Flammability Rating:

UL 94V-O

Insulation Resistance:

5000 megohm @ 500 VDC

Temperature Range:

-55°C to +125°C

Withstanding Voltage:

1000 VRMS @ 60 Hz

Terminal Material:

Brass except styles -M, -N,

-P and -Q are Phosphor

Bronze

Plating:

Au over 50µ" Ni or Sn over

100µ" Cu or 50µ" Ni

Current Rating:

1 amp continuous

@ 100 VDC per contact

Terminal Retention in

Body:

5 lbs. against barb

TYPE PLUG

AP
= Dip Adaptor
Plug

APS
= Dip Adaptor
Plug

ROW SPACING & NUMBER OF CONTACTS


-306 = .300 Row 06 Contacts

-308 = .300 Row 08 Contacts

-310 = .300 Row 10 Contacts

Part No.	A Length	B Width
AP or APS-306	(8.89) .350	(10.16) .400
AP or APS-308	(11.43) .450	(10.16) .400
*AP or *APS-310	(13.97) .550	(10.16) .400

* Mounting hole off center on 10 position.



-314 = .300 Row 14 Contacts

-316 = .300 Row 16 Contacts

-318 = .300 Row 18 Contacts


-320 = .300 Row 20 Contacts

-324 = .300 Row 24 Contacts

-422 = .400 Row 22 Contacts

-424 = .400 Row 24 Contacts

Part No.	A LENGTH	B WIDTH	E MNT HOLES
AP or APS-314	(17.78) .700	(10.16) .400	(10.16) .400
AP or APS-316	(20.32) .800	(10.16) .400	(12.70) .500
AP or APS-318	(22.86) .900	(10.16) .400	(15.24) .600
AP or APS-320	(25.40) 1.000	(10.16) .400	(17.78) .700
AP or APS-324	(30.48) 1.200	(10.16) .400	(22.86) .900
AP or APS-422	(27.94) 1.100	(10.16) .400	(20.32) .800
AP-424	(30.48) 1.200	(12.70) .500	(22.86) .900




-610 = .600 Row 10 Contacts

-614 = .600 Row 14 Contacts

-616 = .600 Row 16 Contacts

-618 = .600 Row 18 Contacts

Part No.	A Length
AP-610	(12.70) .500
AP-614	(17.78) .700
AP-616	(20.32) .800
AP-618	(22.86) .900



Note:
Some sizes, styles and
options are non-standard,
non-returnable.


Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 • Fax: 812-948-5047
SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0 • Fax: +49 (0) 89 / 89460-299
SAMTEC JAPAN • Tel: +65-6745-5955 • Fax: +65-6745-5956
SAMTEC KOREA • Tel: 82-31-717-5685 • Fax: 82-31-717-5681
SAMTEC SILICON VALLEY • Tel: 408-395-5900 • Fax: 408-395-1520
SAMTEC FRANCE • Tel: 01 60 95 06 60 • Fax: 01 60 95 06 61
SAMTEC CHINA • Tel: 86-21-61103766 • Fax: 86-21-61103766
SAMTEC SOUTH AFRICA • Tel: 27 11 4528112 • Fax: 27 11 4528112
SAMTEC UK • Tel: 01236 739292 • Fax: 01236 727113
SAMTEC ITALY • Tel: 39 039 6890337 • Fax: 39 039 6890315
SAMTEC INDIA • Tel: +91-80-3272 1612 • Fax: +91-80-4152 8187
SAMTEC TAIWAN • Tel: 886 02 2698-3367 • Fax: 886 02 8698-2159
SAMTEC ANZ • Tel: 613 9512 7747 • Fax: 613 9512 7745

samtec

**MOLD-TO-POSITION
PRODUCT**

 Minimums or set-up charges
may apply. Call Samtec.


AP-314-T-A

AP & APS SERIES

PLATING OPTION


-G
= 20μ" Gold


-T
Tin

STYLE OPTION


-A or -A1
= Round Pin

STYLE	X DIA
-A	(0.64) .025
-A1	(0.46) .018



 Style A Component No. = T-1R0-
Style A1 Component No. = T-1R5-

-B
= Solder Pot


Component No. = T-1R1-

-C
= Slotted Head



Component No. = T-1R2-

-D
= Wire-Wrap



Component No. = T-1S4-1-1

-E
= Slot-head W.W.


(-648 N/A)




Component No. = T-1S5-

-F
= Flat-head W.W.



Component No. = T-1S2-

-J
= Solder Shell


Component No. = S-1P1-

-K
= Test Point


Component No. = T-1R15-

-M, -N, -P or -Q
= Interconnect Post


Component No. = T-1R14-

STYLE	Y
-M	(1.52) .060
-N	(4.67) .185
-P	(11.05) .435
-Q	(17.40) .685

-624 = .600 Row 24 Contacts

-628 = .600 Row 28 Contacts

-632 = .600 Row 32 Contacts

-640 = .600 Row 40 Contacts

-940 = .900 Row 40 Contacts


-950 = .900 Row 50 Contacts

-964 = .900 Row 64 Contacts

PART NO.	A LENGTH	B WIDTH
AP or APS-624	(30.48)1.200	(17.78).700
AP or APS-628	(35.56)1.400	(17.78).700
AP or APS-632	(40.64)1.600	(17.78).700
AP or APS-640	(50.80)2.000	(17.78).700
*AP-940		
*†AP-950	(63.50)2.500	(26.27)1.050
AP-964	(81.28)3.200	

 *AP-940 and AP-950
are non-standard
non-returnable.

† Mounting hole off center on 50 positions



Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 • Fax: 812-948-5047
 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0 • Fax: +49 (0) 89 / 89460-299
 SAMTEC SCANDINAVIA • Tel: +46-84477280 • Fax: +46-84420413
 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 • Fax: 65 6841-1502
 SAMTEC HONG KONG • Tel: 852-26904858 • Fax: 852-26904842
 SAMTEC JAPAN • Tel: 045-475-1385 • Fax: 045-475-1340
 SAMTEC KOREA • Tel: 82-31-717-5685 • Fax: 82-31-717-5681
 SAMTEC SILICON VALLEY • Tel: 408-395-5900 • Fax: 408-395-1520
 SAMTEC FRANCE • Tel: 01 60 95 06 60 • Fax: 01 60 95 06 61
 SAMTEC CHINA • Tel: 86-21-61103766 • Fax: 86-21-61103766
 SAMTEC SOUTH AFRICA • Tel: 27 11 4528112 • Fax: 27 86 6714432
 SAMTEC UK • Tel: 01236 739292 • Fax: 01236 727113
 SAMTEC ITALY • Tel: 39 039 6890337 • Fax: 39 039 6890315
 SAMTEC INDIA • Tel: +91-80-3272 1612 • Fax: +91-80-4152 8187
 SAMTEC TAIWAN • Tel: 886 02 2698-3367 • Fax: 886 02 8698-2159
 SAMTEC ANZ • Tel: 613 9512 7747 • Fax: 613 9512 7745