

HUBER+SUHNER® DATA SHEET

Between Series Adapter: 31_PC24-SK-50-1/199_N



Description

Adaptor jack/jack
PC 2.4 jack (female) / SK jack (female)

Interface standards
IEC 60169-38

Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	40 GHz
Frequency range	DC to 40 GHz
Return loss	≥ 25 dB
Electrical Length	16.1 mm +/- 0.1

Mechanical Data

Number of matings	500
-------------------	-----

Environmental Data

Operating Temperature 2002/95/EC (RoHS)	-55 °C to 125 °C compliant
--	-------------------------------

Material Data

Piece Parts (PC 2.4)

Centre contact	Material Copper Beryllium Alloy
Outer contact	Stainless Steel
Body	Stainless Steel
Insulator	PPO_PPE

Surface Plating

SUCOPRO Plating

Piece Parts (SK)

Centre contact	Material Copper Beryllium Alloy
Outer contact	Stainless Steel
Body	Stainless Steel
Insulator	PPO_PPE

Surface Plating

SUCOPRO Plating

Related Documents

Outline drawing	DOU-00062612
-----------------	--------------

Ordering Information

Single package	31_PC24-SK-50-1/199_NE
----------------	------------------------



HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions