


POWER LINE CHOKES

PC-PVC SERIES

Body Size : A=16.50mm B=38.0mm
 Leading Wire : #AWG 20
 Testing : Inductance measured at 1KHz
 Sleeving : PVC shrink tubing (UL rated)
 Packaging : Bulk or Tape & Reel (1k pcs)



PART NO.	INDUCTANCE (μ H)	DC RESISTANCE MAX (Ω)	SATURATION CURRENT (Amps)	SUGGESTED CURRENT (Amps)	DIAMETER (NOMINAL) (mm)
PC-PVC-3R9K	3.9 \pm 10%	0.019	7.3	1.28	6.60
PC-PVC-4R7K	4.7 \pm 10%	0.022	6.3	1.28	6.60
PC-PVC-5R6K	5.6 \pm 10%	0.024	5.6	1.28	6.60
PC-PVC-6R8K	6.8 \pm 10%	0.026	5.3	1.28	6.60
PC-PVC-8R2K	8.2 \pm 10%	0.028	4.5	1.28	6.60
PC-PVC-100K	10 \pm 10%	0.033	4.1	1.28	6.60
PC-PVC-120K	12 \pm 10%	0.037	3.6	1.28	6.60
PC-PVC-150K	15 \pm 10%	0.040	3.3	1.28	6.60
PC-PVC-180K	18 \pm 10%	0.044	3.0	1.28	6.60
PC-PVC-220K	22 \pm 10%	0.050	2.7	1.28	6.60
PC-PVC-270K	27 \pm 10%	0.058	2.5	1.28	6.60
PC-PVC-330K	33 \pm 10%	0.075	2.2	1.008	6.60
PC-PVC-390K	39 \pm 10%	0.094	2.0	0.804	6.60
PC-PVC-470K	47 \pm 10%	0.109	1.8	0.804	6.60
PC-PVC-560K	56 \pm 10%	0.140	1.7	0.804	6.60
PC-PVC-680K	68 \pm 10%	0.131	1.5	0.804	6.60
PC-PVC-820K	82 \pm 10%	0.152	1.4	0.804	6.60
PC-PVC-101K	100 \pm 10%	0.208	1.2	0.632	6.60
PC-PVC-121K	120 \pm 10%	0.283	1.1	0.508	6.60
PC-PVC-151K	150 \pm 10%	0.340	1.0	0.508	6.60
PC-PVC-181K	180 \pm 10%	0.362	0.95	0.508	6.60
PC-PVC-221K	220 \pm 10%	0.430	0.86	0.508	6.60
PC-PVC-271K	270 \pm 10%	0.557	0.77	0.400	6.60
PC-PVC-331K	330 \pm 10%	0.665	0.70	0.400	6.60
PC-PVC-391K	390 \pm 10%	0.712	0.64	0.400	6.60
PC-PVC-471K	470 \pm 10%	1.15	0.59	0.315	6.60
PC-PVC-561K	560 \pm 10%	1.27	0.54	0.315	6.60
PC-PVC-681K	680 \pm 10%	1.61	0.49	0.250	6.60
PC-PVC-821K	820 \pm 10%	1.96	0.44	0.200	6.60
PC-PVC-102K	1000 \pm 10%	2.30	0.40	0.200	6.60
PC-PVC-122K	1200 \pm 10%	2.65	0.35	0.200	6.60
PC-PVC-152K	1500 \pm 10%	3.45	0.33	0.158	6.60
PC-PVC-182K	1800 \pm 10%	4.03	0.29	0.158	6.60
PC-PVC-222K	2200 \pm 10%	4.48	0.27	0.158	6.60
PC-PVC-272K	2700 \pm 10%	5.40	0.24	0.125	6.60
PC-PVC-332K	3300 \pm 10%	6.56	0.22	0.125	6.60
PC-PVC-392K	3900 \pm 10%	8.63	0.20	0.100	6.60
PC-PVC-472K	4700 \pm 10%	9.66	0.18	0.100	6.60
PC-PVC-562K	5600 \pm 10%	13.9	0.166	0.082	6.60
PC-PVC-682K	6800 \pm 10%	16.3	0.151	0.082	6.60
PC-PVC-822K	8200 \pm 10%	20.8	0.138	0.065	6.60
PC-PVC-103K	10000 \pm 10%	26.4	0.125	0.050	6.60
PC-PVC-123K	12000 \pm 10%	29.9	0.114	0.050	6.60
PC-PVC-153K	15000 \pm 10%	42.5	0.098	0.039	6.60
PC-PVC-183K	18000 \pm 10%	48.3	0.091	0.039	6.60