


Inductors

Subminiature, Shielded


FEATURES

- Classification is Grade 1, Class B.
- Subminiature shielded.
- Inductance range is .10 μ H to 100,000 μ H.
- Printed board mounting facilitated by 0.200" [5.08mm] grid spacing.
- Radial lead fixed inductor.
- High Q values.
- Unitized epoxy-molded construction.
- Shielded construction to allow maximum density packaging.

ELECTRICAL SPECIFICATIONS

Inductance Tolerance: $\pm 10\%$.

Dielectric Strength: 840VRMS at sea level.

Working Voltage: 300VDC.

Q and SRF Values: Minimum not less than 80% of specified value.

Maximum Current: Based on temperature rise not to exceed 35°C at + 90°C ambient.

MECHANICAL SPECIFICATIONS

Operating Temperature: - 55°C to + 125°C.

Terminal Pull: 3 pounds.

DENSITY SPECIFICATIONS

Weight: 1.5 grams maximum.


Shielding: 3% coupling maximum when two units are tested side by side.

ENVIRONMENTAL SPECIFICATIONS

Moisture: Per MIL-STD-202, Method 106.

Vibration: Low frequency, 10Hz to 55Hz @ .06" [1.52 mm] maximum total excursion at rate of 1 linear sweep per minute for 2 hours repeated for each of three mutually perpendicular planes.

Shock: 100g, 6ms, body mounted.

DIMENSIONS in inches [millimeters]

STANDARD ELECTRICAL SPECIFICATIONS

MODEL	IND. (μ H)	TOL.	Q NOM.	TEST FREQ. (MHz)	SELF-RESONANT FREQ. NOM. (MHz)	DCR MAX. (Ohms)	RATED DC CURRENT (mA)	INCREMENTAL* CURRENT (mA)
PC	0.10	$\pm 10\%$	70	25	> 250	0.030	2500	2500
PC	0.12	$\pm 10\%$	70	25	> 250	0.030	2500	2500
PC	0.15	$\pm 10\%$	70	25	> 250	0.030	2500	2500
PC	0.18	$\pm 10\%$	70	25	> 250	0.035	2400	2400
PC	0.22	$\pm 10\%$	70	25	> 250	0.038	2300	2300
PC	0.27	$\pm 10\%$	80	25	> 250	0.040	2200	2200
PC	0.33	$\pm 10\%$	80	25	> 250	0.040	2200	2200

*Incremental Current: The DC current required to cause a 5% reduction in the nominal inductance value.

STANDARD ELECTRICAL SPECIFICATIONS

MODEL	IND. (μ H)	TOL.	Q NOM.	TEST FREQ. (MHz)	SELF-RESONANT FREQ. NOM. (MHz)	DCR MAX. (Ohms)	RATED DC CURRENT (mA)	INCREMENTAL* CURRENT (mA)
PC	0.39	$\pm 10\%$	80	25	250	0.045	2100	2100
PC	0.47	$\pm 10\%$	80	25	230	0.045	2100	2100
PC	0.56	$\pm 10\%$	80	25	220	0.050	2000	2000
PC	0.68	$\pm 10\%$	80	25	190	0.055	1900	1900
PC	0.82	$\pm 10\%$	85	25	180	0.060	1800	1800
PC	1.0	$\pm 10\%$	85	25	160	0.070	1700	1700
PC	1.2	$\pm 10\%$	90	7.9	170	0.085	1670	1670
PC	1.5	$\pm 10\%$	100	7.9	155	0.100	1540	1540
PC	1.8	$\pm 10\%$	115	7.9	135	0.110	1470	1470
PC	2.2	$\pm 10\%$	110	7.9	120	0.120	1410	1410
PC	2.7	$\pm 10\%$	110	7.9	104	0.125	1380	1380
PC	3.3	$\pm 10\%$	90	7.9	93	0.165	1200	1200
PC	3.9	$\pm 10\%$	90	7.9	87	0.180	1135	1135
PC	4.7	$\pm 10\%$	95	7.9	79	0.245	985	985
PC	5.6	$\pm 10\%$	95	7.9	72	0.265	950	950
PC	6.8	$\pm 10\%$	85	7.9	63	0.330	853	853
PC	8.2	$\pm 10\%$	95	7.9	60	0.460	720	720
PC	10	$\pm 10\%$	90	7.9	54	0.640	620	620
PC	12	$\pm 10\%$	120	2.5	37	0.800	545	545
PC	15	$\pm 10\%$	120	2.5	28.8	0.865	520	520
PC	18	$\pm 10\%$	115	2.5	23.8	0.940	504	504
PC	22	$\pm 10\%$	125	2.5	21.3	1.03	460	460
PC	27	$\pm 10\%$	115	2.5	20.6	1.18	418	418
PC	33	$\pm 10\%$	120	2.5	18.6	1.30	398	398
PC	39	$\pm 10\%$	120	2.5	17.7	1.41	385	385
PC	47	$\pm 10\%$	110	2.5	14.9	1.61	350	350
PC	56	$\pm 10\%$	115	2.5	13.9	2.08	330	333
PC	68	$\pm 10\%$	105	2.5	12.9	2.20	320	330
PC	82	$\pm 10\%$	105	2.5	11.7	2.42	300	320
PC	100	$\pm 10\%$	95	2.5	10.5	2.15	333	300
PC	120	$\pm 10\%$	95	0.79	5.6	2.38	316	190
PC	150	$\pm 10\%$	90	0.79	5.2	2.52	306	175
PC	180	$\pm 10\%$	95	0.79	4.9	2.88	288	150
PC	220	$\pm 10\%$	95	0.79	4.6	3.18	273	125
PC	270	$\pm 10\%$	100	0.79	4.2	3.50	260	120
PC	330	$\pm 10\%$	100	0.79	3.55	4.80	222	110
PC	390	$\pm 10\%$	100	0.79	3.45	5.44	209	105
PC	470	$\pm 10\%$	100	0.79	3.2	5.9	201	100
PC	560	$\pm 10\%$	95	0.79	2.9	6.3	194	90
PC	680	$\pm 10\%$	100	0.79	2.7	7.2	181	80
PC	820	$\pm 10\%$	90	0.79	2.5	8	172	70
PC	1000	$\pm 10\%$	100	0.79	2.35	12	141	65

*Incremental Current: The DC current required to cause a 5% reduction in the nominal inductance value.

MARKING

— Manufacturer data printed

ORDERING INFORMATION

PC MODEL	0.10 μ H INDUCTANCE VALUE	$\pm 10\%$ INDUCTANCE TOLERANCE
-------------	-------------------------------------	---------------------------------------



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.