



2mm ISOLATED POWER TPCM, TPCF SERIES

SPECIFICATIONS

For complete specifications see www.samtec.com?TPCM or www.samtec.com?TPCF

Insulator Material: Black Liquid Crystal Polymer
Terminal Material (TPCM): Phosphor Bronze
Contact Material (TPCF): Phosphor Bronze
Current Rating: Signal Pins: 3A @ 80°C ambient
 Power Pins: Testing Now!
Operating Temp Range: -65°C to +105°C with Tin; -65°C to +125°C with Gold
Max Processing Temp: 230°C for 60 seconds
Plating: Sn or Au over 50µ" (1,27µm) Ni
Impedance: 50Ω ±5% @ 170MHz
 50Ω ±20% @ 253MHz (system @ 50Ω)

TPCM - **1** **NO. POS. PER ROW** - **LEAD STYLE** - **PLATING OPTION** - **Q** - **POWER POSITIONS** - **BODY HEIGHT**

20, 30, 40, 50
= No. of positions per row + 2 x No. of power positions

Specify LEAD STYLE from chart

-G
= 20µ" (0,51µm) Gold on contact area, Gold flash on tail

-S
= 30µ" (0,76µm) Gold on contact area, Tin on tail

-T
= Tin

-4
= Four Banks

-8
= Eight Banks

"XXX"
= Body Height In inches (9,60mm) .378" Min.

LEAD STYLE	A (Max)	B
-02	(10,08) .397	(9,58) .377
-03	(14,10) .555	(13,59) .535
-05	(10,59) .417	(10,08) .397
-06	(14,61) .575	(14,10) .555
-09	(15,60) .614	(15,09) .594
-10	(17,60) .693	(17,09) .673
-11	(19,58) .771	(19,08) .751

TPCF - **1** **NO. POS. PER ROW** - **01** - **PLATING OPTION** - **Q** - **POWER POSITIONS**

20, 30, 40, 50
= No. of positions per row + 2 x No. of power positions

-L
= 10µ" (0,25µm) Gold on contact area, Tin on tail

-F
= Gold flash on contact area, Tin on tail

-4
= Four Banks

-8
= Eight Banks

Note: Some lengths, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM