



High Quality Data Cables - Molded and Totally Shielded for Noisy Environments

All our molded data cables are fully populated and wired straight-thru (1-1, 2-2, 3-3...) for various applications. A PVC jacket is used for flexibility and contains 26 AWG stranded conductors. A single foil shield runs over conductors while foil tape surrounds premold at connector ends. The final result is optimum shielding for noisy environments. Please ask for quantity and custom cable pricing.

9 Pin D-Subs - For Serial Connections and Other Applications. Fully Populated

CSM9MM-2.5	Shielded DB9	Male / Male	9	13.15	12.10	11.05
CSM9MM-5	Shielded DB9	Male / Male	9	13.75	12.65	11.55
CSM9MM-10	Shielded DB9	Male / Male	9	15.00	13.30	12.60
CSM9MM-15	Shielded DB9	Male / Male	9	16.25	14.95	13.65
CSM9MM-25	Shielded DB9	Male / Male	9	18.75	17.25	15.75
CSM9MM-50	Shielded DB9	Male / Male	9	25.00	23.00	21.00
CSM9MF-2.5	Shielded DB9	Male / Female	9	13.15	12.10	11.05
CSM9MF-5	Shielded DB9	Male / Female	9	13.75	12.65	11.55
CSM9MF-10	Shielded DB9	Male / Female	9	15.00	13.30	12.60
CSM9MF-15	Shielded DB9	Male / Female	9	16.25	14.95	13.65
CSM9MF-25	Shielded DB9	Male / Female	9	18.75	17.25	15.75
CSM9MF-50	Shielded DB9	Male / Female	9	25.00	23.00	21.00

High Density 15 Pin D-Sub Cables - Fully Populated and Completely Shielded

CSHD15MM-2.5	Shielded HD15	Male / Male	15	17.50	16.10	14.70
CSHD15MM-5	Shielded HD15	Male / Male	15	18.50	17.02	15.54
CSHD15MM-10	Shielded HD15	Male / Male	15	20.50	18.86	17.22
CSHD15MM-15	Shielded HD15	Male / Male	15	22.50	20.70	18.90
CSHD15MM-25	Shielded HD15	Male / Male	15	26.50	24.38	22.26
CSHD15MF-2.5	Shielded HD15	Male / Female	15	17.50	16.10	14.70
CSHD15MF-5	Shielded HD15	Male / Female	15	18.50	17.02	15.54
CSHD15MF-10	Shielded HD15	Male / Female	15	20.50	18.86	17.22
CSHD15MF-15	Shielded HD15	Male / Female	15	22.50	20.70	18.90
CSHD15MF-25	Shielded HD15	Male / Female	15	26.50	24.38	22.26

NOTE: Most monitor manufacturers recommend using premium grade VGA cables that utilize 75 ohm coaxial lines. See page 42

15 Pin D-Subs - For Various Applications. Shielded and Fully Populated

CSM15MM-2.5	Shielded DB15	Male / Male	15	17.50	16.10	14.70
CSM15MM-5	Shielded DB15	Male / Male	15	18.50	17.02	15.54
CSM15MM-10	Shielded DB15	Male / Male	15	20.50	18.86	17.22
CSM15MM-15	Shielded DB15	Male / Male	15	22.50	20.70	18.90
CSM15MM-25	Shielded DB15	Male / Male	15	26.50	24.38	22.26
CSM15MM-50	Shielded DB15	Male / Male	15	36.50	33.58	30.66
CSM15MF-2.5	Shielded DB15	Male / Female	15	17.50	16.10	14.70
CSM15MF-5	Shielded DB15	Male / Female	15	18.50	17.02	15.54
CSM15MF-10	Shielded DB15	Male / Female	15	20.50	18.86	17.22
CSM15MF-15	Shielded DB15	Male / Female	15	22.50	20.70	18.90
CSM15MF-25	Shielded DB15	Male / Female	15	26.50	24.38	22.26
CSM15MF-50	Shielded DB15	Male / Female	15	36.50	33.58	30.66

25 Pin D-Subs - For Serial and Parallel Applications. Shielded and Fully Populated

CSM25MM-2.5	Shielded DB25	Male / Male	25	21.00	19.32	17.64
CSM25MM-5	Shielded DB25	Male / Male	25	22.50	20.70	18.90
CSM25MM-10	Shielded DB25	Male / Male	25	25.50	23.46	21.42
CSM25MM-15	Shielded DB25	Male / Male	25	28.50	26.22	23.94
CSM25MM-25	Shielded DB25	Male / Male	25	34.50	31.74	28.98
CSM25MM-50	Shielded DB25	Male / Male	25	49.50	45.54	41.58
CSM25MF-2.5	Shielded DB25	Male / Female	25	21.00	19.32	17.64
CSM25MF-5	Shielded DB25	Male / Female	25	22.50	20.70	18.90
CSM25MF-10	Shielded DB25	Male / Female	25	25.50	23.46	21.42
CSM25MF-15	Shielded DB25	Male / Female	25	28.50	26.22	23.94
CSM25MF-25	Shielded DB25	Male / Female	25	34.50	31.74	28.98
CSM25MF-50	Shielded DB25	Male / Female	25	49.50	45.54	41.58

37 Pin D-Subs - For EIA449 and Other Applications. Shielded and Fully Populated

CSM37MM-2.5	Shielded DB37	Male / Male	37	39.00	35.83	32.76
CSM37MM-5	Shielded DB37	Male / Male	37	41.00	37.72	34.44
CSM37MM-10	Shielded DB37	Male / Male	37	45.00	41.40	37.80
CSM37MM-15	Shielded DB37	Male / Male	37	49.00	45.03	41.16
CSM37MM-25	Shielded DB37	Male / Male	37	57.00	52.44	47.88
CSM37MM-50	Shielded DB37	Male / Male	37	77.00	70.54	64.68
CSM37MF-2.5	Shielded DB37	Male / Female	37	39.00	35.83	32.76
CSM37MF-5	Shielded DB37	Male / Female	37	41.00	37.72	34.44
CSM37MF-10	Shielded DB37	Male / Female	37	45.00	41.40	37.80
CSM37MF-15	Shielded DB37	Male / Female	37	49.00	45.03	41.16
CSM37MF-25	Shielded DB37	Male / Female	37	57.00	52.44	47.88
CSM37MF-50	Shielded DB37	Male / Female	37	77.00	70.54	64.68

Order Toll Free: 800-343-1455

Web: <http://www.L-com.com>

8am - 6pm EASTERN STANDARD TIME



N. ANDOVER, MA 01845

24 Hour Fax Service: 978-689-9484

E-mail: sales@L-com.com

PRICES AND SPECIFICATIONS SUBJECT TO CHANGE.