

Stock thickness same as ring terminal of same size.

Vinyl Insulated Locking Fork—Expanded Insulation Support

Cat. No.	Bulk Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Wt./lbs. Bolt Hole	Per 1000	Dimensions			
							A	B	C	M
18RA-6FLX	—	100	22-16	.170	#6	5	.97	.25	.25	.81
18RA-8FLX	—	100	22-16	.170	#8	5	.97	.29	.25	.81
18RA-10FLX	RA2257-170	100/1M	22-16	.170	#10	5	.97	.29	.25	.81
14RB-6FLX	RB2207-200	100/1M	18-14	.200	#6	6	.97	.31	.27	.81
—	RB2217-200	1000	18-14	.200	#6	6	.97	.29	.27	.81
14RB-8FLX	RB2237-200	100/1M	18-14	.200	#8	6	.97	.31	.27	.81
14RB-10FLX	RB2257-200	100/1M	18-14	.200	#10	6	.97	.31	.27	.81
10RC-6FLX	RC2207-250	50/500	12-10	.250	#6	8	1.07	.31	.27	.91
10RC-8FLX	—	50	12-10	.250	#8	8	1.10	.37	.27	.91
10RC-10FLX	RC2227-250	50/500	12-10	.250	#10	8	1.10	.37	.27	.91
10RC-14FLX	—	50	12-10	.250	¼"	8	1.22	.50	.32	.96


U.L. Listed E-9809

Installing tools: ERG-2001, ERG-2003, WT145C, WT2000, WT112M, WT1455

Most standard bulk catalogue numbers can be put on Mylar Tape for reel fed applications (12050 tool and application dies). See page C61.

Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

Heat Shrinkable Locking Fork Terminals—Expanded Insulation Support



Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Bolt Hole	Wt./lbs Per 1000	Dimensions	
						A	B
RAS18-6FLX	100	22-18	.170	#6	5	1.350	.25
RAS18-8FLX	100	22-18	.170	#8	5	1.350	.29
RAS18-10FLX	100	22-18	.170	#10	5	1.350	.29
RBS14-6FLX	100	16-14	.200	#6	6	1.350	.25
RBS14-8FLX	100	16-14	.200	#8	6	1.350	.29
RBS14-10FLX	100	16-14	.200	#10	6	1.350	.29
RCS10-6FLX	50	12-10	.250	#6	8	1.350	.31
RCS10-8FLX	50	12-10	.250	#8	8	1.350	.37
RCS10-10FLX	50	12-10	.250	#10	8	1.350	.37
RCS10-14FLX	50	12-10	.250	¼"	8	1.350	.49

U.L. Listed E-9809

Installing tool: WT1255

Heat Shrinkable terminals not available on Mylar Tape.

For Mil Specs listing, please refer to page C73.