



FEMALE DISCONNECTS

Non-Insulated


- Sleeved Barrel  



RECOGNIZED




Non-Insulated

- Butted Seam 



CERTIFIED




PANDUIT® Part Number	Wire Range	Color Code	Max. Ins.	Dim. (In.)				Tab Size	Std. Pkg. Qty.	Std. Ctn. Qty.	Bulk Pkg. Qty.	Bulk Ctn. Qty.	Crimp Tools
				A	W								
D18-187-C	22-18	—	—	.58	.23			.187 x .032	100	500	1000	10,000	CT-100‡ CT-200‡ CT-1570‡
D18-188-C		—	—	.58	.23			.187 x .020	100	500	1000	10,000	
D18-250-C		—	—	—	.66	.30			.250 x .032	100	500	1000	
D14-187-C	16-14	—	—	.58	.23			.187 x .032	100	500	1000	10,000	CT-100 CT-200 CT-600 CT-1570
D14-188-C		—	—	.58	.23			.187 x .020	100	500	1000	10,000	
D14-250-C		—	—	—	.66	.30			.250 x .032	100	500	1000	
D10-250-L	12-10	—	—	.72	.30			.250 x .032	50	500	500	5000	CT-600‡ CT-1570‡
D18-188B-C	22-18	—	—	.56	.23			.187 x .020	100	500	1000	10,000	CT-100
D18-250B-C		—	—	.63	.30			.250 x .032	100	500	1000	10,000	
D14-188B-C	16-14	—	—	.56	.23			.187 x .020	100	500	1000	10,000	
D14-250B-C		—	—	—	.63	.30			.250 x .032	100	500	1000	

Order the number of pieces required in multiples of standard package quantities. L=50 pcs., C=100 pcs., D=500 pcs. and M=1000 pcs. ‡ UL and CSA approved tooling/product combinations. Prime items appear in **BOLD**.

RIGHT ANGLE FEMALE DISCONNECTS



Nylon Fully Pre-Insulated Funnel Entry

- Insulation Support
- Used in Limited Space Applications



Nylon Pre-Insulated Funnel Entry

- Insulation Support



PANDUIT Part Number	Wire Range	Color Code	Max. Ins.	Dim. (In.)				Tab Size	Std. Pkg. Qty.	Std. Ctn. Qty.	Bulk Pkg. Qty.	Bulk Ctn. Qty.	Crimp Tools
				A	H	W	X						
DNFR18-205FIB-C	22-18	Red	.178	.58	.21	.37	.60	.205/.187 x .032	100	1000	1000	6000	CT-300-1
DNFR18-206FIB-C			.178	.58	.21	.37	.60	.205/.187 x .020	100	1000	1000	6000	
DNFR18-250FIB-C			.178	.58	.21	.37	.60	.250 x .032	100	1000	1000	6000	
DNFR14-205FIB-C	16-14	Blue	.178	.58	.21	.37	.60	.205/.187 x .032	100	1000	1000	6000	CT-300-1
DNFR14-206FIB-C			.178	.58	.21	.37	.60	.205/.187 x .020	100	1000	1000	6000	
DNFR14-250FIB-C			.178	.58	.21	.37	.60	.250 x .032	100	1000	1000	6000	
DNFR18-205B-C	22-18	Red	.125	.78	.36	.20	.62	.205/.187 x .032	100	1000	1000	6000	CT-1525‡
DNFR18-206B-C			.125	.78	.36	.20	.62	.205/.187 x .020	100	1000	1000	6000	
DNFR18-250B-C			.125	.78	.36	.20	.62	.250 x .032	100	1000	1000	6000	
DNFR14-205B-C	16-14	Blue	.155	.78	.36	.20	.63	.205/.187 x .032	100	1000	1000	6000	CT-1525‡
DNFR14-206B-C			.155	.78	.36	.20	.63	.205/.187 x .020	100	1000	1000	6000	
DNFR14-250B-C			.155	.78	.36	.20	.63	.250 x .032	100	1000	1000	6000	

Order the number of pieces required in multiples of standard package quantities. C = 100 pcs., D = 500 pcs. and M = 1000 pcs. ‡ UL and CSA approved tooling/product combinations. Prime items appear in **BOLD**.