

FRED Modules

$$I_{FAV} = 75 - 582 \text{ A}$$

Type	V_{RRM} V	$I_{FAV} @ T_C$ $d=0.5$		I_{FRMS} T_{VJM} A	I_{FSM} 10 ms 45°C A	$V_F @ I_F$ max. $T_{VJ} = 125^\circ\text{C}$ V A		t_{rr} typ. $T_{VJ} = 25^\circ\text{C}$ ns	$I_{RM} @ -di/dt$ typ. $T_{VJ} = 100^\circ\text{C}$ A A/μs		R_{thJC} K/W	P_{tot} max. W	Fig. No.	Package style
Outline drawings on page 91-100														
MEO 550-02DA	200	582	75	822	4800	1.08	520	150	15	200	0.071	1750	29	Fig. 29 Weight 150 g
MEO 500-06DA	600	514	75	726		1.41	520	250	132	800		1750		
MEO 450-12DA	1200	453	75	640		1.76	520	450	165	800		1750		
MEK 75-12DA	1200	75	75	107	1200	1.85	100	250	33	200	0.45	280	27	Fig. 29 Weight 150 g
MEA 75-12DA	1200	75	75											
MEE 75-12DA	1200	75	75											
MEK 95-06DA	600	95	75	142	1200	1.36	100	250	21	200	0.45	280		Fig. 29 Weight 150 g
MEA 95-06DA	600	95	75											
MEE 95-06DA	600	95	75											
MEK 150-04DA	400	150	100	200	1200	1.4*	300	300	11	100	0.35	360		Fig. 30 Weight 150 g
MEK 350-02DA	200	356	75	503	2400	0.92	260	150	15	200	0.143	875	30	
MEK 300-06DA	600	304	75	430		1.19	260	250	66	400		875		
MEK 250-12DA	1200	260	75	367		1.54	260	450	83	400		875		
MEE 300-06DA	600	304	75	430	2400	1.19	260	250	66	400	0.143	875		Fig. 30 Weight 150 g
MEE 250-12DA	1200	260	75	367		1.54	260	450	83	400		875		
MEA 300-06DA	600	304	75	430	2400	1.19	260	250	66	400	0.143	875		
MEA 250-12DA	1200	260	75	367		1.54	260	450	83	400		875		
1 phase and 3 phase rectifiers with fast recovery epitaxial diodes (FRED); see also page 64														
$P_D \neq T_{VJM} = 150^\circ\text{C}$														
Diode connections for Fig. 27 (TO-240)														
Fig. 27 Weight = 90 g														
Diode connections for Fig. 29 and 30 (34 mm package)														

