

P-tec Corp.
 2405 Commerce Circle
 Alamosa Co. 81101
 www.p-tec.net

Tel:(800)688-0613
 Tel:(719) 589 3122
 Fax:(719) 589 3592
 sales@p-tec.net



PL16 Series 5mm (T1¾) LED

Features

- *Popular T1 3/4 Lens style with Flange
- *AlGaInP Ultra Bright Red Chip used
- *Narrow Viewing Angle
- *High Intensity
- *Ultra High Light Output
- *RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

| | |
|--|---------------------|
| Power Dissipation | 72mW |
| Reverse Voltage (<100µA)..... | 5.0V |
| Max Forward Current | 30mA |
| Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)..... | 100mA |
| Operating Temperature Range | -25°C to +85°C |
| Storage Temperature Range..... | -40°C to +100°C |
| Soldering Temperature (1.6mm below body)..... | 260°C for 5 seconds |

Electrical & Optical Characteristics at T_A = 25°C

| Part Number | Emitting Color | Chip Material | Dominant Wave Length | Peak Wave Length | Viewing Angle 2θ ½ | Forward Voltage @20mA (V) | | Luminous Intensity @20mA (mcd) | |
|------------------|----------------|---------------|----------------------|------------------|--------------------|---------------------------|-----|--------------------------------|-------|
| | | | | | | Typ | Max | Min | Typ |
| Water Clear Lens | | | nm | nm | Deg | | | | |
| PL16D-WCR28 | Red | AlInGaP | 630 | 639 | 20° | 1.9 | 2.4 | 429.0 | 800.0 |

All dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified. An epoxy meniscus may extend about 1mm down the leads.

