



Series 804 "Mighty Mouse" Push-Pull Quick-Disconnect

Series 804 Plug Connectors



Quick Disconnect These plugs snap securely into receptacle housings and release with a simple pull.

Two Keying Styles: A single master key provides fast mating in low-light situations, or specify three keys for more polarizing options.

Two Shell Styles: Integral platform for direct shield attachment using the *BAND-IT*® termination system, or an accessory thread for attaching a strain relief.

Series 804 Plug Connector

HOW TO ORDER

Sample Part Number


804-001

-06


M

9-19

S

Series	Shell Style	Shell Material / Finish	Shell Size- Insert Arrangement		Contact Type	Shell Key Position
 804-001 Plug with Banding Platform	-06 Plug	C Aluminum / Black Anodize	5-3 6-1 6-4 6-7 7-1 7-10 8-13 9-4 9-19 10-26 12-2 12-37 14-55 15-85	3 #23 Contacts 1 #16 Contact 4 #23 Contacts 7 #23 Contacts 1 #12 Contact 10 #23 Contacts 13 #23 Contacts 4 #16 Contacts 19 #23 Contacts 26 #23 Contacts 2 #12 Contacts 37 #23 Contacts 55 #23 Contacts 85 #23 Contacts	Standard #23 contacts accept #22 through #28 AWG wire. Use the following contact codes to specify these contacts: P Pin S Socket Special contacts for #26 to #30 AWG are also available. Use the following contact codes to specify these contacts: G Pin H Socket	Omit for Single Master Key A Pos. A (Normal) B Pos. B C Pos. C D Pos. D
		M Aluminum / Electroless Nickel NF Aluminum / Cadmium with Olive Drab Chromate ZN Aluminum / Zinc-Nickel with Olive Drab Chromate ZNU Aluminum / Zinc-Nickel with Black Chromate Z1 Stainless Steel / Passivated	#23 contacts are packaged with connectors. #16 and #12 contacts must be ordered separately.			

Series 804 Plug Connectors



DIMENSIONS									
Shell Size	Ø A		Ø B		Ø C		Ø D Max.		E Threads
	In.	mm.	In.	mm.	In.	mm.	In.	mm.	
5	.427	10.85	.246	6.25	.219	5.56	.250	6.35	.250-32 UNEF-2A
6	.495	12.57	.286	7.26	.282	7.16	.313	7.95	.3125-32 UNEF-2A
7	.575	14.61	.390	9.91	.351	8.92	.383	9.73	.4375-28 UNEF-2A
8	.614	15.60	.442	11.23	.398	10.11	.429	10.90	.5000-28 UNEF-2A
9	.670	17.02	.500	12.70	.454	11.53	.486	12.34	.5625-24 UNEF-2A
10	.745	18.92	.564	14.33	.529	13.44	.563	14.30	.6250-24 UNEF-2A
12	.865	21.97	.650	16.51	.646	16.41	.676	17.17	.6875-24 UNEF-2A
14	.985	25.02	.805	20.45	.768	19.51	.800	20.32	.9375-20 UNEF-2A
15	1.041	26.44	.850	21.59	.828	21.03	.860	21.84	.9375-20 UNEF-2A

SERIES 804 PLUG KEY POSITIONS			
	A°	B°	
A	150°	210°	
B	75°	210°	
C	95°	230°	
D	140°	275°	