


## Strip Block for Snap-in Mounting with up to 7 IEC Appliance Outlets F

**Description**

- Panel Mount:  
Snap-in version from front side
- 2 Functions:  
Module of 2 up to 7 outlets, Pin temperature 70 °C, Protection class I
- Solder terminals

**Characteristics**

- Qualified for use in equipment according IEC/EN 60950

**Other versions on request**

- Other panel thickness


**References****Weblinks**

[pdf](#), [General Product Information](#), [Approvals](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Store](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#), [Accessories](#)

**Technical Data**

Ratings IEC	10A / 250VAC; 50Hz
Ratings UL/CSA	15A / 250VAC; 60Hz
Dielectric Strength	> 2kVAC between L-N > 2kVAC between L/N-PE (1 min/50Hz)
Allowable Operation Temp.	-25 °C to 70 °C
Degree of Protection	from front side IP 30 acc. to IEC 60529
Protection Class	Suitable for appliances with protection class 1 acc. to IEC 61140
Terminal	Solder terminals
Panel Thickness s	Snap-in 1.5mm tolerance +0.0/-0.1
Material: Housing	Thermoplastic, black, UL 94V-0

Appliance Outlet	F acc. to IEC/EN 60320-2-2, UL 498 CSA C22.2 no. 42 (for cold conditions) pin-temperature 70 °C, 10A, Protection Class 1
------------------	---

**Dimensions**

## Variants

Panel Thickness [mm]	Connector	Length L1 [mm]	Length L2 [mm]	Order Number
1.5	2	51.2	48.3	0909.0001
1.5	3	75.2	72.3	0909.0011
1.5	4	99.2	96.3	0909.0021
1.5	5	123.2	120.3	0909.0031
1.5	6	147.2	144.4	0909.0041
1.5	7	171.2	168.4	0909.0051

Packaging unit 120 Pcs

## Accessories

## Description



[Cord retaining kits](#)  
Cord retaining strain relief

Flat head, Z	0888.0021
Countersunk, C	4700.0003

## Mating Inlets/Plugs

## Category / Description

[Interconnection CordOverview complete](#)



Interconnection Cord with IEC Plug E, Angled	0607
Interconnection Cord with IEC Plug E, Angled	0608
Interconnection Cord with IEC Plug E, Straight	0609
Interconnection Cord with IEC Plug G, Angled	607B
Interconnection Cord with IEC Plug G, Angled	608B

[Interconnection Cordfurther types to0909](#)

...

[PlugOverview complete](#)



IEC Plug E, Cord Connector (Rewireable), Straight, max. cable Diameter 8.5 mm	4732
IEC Plug E, Cord Connector (Rewireable), Angled, max. Cable Diameter 10 mm	4733
IEC Plug E, Cord Connector (Rewireable), Straight, max. Cable Diameter 10 mm	4735
IEC Plug E, Cord Connector (Rewireable), Angled, max. Cable Diameter 10 mm	4736
IEC Plug E, Cord Connector (Rewireable), Straight	9009

[Plugfurther types to0909](#)

...