

SELECTABLE FREQUENCY SYNTHESIZER

SURFACE MOUNT MODEL: FCPL-70

OPTIMIZED LOOP PARAMETERS


65 - 72 MHz

FEATURES:

- ▶ Exceptionally Low Phase Noise
- ▶ No Programming Required
- ▶ Lead Free - RoHS Compliant
- ▶ Patent Pending REL-PRO® Technology
- ▶ Small Size, Surface Mount




Phase Noise



SPECIFICATIONS (Rev. B 05/30/08)

Frequency	65 - 72 MHz		
Step Size	1 MHz		
Reference Input Frequency	10 MHz		
Reference Input Voltage	1 V p-p to 3.5 V p-p		
Bias Voltage	Vcc	V (Vdc)	I (mA Max.)
	PLL	+5	15
	VCO	+5	35
	Vtune	+5	35
	D0, D1, D2	0 V / +5V	
Output Power	+3 dBm ±2dB		
Spurious & Ref. Sideband	80 dB (Typ.)		
Harmonic Suppression	12 dB (Typ.)		
Output Impedance	50 Ohms (Nom.)		
Typical Phase Noise	Offset	Phase Noise	
	@ 1 kHz	-120 dBc/Hz	
	@ 10 kHz	-112 dBc/Hz	
	@ 100 kHz	-131 dBc/Hz	
Operating Temperature Range	-40 to +85 °C		

Package # 273LF



Binary Frequency Selection			
D2	D1	D0	Frequency (MHz)
0	0	0	65
0	0	1	66
0	1	0	67
0	1	1	68
1	0	0	69
1	1	1	70
1	0	1	71
1	1	0	72

This product is manufactured under one or more of the following patents: Approved: 5,180,810; 5,122,621; 5,390,346; 5,416,446; 5,630,754; 5,805,431; 6,325,623; 6,806,573; 7,088,189; 7,180,381; 7,185,591; 7,282,670; 7,283,642; 7,292,113
 Pending: 65/48,307; 60/501,371 & 65/581,756; 60/527,937 & 65/536,675; 60/263,481; 60/564,173; 60/580,083; 60/661,822; 60/605,579; EV3126A034; 11/258,768; 60/622,485 & 66/710,112; 10/607,325/607,369/1; 60/732,737




SELECTABLE FREQUENCY SYNTHESIZER

SURFACE MOUNT MODEL: FCPL-70


OPTIMIZED LOOP PARAMETERS

65 - 72 MHz

HARMONIC SUPPRESSION



REFERENCE SIDEBAND SUPPRESSION



PERFORMANCE PLOTS

This product is manufactured under one or more of the following patents: Approved: 5,180,810; 5,122,621; 5,390,346; 5,416,446; 5,630,754; 5,805,437; 6,325,623; 6,856,573; 7,088,189; 7,180,381; 7,185,591; 7,262,670; 7,263,642; 7,292,173
Pending: 6649,307; 60501371 & 66561796; 60527957 & 66538675; 60263481; 60564173; 60580083; 60661622; 60605791; EV31268034; 11,258,768; 60622485 & 66710319; 1060732560736901; 60732787

Copyright © 2006 Synergy Microwave Corporation
201 McLean Boulevard • Paterson, New Jersey 07504 • Tel: (973) 881-8800 • Fax: (973) 881-8361
E-Mail: sales@synergymw.com • World Wide Web: <http://www.synergymw.com>




SELECTABLE FREQUENCY SYNTHESIZER

SURFACE MOUNT MODEL: FCPL-70

OPTIMIZED LOOP PARAMETERS

65 - 72 MHz

CLOSE IN SPURIOUS SUPPRESSION



PERFORMANCE PLOTS

This product is manufactured under one or more of the following patents: Approved: 5,180,810; 5,122,621; 5,390,346; 5,416,446; 5,630,754; 5,805,431; 6,325,623; 6,856,573; 7,088,189; 7,180,381; 7,185,591; 7,262,670; 7,265,642; 7,292,113
Pending: 66/48,307; 60/501,371 & 66/561,796; 60/527,957 & 66/538,675; 60/563,481; 60/564,173; 60/580,083; 60/601,822; 60/605,791; EV31268034;
RU258768; 60/622,485 & 66/710,219; RU60732560736901; 60/732787

Copyright © 2006 Synergy Microwave Corporation
201 McLean Boulevard • Paterson, New Jersey 07504 • Tel: (973) 881-8800 • Fax: (973) 881-8361
E-Mail: sales@synergymw.com • World Wide Web: <http://www.synergymw.com>

