

RF AMPLIFIER

MODEL *TR3096*

Available as: TR3096, 4 Pin TO-8B (T8)
 RN3096, 4 Pin Surface Mount (SM19)
 BR3096, Connectorized Housing (H2)

Preliminary

Features

- High Gain: 25 dB Typical
- Operating Temp. - 55 °C to + 85 °C
- Environmental Screening Available
- Phase Matched to a Standard Unit

Typical Intermodulation Performance at 25 ° C

Second Order Harmonic Intercept Point +37 dBm (Typ.)
 Second Order Two Tone Intercept Point +32 dBm (Typ.)
 Third Order Two Tone Intercept Point +24 dBm (Typ.)

Specifications


CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = -55 °C to +85 °C
Frequency	700-1300 MHz	700-1300 MHz
Gain (dB)	25	23 Min.
Power @ 1 dB Comp. (dBm)	+24	+22 Min.
Gain Flatness (dB)	-	+/- 0.5 Max.
VSWR In	1.5:1	1.8:1 Max.
Out	1.5:1	1.8:1 Max.
Noise Figure (dB)	4.0	6.0 Max.
Power Vdc	+15	+15
mA	120	150 Max.
Gain Variation (dB)	-	+/-1.0
Phase Matched Against a Reference Unit (deg.)	-	+/-5.0

Maximum Ratings

Ambient Operating Temperature -55°C to + 100 °C
 Storage Temperature -62°C to + 125 °C
 Case Temperature + 125 °C
 DC Voltage + 18 Volts
 Continuous RF Input Power + 13 dBm
 Short Term RF Input Power 50 Milliwatts (1 Minute Max.)
 Maximum Peak Power 0.5 Watt (3 µsec Max.)

Note: Care should always be taken to effectively ground the case of each unit.

Typical Performance Data



Legend ——— + 25 °C - - - - + 85 °C ······ -55 °C



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532

02/14/05

www.spectrummicrowave.com Spectrum Microwave (Europe) · 2707 Black Lake Place · Philadelphia, Pa. 19154 · PH (215) 464-4000 · Fax (215) 464-4001