

## Surface mount diode

## Standard Avalanche Diodes

### GLA 1A ... GLA 1M

**Forward Current: 1 A**

**Reverse Voltage: 50 to 1000 V**

## Features

- Max. solder temperature: 260°C
- Plastic material has UL classification 94V-0
- white ring denotes "cathode" and "Standard Avalanche family"
- colored ring denotes "repetitive peak reverse voltage"

## Mechanical Data

- Plastic case: MiniMelf / SOD-80 / DO-213AA
- Weight approx.: 0,04 g
- Terminals: plated terminals solderable per MIL-STD-750
- Mounting position: any
- Standard packaging: 10000, 2500 pieces per reel

1) Max. temperature of the terminals  $T_T = 75^\circ\text{C}$

2)  $I_F = 1 \text{ A}$ ,  $T_J = 25^\circ\text{C}$

3)  $T_A = 25^\circ\text{C}$

4) Mounted on P.C. board with 25 mm<sup>2</sup> copper pads at each terminal

Type	Polarity color band	Repetitive peak reverse voltage	Surge peak reverse voltage	Maximum forward voltage $T_j = 25^\circ\text{C}$ $I_F = 1 \text{ A}$	Maximum reverse recovery time $I_F = -1 \text{ A}$ $I_R = -1 \text{ A}$ $I_{RR} = -1 \text{ A}$ $t_{rr}$ ns
		$V_{RRM}$ V	$V_{RSM}$ V	$V_F^{(2)}$ V	
GLA 1A	gray	50	50	1,2	-
GLA 1B	red	100	100	1,2	-
GLA 1D	orange	200	200	1,2	-
GLA 1G	yellow	400	400	1,2	-
GLA 1J	green	600	600	1,2	-
GLA 1K	blue	800	800	1,2	-
GLA 1M	violet	1000	1000	1,2	-

## Absolute Maximum Ratings


$T_A = 25^\circ\text{C}$ , unless otherwise specified

Symbol	Conditions	Values	Units
$I_{FAV}$	Max. averaged fwd. current, R-load, $T_T = 75^\circ\text{C}$ <sup>1)</sup>	1	A
$I_{FRM}$	Repetitive peak forward current $f > \text{Hz}$	-	A
$I_{FSM}$	Peak fwd. surge current 50 Hz half sinus-wave <sup>3)</sup>	25	A
$I_{Pt}$	Rating for fusing, $t < 10 \text{ ms}$ <sup>3)</sup>	3,1	A <sup>2</sup> s
$R_{thA}$	Max. thermal resistance junction to ambient <sup>4)</sup>	150	K/W
$R_{thT}$	Max. thermal resistance junction to terminals	60	K/W
$T_j$	Operating junction temperature	- 50 ... + 175	°C
$T_s$	Storage temperature	- 50 ... + 175	°C

## Characteristics

$T_A = 25^\circ\text{C}$ , unless otherwise specified

Symbol	Conditions	Values	Units
$I_R$	Maximum leakage current, $T_j = 25^\circ\text{C}$ ; $V_R = V_{RRM}$ $T_j = ?^\circ\text{C}$ ; $V_R = V_{RRM}$	<1	µA
$C_J$	Typical junction capacitance (at MHz and applied reverse voltage of V)	-	pF
$Q_{rr}$	Reverse recovery charge ( $U_R = V$ ; $I_F = A$ ; $dI_F/dt = A/\text{ms}$ )	-	µC
$E_{RSM}$	Non repetitive peak reverse avalanche energy ( $I_R = 1 \text{ mA}$ ; $T_j = 25^\circ\text{C}$ ; inductive load switched off)	20	mJ



# GLA 1A ... GLA 1M




Fig. 1 Forward characteristics (typical values)




Fig. 2 Rated forward current vs. temp. of the terminals<sup>4)</sup>