



CIRCUIT: SP2T
CONTACT CONFIGURATION

- NOTES:
1. ALL DIMENSIONS IN MM
 2. TERM. NOS. FOR REF ONLY
 3. RATING: DC 4V, 0.3A
 4. OPERATING FORCE: 200±100gf
 5. CONTACT RESISTANCE: 70m Ohms Max.
 6. INSULATION RESISTANCE: DC 100V-100M Ohms Min
 7. WITHSTAND VOLTAGE: AC 100V-1MINUTE
 8. OPERATING TEMP: -20°C to +70°C
 9. LIFE: 10,000 Cycles min.

ADD NOTE 8 & 9

| | | | |
|------|---------|-------------------|------|
| E | 12175 | ADD NOTE 8 & 9 | CJB |
| D | 11271 | REMOVED DIMENSION | CJB |
| REV. | ECN No. | DESCRIPTION | DATE |
| | | CHKD | |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E-SWITCH®

EG 1257

| | | | | | | | | | |
|-------|------|------|---------|----|----|-----|---------|-----|---|
| SCALE | 10:1 | DATE | 8/27/97 | DR | MM | DWG | P112221 | REV | E |
|-------|------|------|---------|----|----|-----|---------|-----|---|